


DEFGHIJKLMNOPQRSTUVWXYZ0123456789 ABCDEFGHIJKLMNOPQRSTUVWXYZ0123456789

Stephen J.Singel
Labanda Sinpat Abarress
Tendar,BSF
URANGLE



LSB
Funtres Solber Netener

26 March 2002



Jonathan Q.Maderia

Inpert Mampem Abaress
2343 Stantin Dawer Lank
Benhibe,SDF

Mr.Maderia:

Nam liber tempor cum soluta nobis eleifend option cogue nihil consequat, velillum. Dolore eu zril feugiat nulla facilisis at vero eros accumsan et iustó odio dignissim qui blandit praesent lutatum ril lobortis nisl ut aliquip exea commodo consequat. Duis autem vel eum iriure dolor in hendreritin vulputate velit esse molestie tincidunt ut laoreet dolore magna aliquam erat volutpat. Ut wisi enim ad minim vêniam, quis nostrud exerci tation ullamcorper suscipit lotis nisl ut aliquip ex ea commodo con-sequat. Lorem ipsum dolor sit.

Amet,consectetuer adipiscing elit, sêd diam nonummy nibh veniam, recneps adipiscing elit, sed diam nonummy nibtil laoreet dolore magmana aliam erat volutpat. Ut wisi enim minim veniam, quisient nostrud. Soluta nobis eleifend optn cogue nihil imerdiet domg id quod mzim plerat facer posim aum. Lorem ipsum dolor sit amet, consectuer. Duis autem vel eum iriure dolor in hendreritin vulputate velit esse ea commodo molestie.





L* / Y (absolute)	18,0/2,5	23,1/3,8	28,2/5,5	33,3/7,7	38,5/10,3	43,6/13,6	48,8/17,4	54,0/21,9	59,1/27,2	64,3/33,2	69,5/40,0	74,7/47,8	79,8/56,5	85,0/66,1	90,2/76,8	95,4/88,6
No. and Hex code	00,F	01,E	02,D	03,C	04,B	05,A	06,9	07,8	08,7	09,6	10,5	11,4	12,3	13,2	14,1	15,0
I* _{CIE LAB,r} (relative) w*	0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000


Stephen J.Singel
Demperta Aminerimum
Labanda Sinpat Abarress

SJS:dwg



170 mm +/- 1%









www.ps.bam.de/CE98/10L/L98E02FP.PS/.PDF; linearized output
F: Output Linearization (OL) data CE98/10L/L98E02FP.DAT in File (F)




Radial grating (Siemens-star) N-W



Radial grating (Siemens-star) W-N




Radial grating (Siemens-star) N-Z




Radial grating (Siemens-star) W-Z

Picture C1: Radial gratings (Siemens-stars) N-W, W-N, N-Z and W-Z; PS operator: `www* setrgbcolor`



Picture C2: 5 visual equidistant L^* -grey steps + N_0 + W_1 ; PS operator: `www* setrgbcolor`




Picture C3: 16 visual equidistant L^* -grey steps; PS operator: `www* setrgbcolor`




ISO/IEC 19752-test chart, form 3
Proposal by DIN NI28

2003-05-01, name1 input: `www* setrgbcolor`
Test device type: name2 output: `olv*/www* setrgbcolor`


Form: 3, Serie: 1, Page: 4




Picture C4: Landolt-rings W-N; PS operator: `www* setrgbcolor`



Picture C5: Line raster under 45° (or 135°); PS operator: `www* setrgbcolor`




Picture C6: Line raster under 90° (or 0°); Use of the PS operator `www* setrgbcolor`



-See for similar files: <http://www.ps.bam.de/CE98/>
 Technical information: <http://www.ps.bam.de/197>

Version 2.0, io=3,3; iORS; oORS, CIELAB

www.ps.bam.de/CE98/10L/L98E03FP.PS/.PDF; linearized output
F: Output Linearization (OL) data CE98/10L/L98E03FP.DAT in File (F)
224 mm (+/- 1 mm)



Form 4: Grey areas 14 mm x 14 mm for yield or emission: 10% geometrical and 5% visual area coverage; PS operator used: `www* setrgbcolor`

ISO/IEC 19752-test chart, form 4
Proposal by DIN NI28

```
2003-05-01, name1      input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor
```

Form: 4, Serie: 1, Page: 5

BAM registration: 20030501-CE98/10/L198FE03FP.PS.PDF BAM material: code=rha4ta
application for yield test of monochromatic printers

170 mm (+/- 1 mm)

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; ooRS, CIELAB

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E05FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers

Grey Page

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E06FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers

White Page

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E07FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers

Black Page

Form 8: Black area 150 mm x 230 mm and rectangles 10 mm x 10 mm for yield or emission; PS operator used: www* setrgbcolor

Form: 8, Serie: 1, Page: 9

ISO/IEC 19752-test chart, form 8
Proposal by DIN NI28

2003-05-01, name1 input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor

AB

BAM material: code=rh4ta
natic printers

Fb

1r

Form 9: Grey rectangles 115 mm x 14.4 mm for yield or emission; PS operator used: `www* setrgbcolor`


ISO/IEC 19752-test chart, form 9
Proposal by DIN NI28

2003-05-01, name1 input: *www* setrgbcolor*
Test device type: name2 output: *olv*/www* setrgbcolor*

Form: 9, Serie: 1, Page: 10

DEF GHIJ KLMNOPQRSTUVWXYZ0123456789 ABCDEFGHIJ KLMNOPQRSTUVWXYZ0123456789

Stephen J.Singel
Labanda Sinpat Abarress
Tendar,BSF
URANGLE



LSB
Funtres Solber Netener

26 March 2002



Jonathan Q.Maderia

Inpert Mampem Abaress
2343 Stantin Dawer Lank
Benhibe,SDF

Mr.Maderia:

Nam liber tempor cum soluta nobis eleifend option cogue nihil consequat, velillum. Dolore eu zril feugiat nulla facilisis at vero eros accumsan et iustó odio dignissim qui blandit praesent lutatum ril lobortis nisl ut aliquip exea commodo consequat. Duis autem vel eum iriure dolor in hendreritin vulputate velit esse molestie tincidunt ut laoreet dolore magna aliquam erat volutpat. Ut wisi enim ad minim vêniam, quis nostrud exerci tation ullamcorper suscipit lotis nisl ut aliquip ex ea commodo con-sequat. Lorem ipsum dolor sit.

Amet,consectetuer adipiscing elit, sêd diam nonummy nibh veniam, recneps adipiscing elit, sed diam nonummy nibtil laoreet dolore magmana aliam erat volutpat. Ut wisi enim minim veniam, quisient nostrud. Soluta nobis eleifend optn cogue nihil imerdiet domg id quod mzim plerat facer posim aum. Lorem ipsm dolor sit amet, consectuer. Duis autem vel eum iriure dolor in hendreritin vulputate velit esse ea commodo molestie.





L* / Y (absolute)	18,0/ 2,5	23,1/ 3,8	28,2/ 5,5	33,3/ 7,7	38,5/10,3	43,6/13,6	48,8/17,4	54,0/21,9	59,1/27,2	64,3/33,2	69,5/40,0	74,7/47,8	79,8/56,5	85,0/66,1	90,2/76,8	95,4/88,6
No. and Hex code	00,F	01,E	02,D	03,C	04,B	05,A	06,9	07,8	08,7	09,6	10,5	11,4	12,3	13,2	14,1	15,0
I* CIELAB,r (relative)	w* 0,000	0,067	0,133	0,200	0,267	0,333	0,400	0,467	0,533	0,600	0,667	0,733	0,800	0,867	0,933	1,000


Stephen J.Singel
Demperta Aminerimum
Labanda Sinpat Abarress

SJS:dwg



170 mm +/- 1%









www.ps.bam.de/CE98/10L/L98E02FP.PS/.PDF; linearized output
F: Output Linearization (OL) data CE98/10L/L98E02FP.DAT in File (F)




Radial grating (Siemens-star) N-W



Radial grating (Siemens-star) W-N




Radial grating (Siemens-star) N-Z




Radial grating (Siemens-star) W-Z

Picture C1: Radial gratings (Siemens-stars) N-W, W-N, N-Z and W-Z; PS operator: `www* setrgbcolor`



Picture C2: 5 visual equidistant L^* -grey steps + N_0 + W_1 ; PS operator: `www* setrgbcolor`



Picture C3: 16 visual equidistant L^* -grey steps; PS operator: `www* setrgbcolor`



ISO/IEC 19752-test chart, form 3
Proposal by DIN NI28

2003-05-01, name1

Test device type: name2


input: `www* setrgbcolor`

output: `olv*/www* setrgbcolor`


Form: 3,

Serie: 2,


Page: 4




Picture C4: Landolt-rings W-N; PS operator: `www* setrgbcolor`



Picture C5: Line raster under 45° (or 135°); PS operator: `www* setrgbcolor`




Picture C6: Line raster under 90° (or 0°); Use of the PS operator `www* setrgbcolor`



Version 2.0, io=3,3; iORS; oORS, CIELAB

ISO/IEC 19752-test chart, form 4
Proposal by DIN NI28

```
2003-05-01, name1      input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor
```



Form 4: Grey areas 14 mm x 14 mm for yield or emission: 10% geometrical and 5% visual area coverage; PS operator used: `www* setrgbcolor`

Form: 4, Serie: 2, Page: 5

BAM registration: 20030501-CE98/10/L98FE03FP.PS.PDF BAM material: code=rha4ta
application for yield test of monochromatic printers

170 mm (+/- 1 mm)

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E05FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers

Grey Page

Form 6: Grey area 150 mm x 230 mm and rectangles 10 mm x 10 mm for yield or emission; PS operator used: www* setrgbcolor

Form: 6, Serie: 2, Page: 7

ISO/IEC 19752-test chart, form 6
Proposal by DIN NI28

2003-05-01, name1 input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor

White Page

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E07FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers

Black Page

Form 8: Black area 150 mm x 230 mm and rectangles 10 mm x 10 mm for yield or emission; PS operator used: www* setrgbcolor

ISO/IEC 19752-test chart, form 8
Proposal by DIN NI28


2003-05-01, name1 input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor

Form: 8, Serie: 2, Page: 9

See for similar files: <http://www.ps.bam.de/CE98/>
Technical information: <http://www.ps.bam.de/19752>

Version 2.0, io=3,3; iORS; oORS, CIELAB

BAM registration: 20030501-CE98/10L/L98E08FP.PS/.PDF BAM material: code=rh4ta
application for yield test of monochromatic printers



Form 9: Grey rectangles 115 mm x 14.4 mm for yield or emission; PS operator used: www* setrgbcolor

ISO/IEC 19752-test chart, form 9
Proposal by DIN NI28

2003-05-01, name1 input: www* setrgbcolor
Test device type: name2 output: olv*/www* setrgbcolor

Form: 9, Serie: 2, Page: 10