www.ps.bam.de/FE98/10L/L98E04SP.PS/.PDF;
S: Output Linearization (OL) data FE98/10L/L98E04SP.DAT in Distiller Startup (S) Directory

Picture D1: Flower motif, 14 CIE-test colours and 2 + 16 grey steps (nf); PS operators *settransfer, 4 colorimage*



Picture D2: Radial gratings ***W-O, W-L, W-V, W-N,*** and ***W-Z***; PS operator *cmy0* setcmykcolor (only)*



Picture D3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator *cmy0* setcmykcolor (only)*



Picture D4: 16 equidistant steps ***W-O, W-L, W-V*** and ***W-N***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D5: Script and Landolt-rings ***N, O, L*** and ***V***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D6: Landolt-rings ***W-O*** and ***W-L***; Use of PS operator *cmy0* setcmykcolor* (only)



Picture D7: Landolt-rings ***W-V*** and ***W-N***; Use of PS operator *cmy0* setcmykcolor* (only)

See for similar files: http://www.ps.bam.de/FE98/
Information and Order: http://www.ps.bam.de Version 2.0, io=2,2?

BAM registration: 20030101-FE98/10L/L98E04SP.PS/.PDF BAM material: code=rha4ta
application for monitors (Yr=2.5) and printers

Fig. D1 to D7 of ISO/IEC-test chart 4;

ISO/IEC 15775 and input: *cmy0* setcmykcolor (only)*
DIS ISO/IEC 19839-X; output: *Startup (S) data dependend*