

Picture C1: Radial gratings (Siemens-stars) *N-W*, *W-N*, *N-Z* and *W-Z*; PS oper.: *w*lin 1.0 exp setgray*



Picture C4: Landolt-rings *W-N*; PS operator: *w*lin 1.0 exp setgray*



Picture C5: Line raster under 45° (or 135°); PS operator: *w*lin 1.0 exp setgray*



Picture C2: 5 visual equidistant *L**-grey steps + *N0* + *W1*; PS operator: *w*lin 1.0 exp setgray*



Picture C6: Line raster under 90° (or 0°); PS operator: *w*lin 1.0 exp setgray*



Picture C3: 16 visual equidistant *L**-grey steps; PS operator: *w*lin 1.0 exp setgray*; use file www.bam.de/KE87/10D/D87E00FA.PS or /D87E00FP.PS/.PDF for DPS or PDF systems to complete the figure

See for similar files: http://www.ps.bam.de/JE87/
Information and Order: http://www.ps.bam.de Version 2.0, io=1,0; iLRS; oLRS, CIEXYZ

BAM registration: 20031201-JE87/D87E00F1.PS/.TXT
Top part of page: application for monitors, Yr=7,5, XYZ
BAM material: code=rha4a

ISO/IEC-test chart no. 3D according to ISO/IEC 15775 and DIS ISO/IEC 19839-X; input: *w*lin 1.0 exp setgray* output: *cmy0* / 000n* setcmykcolor*