

www.ps.bam.de/KE89/B89E00F1.PS/.TXT; linearized output


F: Output Linearization (OL) data KE89/B89E00F1.DAT in File (F)

See for similar files: <http://www.ps.bam.de/KE89/>  
Information and Order: <http://www.ps.bam.de>

Version 2.0, io=3,0; iLRS; oLRS; cIE XYZ

BAM registration: 20031201-KE89/B89E00F1.PS/.TXT  
Bottom part of page: application for monitors, Y1=2.5, XY2

BAM material: code=thata



Picture C3: 16 visual equidistant  $L^*$ -grey steps; PS operator: [www\\*lin 1.0 exp setrgbcolor](http://www.lin1.0.exp.setrgbcolor); use file [www.bam.de/KE89/10B/B89E00FA.PS](http://www.bam.de/KE89/10B/B89E00FA.PS) or [/B89E00FP.PS](http://B89E00FP.PS) for DPS or PDF systems to complete the figure

ISO/IEC-test chart no. 3B according to

ISO/IEC 15775 and  
DIS ISO/IEC 19839-X;

input: [www\\*lin 1.0 exp setrgbcolor](http://www.lin1.0.exp.setrgbcolor)  
output:  $cmY0^*/1000n^*setcmykcolor$