

Siehe ähnliche Dateien: <http://www.ps.bam.de/LG19/LG19.HTM>
Information, Bestellung: <http://www.ps.bam.de> Version 2.0, io=0,0; iTLS; oTLS, CIELAB

	A	B	C	D	E	F	G	H	I	J	K	L	M	N	O	P	Q	Benutzte Koordinate
01																		Umfeld Infeld
02																		C $LAB^*_{\text{TLS00}} 011^*$
03																		$LAB^*_{\text{TLS00}} 01v^*$
04																		M $LAB^*_{\text{TLS00}} 111^*$
05																		$LAB^*_{\text{TLS00}} 00v^*$
06																		Y $LAB^*_{\text{TLS00}} 11v^*$
07																		$LAB^*_{\text{TLS00}} 010^*$
08																		O $LAB^*_{\text{TLS00}} 11v^*$
09																		$LAB^*_{\text{TLS00}} 000^*$
10																		L $LAB^*_{\text{TLS00}} 01v^*$
11																		$LAB^*_{\text{TLS00}} 010^*$
12																		$LAB^*_{\text{TLS00}} 011^*$
13																		V $LAB^*_{\text{TLS00}} 00v^*$
14																		$LAB^*_{\text{TLS00}} 00v^*$
																		N/W $LAB^*_{\text{TLS00}} 01v^*$
																		$LAB^*_{\text{TLS00}} w^*$

16 gleichabständige CIELAB-Stufen: C-W, C-N, M-W, M-N, Y-W, Y-N, O-W, O-N, L-W, L-N, V-W, V-N, N-W, W-N und 14 CIE-Testfarben (links)

Prüfvorlage LG19: CIELAB-Stufen ISO/IEC 15775
Bunt-Weiß, Bunt-Schwarz, Schwarz-Weiß

Eingabe ,TLS00,TLS00: $LAB^* \text{ setcolor (2x)}$
Ausgabe ,TLS00: $cmY0^* / 000n^* \text{ setcmykcolor}$