

i	LAB*ref		l*out		LAB*out		LAB*out/c-ref			ΔE*	Intended output S2
1	18.0	0.0	0.0	0.0	18.0	0.0	0.0	0.0	0.0	0.01	Specification according to
2	23.16	0.0	0.0	0.07	23.2	0.0	0.0	0.04	0.0	0.04	ISO/IEC 15775:1999 Annex G
3	28.32	0.0	0.0	0.13	28.3	0.0	0.0	-0.01	0.0	0.02	and DIN 33866>1:2000 Annex G
4	33.48	0.0	0.0	0.2	33.5	0.0	0.0	0.02	0.0	0.02	
5	38.64	0.0	0.0	0.27	38.6	0.0	0.0	-0.03	0.0	0.04	
6	43.8	0.0	0.0	0.33	43.8	0.0	0.0	0.0	0.0	0.01	
7	48.96	0.0	0.0	0.4	49.0	0.0	0.0	0.04	0.0	0.04	
8	54.12	0.0	0.0	0.47	54.1	0.0	0.0	-0.01	0.0	0.02	
9	59.28	0.0	0.0	0.53	59.3	0.0	0.0	0.02	0.0	0.02	
10	64.44	0.0	0.0	0.6	64.4	0.0	0.0	-0.03	0.0	0.04	
11	69.6	0.0	0.0	0.67	69.6	0.0	0.0	0.0	0.0	0.01	
12	74.76	0.0	0.0	0.73	74.8	0.0	0.0	0.04	0.0	0.04	
13	79.92	0.0	0.0	0.8	79.9	0.0	0.0	-0.01	0.0	0.02	
14	85.08	0.0	0.0	0.87	85.1	0.0	0.0	0.02	0.0	0.02	
15	90.24	0.0	0.0	0.93	90.2	0.0	0.0	-0.03	0.0	0.04	Mean lightness difference (16 steps)
16	95.4	0.0	0.0	1.0	95.4	0.0	0.0	0.0	0.0	0.01	ΔE* _{CIELAB} = 0.0
17	18.0	0.0	0.0	0.0	18.0	0.0	0.0	0.0	0.0	0.01	
18	37.35	0.0	0.0	0.25	37.32	0.0	0.0	-0.02	0.0	0.03	
19	56.7	0.0	0.0	0.5	56.7	0.0	0.0	0.0	0.0	0.01	
20	76.05	0.0	0.0	0.75	76.08	0.0	0.0	0.03	0.0	0.03	Mean lightness difference (5 steps)
21	95.4	0.0	0.0	1.0	95.4	0.0	0.0	0.0	0.0	0.01	ΔL* _{CIELAB} = 0.0
Mean colour reproduction index:										R* _{ab,m} = 100	