

Documentation of assessor colour vision properties for visual assessment

The assessor has normal colour vision according to one test:	underline Yes/No
either according to DIN 6160 with Anomaloskop of <i>Nagel</i>	underline Yes/unknown
or with test charts using colour points according to <i>Ishihara</i>	underline Yes/unknown
or tested with, please specify:	underline Yes/unknown

Only for display (monitor, data projector) output:

Office workplace illumination is daylight (clouded/north sky)	underline Yes/No
PDF-file output with www.ps.bam.de/XE75/10L/L75E00NP.PDF	underline Yes/No
Comparison of contrast range of 16 steps F to 0 with test chart no. 3 of DIN 33866-1	
give contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0)	
<i>Remark: In daylighted offices the contrast range is in many cases:</i>	
<i>on paper between: >F:0 (highly glossy), F:0 (silk glossy) and E:0 (matte)</i>	
<i>on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)</i>	

Only for optional colorimetric specification with PDF/PS file output

PDF-File: either www.ps.bam.de/XE27/10L/L27E00NP.PDF	underline Yes/No
or www.ps.bam.de/XE27/10P/P27E00NP.PDF	or underline Yes/No
PS-File: either www.ps.bam.de/XE27/10L/L27E00NA.PS	or underline Yes/No
or www.ps.bam.de/XE27/10P/P27E00NA.PS	or underline Yes/No

colour measurement and specification for:

CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry:	underline Yes/No
If No, please give other parameters:	

Colorimetric specification with PS file for colours in the columns A to T

Exchange of CIELAB data in file www.ps.bam.de/XE30/10L/L30E00NP.PS and transfer of the PS-file L30E00NP.PS in PDF-file L30E00NP.PDF	underline Yes/No
If No, please describe other method:	