

Documentation of assessor colour vision properties for visual assessment

| | |
|--|-------------------------|
| The assessor has normal colour vision according to one test: | underline Yes/No |
| either according to DIN 6160 with Anomaloskop of <i>Nagel</i> | underline Yes/unknown |
| or with test charts using colour points according to <i>Ishihara</i> | underline Yes/unknown |
| or tested with, please specify: | underline Yes/unknown |

Only for display (monitor, data projector) output:

| | |
|---|------------------|
| Office workplace illumination is daylight (clouded/north sky) | underline Yes/No |
| PDF-file output with www.ps.bam.de/XE75/10L/L75E00NP.PDF | underline Yes/No |
| Comparison of contrast range of 16 steps F to 0 with test chart no. 3 of DIN 33866-1 | |
| give contrast range: (>F:0) (F:0) (E:0) (D:0) (C:0) (A:0) (9:0) (7:0) (5:0) (3:0) (<3:0) | |

Remark: In daylighted offices the contrast range is in many cases:
on paper between: >F:0 (highly glossy), F:0 (silk glossy) and E:0 (matte)
on display between: >F:0 and E:0 (monitor), D:0 and 3:0 (data projector)

Only for optional colorimetric specification with PDF/PS file output

| | |
|--|---------------------|
| PDF-File: either www.ps.bam.de/XE27/10L/L27E00NP.PDF | underline Yes/No |
| or www.ps.bam.de/XE27/10P/P27E00NP.PDF | or underline Yes/No |
| PS-File: either www.ps.bam.de/XE27/10L/L27E00NA.PS | or underline Yes/No |
| or www.ps.bam.de/XE27/10P/P27E00NA.PS | or underline Yes/No |

colour measurement and specification for:

| | |
|--|------------------|
| CIE standard illuminant D65, 2 degree observer, CIE 45/0 geometry: | underline Yes/No |
| If No, please give other parameters: | |

Colorimetric specification with PS file for colours in the columns A to T

| | |
|---|------------------|
| Exchange of CIELAB data in file www.ps.bam.de/XE30/10L/L30E00NP.PS and transfer of the PS-file L30E00NP.PS in PDF-file L30E00NP.PDF | underline Yes/No |
| If No, please describe other method: | |