T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c−ref			ΔH*	ΔE*
M	1	38.7	79.2	−34.7	336	38.7	79.2	−34.7	336	0.0	0.0	0.0	0.0	0.0
	2	42.0	74.3	−32.5	336	43.2	75.8	−35.0	335	1.2	1.6	−2.4	2.9	3.1
	3	45.4	69.3	−30.4	336	48.1	70.5	−34.0	334	2.6	1.2	−3.5	3.8	4.7
	4	48.8	64.4	−28.2	336	52.5	64.8	−32.4	333	3.7	0.5	−4.1	4.2	5.6
	5	52.2	59.4	−26.0	336	56.7	58.8	−30.6	332	4.5	−0.5	−4.5	4.6	6.5
	6	55.6	54.5	−23.8	336	60.1	53.8	−28.9	332	4.5	−0.5	−5.0	5.1	6.8
	7	58.9	49.5	−21.7	336	63.4	48.7	−26.8	331	4.5	−0.7	−5.0	5.2	6.9
	8	62.3	44.6	−19.5	336	67.5	42.5	−23.9	331	5.2	−1.9	−4.3	4.9	7.1
	9	65.7	39.6	−17.3	336	71.2	36.7	−21.2	330	5.5	−2.8	−3.8	4.9	7.4
	10	69.1	34.6	−15.1	336	75.0	30.7	−18.1	329	5.9	−3.8	−2.9	4.9	7.7
	11	72.4	29.7	−13.0	336	78.6	24.7	−14.9	329	6.2	−4.9	−1.9	5.4	8.2
	12	75.8	24.8	−10.8	336	82.1	18.7	−11.5	328	6.3	−5.9	−0.6	6.1	8.8
	13	79.2	19.8	−8.6	336	85.6	12.7	−8.0	327	6.4	−7.0	0.6	7.1	9.6
	14	82.6	14.8	−6.4	336	89.2	6.5	−4.1	327	6.6	−8.2	2.3	8.7	10.9
	15	85.9	9.9	−4.3	336	92.4	0.5	−0.2	329	6.5	−9.3	4.1	10.2	12.1
	16	89.3	4.9	−2.1	336	92.7	0.0	0.0	0	3.3	−4.8	2.2	5.4	6.4
W	17	92.7	0.0	0.0	0	92.7	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0
M	18	38.7	79.2	−34.7	336	38.7	79.2	−34.7	336	0.0	0.0	0.0	0.0	0.0
	19	52.2	59.4	−26.0	336	56.7	58.8	−30.6	332	4.5	−0.5	−4.5	4.6	6.5
	20	65.7	39.6	−17.3	336	71.2	36.7	−21.2	330	5.5	−2.8	−3.8	4.9	7.4
	21	79.2	19.8	−8.6	336	85.6	12.7	−8.0	327	6.4	−7.0	0.6	7.1	9.6
W	22	92.7	0.0	0.0	0	92.7	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0

Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
relative *CIELAB* data used for "out"
ΔL^* = 92.69 − 38.67
Regularity
g^* = 39.4
Lightness gamut relative to offset
f^* = 69.8
Magenta red − White
rgb: M − W
Mean CIELAB difference (17 steps)
ΔH^*_{CIELAB} = 4.9
ΔE^*_{CIELAB} = 6.6
Mean CIELAB difference (5 steps)
ΔH^*_{CIELAB} = 3.3
ΔE^*_{CIELAB} = 4.7
Mean colour reproduction index: $R^*_{ab,m}$ = 72

YE300−3N, ; Device: FrgbNP_D65_L; Measurement: L26G00NA.PDF; Date: 20070129

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c−ref			ΔH*	ΔE*
M	1	46.1	71.3	−6.3	355	46.1	71.3	−6.3	355	0.0	0.0	0.0	0.0	0.0
	2	49.2	66.8	−5.9	355	46.3	71.4	−6.5	355	−2.8	4.6	−0.5	4.6	5.4
	3	52.3	62.4	−5.5	355	46.7	70.9	−6.7	355	−5.5	8.5	−1.1	8.6	10.3
	4	55.4	57.9	−5.1	355	47.0	70.4	−7.1	354	−8.3	12.5	−1.9	12.6	15.2
	5	58.5	53.5	−4.7	355	47.4	68.7	−8.6	353	−11.0	15.2	−3.8	15.7	19.2
	6	61.5	49.0	−4.3	355	48.8	65.4	−10.6	351	−12.6	16.4	−6.2	17.6	21.7
	7	64.6	44.6	−3.9	355	51.1	61.0	−10.8	350	−13.4	16.4	−6.8	17.8	22.4
	8	67.7	40.1	−3.5	355	55.2	55.1	−11.6	348	−12.5	15.0	−8.0	17.0	21.2
	9	70.8	35.7	−3.1	355	58.8	50.7	−11.1	348	−11.9	15.1	−7.9	17.0	20.9
	10	73.9	31.2	−2.7	355	63.9	43.8	−10.6	346	−9.9	12.6	−7.8	14.9	17.9
	11	77.0	26.7	−2.3	355	69.2	35.8	−9.3	345	−7.7	9.1	−6.9	11.5	13.8
	12	80.0	22.3	−1.9	355	74.3	27.2	−8.7	342	−5.7	4.9	−6.7	8.4	10.2
	13	83.1	17.8	−1.5	355	78.1	20.2	−8.4	337	−4.9	2.4	−6.8	7.3	8.8
	14	86.2	13.4	−1.1	355	82.0	14.0	−7.8	331	−4.1	0.6	−6.6	6.7	7.9
	15	89.3	8.9	−0.7	355	86.4	7.7	−6.5	319	−2.8	−1.1	−5.7	5.9	6.6
	16	92.4	4.5	−0.3	355	89.9	4.5	−4.3	316	−2.3	0.0	−3.9	4.0	4.7
W	17	95.5	0.0	0.0	0	95.5	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0
M	18	46.1	71.3	−6.3	355	46.1	71.3	−6.3	355	0.0	0.0	0.0	0.0	0.0
	19	58.5	53.5	−4.7	355	47.4	68.7	−8.6	353	−11.0	15.2	−3.8	15.7	19.2
	20	70.8	35.7	−3.1	355	58.8	50.7	−11.1	348	−11.9	15.1	−7.9	17.0	20.9
	21	83.1	17.8	−1.5	355	78.1	20.2	−8.4	337	−4.9	2.4	−6.8	7.3	8.8
W	22	95.5	0.0	0.0	0	95.5	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0

Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G
relative *CIELAB* data used for "out"
ΔL^* = 95.45 − 46.14
Regularity
g^* = 6.3
Lightness gamut relative to offset
f^* = 63.7
Magenta red − White
rgb: M − W
Mean CIELAB difference (17 steps)
ΔH^*_{CIELAB} = 10.0
ΔE^*_{CIELAB} = 12.1
Mean CIELAB difference (5 steps)
ΔH^*_{CIELAB} = 8.0
ΔE^*_{CIELAB} = 9.8
Mean colour reproduction index: $R^*_{ab,m}$ = 47

YE301−3N, ; Device: XrgbNP_D65_L; Measurement: L26G00NP.PDF; Date: 20070202

Start output of the file: www.ps.bam.de/YG26/10L/L26G00NA.PS



YE300−7N, ; Device: FrgbNP_D65_L; Measurement: L26G00NA.PDF; Date: 20070129

Start output of the file: www.ps.bam.de/YG26/10L/L26G00NP.PDF



YE301−7N, ; Device: XrgbNP_D65_L; Measurement: L26G00NP.PDF; Date: 20070202

See for similar files: http://www.ps.bam.de/YE30/; www.ps.bam.de/YE.HTM
Technical information: http://www.ps.bam.de Version 2.1, io=1,1

BAM registration: 20070401-YE30/10L/L30E05NA.PS/.TXT BAM material: code=rha4ta
application for output of monitor, data projector, or printer systems