T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c−ref			ΔH*	ΔE*
O	1	46.3	60.2	39.9	34	46.3	60.2	39.9	34	0.0	0.0	0.0	0.0	0.0
	2	47.8	52.7	34.9	34	45.8	58.4	36.2	32	−1.9	5.7	1.3	5.9	6.2
	3	49.3	45.2	30.0	34	44.3	55.0	31.1	29	−5.0	9.8	1.1	9.9	11.1
	4	50.8	37.6	25.0	34	43.6	50.4	23.8	25	−7.2	12.8	−1.1	12.8	14.7
	5	52.3	30.1	20.0	34	44.6	43.7	18.6	23	−7.6	13.6	−1.3	13.7	15.7
	6	53.8	22.6	15.0	34	46.1	32.9	13.8	23	−7.6	10.3	−1.1	10.4	13.0
	7	55.3	15.1	10.0	34	49.6	19.9	9.5	26	−5.6	4.9	−0.4	4.9	7.5
	8	56.8	7.5	5.1	34	55.4	7.8	2.8	20	−1.3	0.3	−2.2	2.3	2.7
Z	9	58.4	0.0	0.1	90	58.4	0.0	0.1	90	0.0	0.0	0.0	0.0	0.0
	10	57.3	−1.7	−6.5	255	57.3	−8.2	−8.0	224	0.1	−6.4	−1.4	6.7	6.7
	11	56.2	−3.4	−13.2	255	50.7	−15.3	−17.9	229	−5.4	−11.8	−4.6	12.8	13.9
	12	55.1	−5.2	−19.9	255	47.3	−19.9	−26.5	233	−7.7	−14.6	−6.5	16.1	17.9
	13	54.0	−7.0	−26.6	255	46.5	−22.0	−35.0	238	−7.4	−15.0	−8.3	17.2	18.8
	14	52.9	−8.7	−33.3	255	48.0	−23.4	−40.1	240	−4.8	−14.6	−6.7	16.2	16.9
	15	51.8	−10.5	−40.0	255	47.4	−20.5	−43.4	245	−4.4	−9.9	−3.3	10.6	11.5
	16	50.7	−12.2	−46.7	255	47.9	−20.1	−45.0	246	−2.7	−7.8	1.7	8.0	8.5
C	17	49.6	−14.0	−53.4	255	49.6	−14.0	−53.4	255	0.0	0.0	0.0	0.0	0.0
O	18	46.3	60.2	39.9	34	46.3	60.2	39.9	34	0.0	0.0	0.0	0.0	0.0
	19	52.3	30.1	20.0	34	44.6	43.7	18.6	23	−7.6	13.6	−1.3	13.7	15.7
Z	20	58.4	0.0	0.1	90	58.4	0.0	0.1	90	0.0	0.0	0.0	0.0	0.0
	21	54.0	−7.0	−26.6	255	46.5	−22.0	−35.0	238	−7.4	−15.0	−8.3	17.2	18.8
C	22	49.6	−14.0	−53.4	255	49.6	−14.0	−53.4	255	0.0	0.0	0.0	0.0	0.0

Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Regularity
$g^* =$ **12.5**

Orange red − Cyan blue
rgb: O − Z − C

Mean CIELAB difference (17 steps)
$\Delta H^*_{CIELAB} =$ **8.7**
$\Delta E^*_{CIELAB} =$ **9.7**

Mean CIELAB difference (5 steps)
$\Delta H^*_{CIELAB} =$ **6.2**
$\Delta E^*_{CIELAB} =$ **6.9**

YE310−3N, ; Device: XrgbNP_D65_L; Measurement: L26G00NP.PDF; Date: 20070202

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c−ref			ΔH*	ΔE*
O	1	48.3	58.2	45.6	38	48.3	58.2	45.6	38	0.0	0.0	0.0	0.0	0.0
	2	48.9	50.7	40.7	39	48.7	51.8	40.6	38	−0.1	1.1	0.0	1.1	1.1
	3	49.5	43.2	35.9	40	49.3	47.3	35.8	37	−0.2	4.1	0.0	4.1	4.1
	4	50.2	35.7	31.0	41	50.4	41.2	30.6	37	0.3	5.5	−0.3	5.5	5.5
	5	50.8	28.2	26.2	43	51.3	33.0	26.5	39	0.5	4.8	0.4	4.8	4.8
	6	51.5	20.7	21.3	46	51.5	24.3	21.1	41	0.1	3.6	−0.1	3.6	3.6
	7	52.1	13.2	16.4	51	52.4	14.4	17.2	50	0.3	1.2	0.8	1.4	1.5
	8	52.7	5.7	11.6	64	53.3	5.4	11.7	65	0.6	−0.2	0.1	0.3	0.7
Z	9	53.4	−1.7	6.7	105	53.4	−1.7	6.7	105	0.0	0.0	0.0	0.0	0.0
	10	53.6	−4.0	0.8	169	53.5	−8.1	0.8	174	0.0	−4.0	0.0	4.1	4.1
	11	53.9	−6.3	−5.0	218	53.5	−13.0	−3.3	195	−0.3	−6.6	1.7	6.9	6.9
	12	54.1	−8.6	−10.9	232	53.8	−16.8	−9.0	208	−0.3	−8.1	1.9	8.4	8.4
	13	54.4	−11.0	−16.8	237	52.9	−20.0	−14.8	217	−1.4	−9.0	2.0	9.3	9.4
	14	54.6	−13.3	−22.7	240	53.9	−21.8	−20.3	223	−0.6	−8.4	2.4	8.9	8.9
	15	54.9	−15.6	−28.6	241	53.9	−21.3	−26.5	231	−0.9	−5.6	2.1	6.1	6.2
	16	55.1	−17.9	−34.5	243	54.5	−21.3	−33.2	237	−0.5	−3.3	1.3	3.7	3.7
C	17	55.4	−20.2	−40.4	243	55.4	−20.2	−40.4	243	0.0	0.0	0.0	0.0	0.0
O	18	48.3	58.2	45.6	38	48.3	58.2	45.6	38	0.0	0.0	0.0	0.0	0.0
	19	50.8	28.2	26.2	43	51.3	33.0	26.5	39	0.5	4.8	0.4	4.8	4.8
Z	20	53.4	−1.7	6.7	105	53.4	−1.7	6.7	105	0.0	0.0	0.0	0.0	0.0
	21	54.4	−11.0	−16.8	237	52.9	−20.0	−14.8	217	−1.4	−9.0	2.0	9.3	9.4
C	22	55.4	−20.2	−40.4	243	55.4	−20.2	−40.4	243	0.0	0.0	0.0	0.0	0.0

Start output S1
Specification according to ISO/IEC 15775 Annex G and DIN 33866-1 Annex G

Regularity
$g^* =$ **17.2**

Orange red − Cyan blue
cmy0: O − Z − C

Mean CIELAB difference (17 steps)
$\Delta H^*_{CIELAB} =$ **4.0**
$\Delta E^*_{CIELAB} =$ **4.1**

Mean CIELAB difference (5 steps)
$\Delta H^*_{CIELAB} =$ **2.8**
$\Delta E^*_{CIELAB} =$ **2.8**

YE311−3N, ; Device: Xcmy0NP_D65_L; Measurement: L27G00NP.PDF; Date: 20070202

Start output of the file: www.ps.bam.de/YG26/10L/L26G00NP.PDF



YE310−7N, ; Device: XrgbNP_D65_L; Measurement: L26G00NP.PDF; Date: 20070202

Start output of the file: www.ps.bam.de/YG27/10L/L27G00NP.PDF



YE311−7N, ; Device: Xcmy0NP_D65_L; Measurement: L27G00NP.PDF; Date: 20070202

See for similar files: http://www.ps.bam.de/YE31/; www.ps.bam.de/YE.HTM
Technical information: http://www.ps.bam.de Version 2.1, io=1,1

BAM registration: 20070401-YE31/10L/L31E0ENP.PS/.PDF BAM material: code=rha4ta
application for output of monitor, data projector, or printer systems