

T	i	LAB*a,ref	hab,ref	LAB*a,out	hab,out	LAB*a,out/c-ref	ΔH^*	ΔE^*
N	1	26.8	0.0	0.0	0.0	0.0	0.0	0.0
	2	31.1	0.0	0.0	0.0	0.0	0.0	0.0
	3	35.4	0.0	0.0	0.0	0.0	0.0	0.0
	4	39.7	0.0	0.0	0.0	0.0	0.0	0.0
	5	43.9	0.0	0.0	0.0	0.0	0.0	0.0
	6	48.2	0.0	0.0	0.0	0.0	0.0	0.0
	7	52.5	0.0	0.0	0.0	0.0	0.0	0.0
	8	56.8	0.0	0.0	0.0	0.0	0.0	0.0
Z	9	61.1	0.0	0.0	0.0	0.0	0.0	0.0
	10	65.4	0.0	0.0	0.0	0.0	0.0	0.0
	11	69.6	0.0	0.0	0.0	0.0	0.0	0.0
	12	73.9	0.0	0.0	0.0	0.0	0.0	0.0
	13	78.2	0.0	0.0	0.0	0.0	0.0	0.0
	14	82.5	0.0	0.0	0.0	0.0	0.0	0.0
	15	86.8	0.0	0.0	0.0	0.0	0.0	0.0
	16	91.1	0.0	0.0	0.0	0.0	0.0	0.0
W	17	95.3	0.0	0.0	0.0	0.0	0.0	0.0
N	18	26.8	0.0	0.0	0.0	0.0	0.0	0.0
	19	43.9	0.0	0.0	0.0	0.0	0.0	0.0
Z	20	61.1	0.0	0.0	0.0	0.0	0.0	0.0
	21	78.2	0.0	0.0	0.0	0.0	0.0	0.0
W	22	95.3	0.0	0.0	0.0	0.0	0.0	0.0


Start output S1
Specification according to
ISO/IEC 15775 Annex G
and DIN 33866-1 Annex G
relative CIELAB data used for "out"
 $\Delta L^* = 95.34 - 26.8$
Regularity
 $g^* = 36.7$
Lightness gamut relative to offset
 $f^* = 88.6$
Black - White
rgb: N - W
Mean CIELAB difference (17 steps)
 $\Delta H^*_{CIELAB} = 3.7$
 $\Delta E^*_{CIELAB} = 7.6$
Mean CIELAB difference (5 steps)
 $\Delta H^*_{CIELAB} = 2.9$
 $\Delta E^*_{CIELAB} = 5.9$
Mean colour reproduction index: $R^*_{ab,m} = 67$

YE320-3N, ; Device: XcmyNP_D50_L; Measurement: L27G00NP.PDF; Date: 20070202


T	i	LAB*a,ref	hab,ref	LAB*a,out	hab,out	LAB*a,out/c-ref	ΔH^*	ΔE^*
N	1	21.7	0.0	0.0	0.0	0.0	0.0	0.0
	2	26.3	0.0	0.0	0.0	0.0	0.0	0.0
	3	30.9	0.0	0.0	0.0	0.0	0.0	0.0
	4	35.5	0.0	0.0	0.0	0.0	0.0	0.0
	5	40.1	0.0	0.0	0.0	0.0	0.0	0.0
	6	44.7	0.0	0.0	0.0	0.0	0.0	0.0
	7	49.3	0.0	0.0	0.0	0.0	0.0	0.0
	8	53.9	0.0	0.0	0.0	0.0	0.0	0.0
Z	9	58.6	0.0	0.0	0.0	0.0	0.0	0.0
	10	63.2	0.0	0.0	0.0	0.0	0.0	0.0
	11	67.8	0.0	0.0	0.0	0.0	0.0	0.0
	12	72.4	0.0	0.0	0.0	0.0	0.0	0.0
	13	77.0	0.0	0.0	0.0	0.0	0.0	0.0
	14	81.6	0.0	0.0	0.0	0.0	0.0	0.0
	15	86.2	0.0	0.0	0.0	0.0	0.0	0.0
	16	90.8	0.0	0.0	0.0	0.0	0.0	0.0
W	17	95.5	0.0	0.0	0.0	0.0	0.0	0.0
N	18	21.7	0.0	0.0	0.0	0.0	0.0	0.0
	19	40.1	0.0	0.0	0.0	0.0	0.0	0.0
Z	20	58.6	0.0	0.0	0.0	0.0	0.0	0.0
	21	77.0	0.0	0.0	0.0	0.0	0.0	0.0
W	22	95.5	0.0	0.0	0.0	0.0	0.0	0.0

Start output S1
Specification according to
ISO/IEC 15775 Annex G
and DIN 33866-1 Annex G
relative CIELAB data used for "out"
 $\Delta L^* = 95.46 - 21.66$
Regularity
 $g^* = 54.2$
Lightness gamut relative to offset
 $f^* = 95.3$
Black - White
rgb: N - W
Mean CIELAB difference (17 steps)
 $\Delta H^*_{CIELAB} = 0.1$
 $\Delta E^*_{CIELAB} = 2.4$
Mean CIELAB difference (5 steps)
 $\Delta H^*_{CIELAB} = 0.1$
 $\Delta E^*_{CIELAB} = 1.6$
Mean colour reproduction index: $R^*_{ab,m} = 90$

YE321-3N, ; Device: Xcmy0NP_D65_L; Measurement: L27G00NP.PDF; Date: 20070202



YE320-7N, ; Device: XcmyNP_D50_L; Measurement: L27G00NP.PDF; Date: 20070202



YE321-7N, ; Device: Xcmy0NP_D65_L; Measurement: L27G00NP.PDF; Date: 20070202