

Input: Colorimetric Television Luminous System TL5000a

with x_{rgb} data of the
four device hues

(1 0 0)_d = Red R_d

(1 1 0)_d = Yellow Y_d

(0 1 0)_d = Green G_d

(0 0 1)_d = Blue B_d



TL5000a adapted (q) CIE1931 data					
$L^*a^*b^*$	a^*	b^*	C^*_{ab}	h^*_{ab}	h^*_{ab}
R_{Munsell}	50.5	36.62	64.35	100.42	40
Y_{Munsell}	92.66	-20.69	90.75	93.08	103
G_{Munsell}	83.63	-82.75	79.9	115.64	136
C_{Munsell}	86.88	-46.16	-13.35	48.12	196
B_{Munsell}	30.39	76.06	-103.59	128.52	206
M_{Munsell}	57.3	94.35	-58.41	110.97	328
N_{Munsell}	0.01	0.0	0.0	0.0	0
W_{Munsell}	95.41	0.0	0.0	0.0	0
E_{CIE94}	29.92	58.74	27.99	65.07	25
L_{CIE94}	81.26	-2.88	71.56	71.62	92
a_{CIE94}	52.23	-82.41	13.6	44.35	162
b_{CIE94}	30.57	1.41	-86.46	46.49	272

Output: Colorimetric Television Luminous System TL5000a

with hue number

n : 01 to 16

01 = Red R_d

05 = Yellow Y_d

09 = Green G_d

13 = Blue B_d

with hue position

(row and column)

of test chart ISO 9241-300:AE49



TL5000a adapted (q) CIE1931 data					
$L^*a^*b^*$	a^*	b^*	C^*_{ab}	h^*_{ab}	h^*_{ab}
R_{Munsell}	50.5	36.62	64.35	100.42	40
Y_{Munsell}	92.66	-20.69	90.75	93.08	103
G_{Munsell}	83.63	-82.75	79.9	115.64	136
C_{Munsell}	86.88	-46.16	-13.35	48.12	196
B_{Munsell}	30.39	76.06	-103.59	128.52	206
M_{Munsell}	57.3	94.35	-58.41	110.97	328
N_{Munsell}	0.01	0.0	0.0	0.0	0
W_{Munsell}	95.41	0.0	0.0	0.0	0
E_{CIE94}	29.92	58.74	27.99	65.07	25
L_{CIE94}	81.26	-2.88	71.56	71.62	92
a_{CIE94}	52.23	-82.41	13.6	44.35	162
b_{CIE94}	30.57	1.41	-86.46	46.49	272

