

Input: Colorimetric Television Luminous System TL5000a

with x_{rgb} data of the

four device hues

(1 0 0)_d = Red R_d

(1 1 0)_d = Yellow Y_d

(0 1 0)_d = Green G_d

(0 0 1)_d = Blue B_d



TL5000a adapted (q) CIE1931 data					
L^*	a^*	b^*	C^*_{ab}	h^*_{ab}	
R_{M0}	50.5	76.92	64.35	100.42	40
Y_{M0}	92.66	-20.69	90.75	93.08	103
G_{M0}	83.63	-82.75	79.9	115.64	136
C_{M0}	86.88	-46.16	-13.35	48.12	196
B_{M0}	30.39	76.06	-103.59	128.52	206
R_{M1}	57.3	94.35	-58.61	110.97	328
R_{M2}	0.01	0.0	0.0	0.0	0
R_{M3}	95.41	0.0	0.0	0.0	0
R_{CM}	29.92	58.74	27.99	65.07	25
L_{CM}	81.26	-2.88	71.56	71.62	92
G_{CM}	52.23	-82.61	13.6	44.35	162
B_{CM}	30.57	1.41	-86.46	46.49	274

Output: Colorimetric Television Luminous System TL5000a

with hue number

n : 01 to 16

01 = Red R_d

05 = Yellow Y_d

09 = Green G_d

13 = Blue B_d

with hue position

(row and column)

of test chart ISO 9241-300:AE49



TL5000a adapted (q) CIE1931 data					
L^*	a^*	b^*	C^*_{ab}	h^*_{ab}	
R_{M0}	50.5	76.92	64.35	100.42	40
Y_{M0}	92.66	-20.69	90.75	93.08	103
G_{M0}	83.63	-82.75	79.9	115.64	136
C_{M0}	86.88	-46.16	-13.35	48.12	196
B_{M0}	30.39	76.06	-103.59	128.52	206
R_{M1}	57.3	94.35	-58.61	110.97	328
R_{M2}	0.01	0.0	0.0	0.0	0
R_{M3}	95.41	0.0	0.0	0.0	0
R_{CM}	29.92	58.74	27.99	65.07	25
L_{CM}	81.26	-2.88	71.56	71.62	92
G_{CM}	52.23	-82.61	13.6	44.35	162
B_{CM}	30.57	1.41	-86.46	46.49	274

