

Input: Colorimetric Television Luminous System TL500a

with x_{gh} , data of the
four device hues

(1 0 0)_d = Red R_d

(1 1 0)_d = Yellow Y_d

(0 1 0)_d = Green G_d

(0 0 1)_d = Blue B_d



TL500a adapted (a) CIECAM data									
L^*	a^*	b^*	C^*_{Muns}	h^*_{Muns}	L^*	a^*	b^*	C^*_{Muns}	h^*_{Muns}
R_{Muns}	50.5	76.92	64.55	100.42	49				
Y_{Muns}	92.65	-20.69	90.75	93.08	103				
G_{Muns}	83.63	-82.75	79.9	115.84	136				
C_{Muns}	86.88	-46.16	-13.55	48.13	196				
B_{Muns}	30.39	76.05	-103.59	128.52	206				
R_{Muns}	57.3	94.75	-58.41	110.97	228				
R_{Muns}	0.01	0.0	0.0	0.0	0				
R_{Muns}	95.41	0.0	0.0	0.0	0				
R_{Muns}	29.92	58.74	27.99	65.87	25				
L_{Muns}	81.26	-2.88	71.56	71.62	92				
C_{Muns}	52.23	-82.41	13.6	44.55	162				
R_{Muns}	30.57	1.41	-85.45	45.45	274				

Output: Colorimetric Television Luminous System TL500a

with hue number

$n = 01$ to 16

01 = Red R_d

05 = Yellow Y_d

09 = Green G_d

13 = Blue B_d

with hue position

(row and column)

of test chart ISO 5241-300:AE49



TL500a adapted (a) CIECAM data									
L^*	a^*	b^*	C^*_{Muns}	h^*_{Muns}	L^*	a^*	b^*	C^*_{Muns}	h^*_{Muns}
R_{Muns}	50.5	76.92	64.55	100.42	49				
Y_{Muns}	92.65	-20.69	90.75	93.08	103				
G_{Muns}	83.63	-82.75	79.9	115.84	136				
C_{Muns}	86.88	-46.16	-13.55	48.13	196				
B_{Muns}	30.39	76.05	-103.59	128.52	206				
R_{Muns}	57.3	94.75	-58.41	110.97	228				
R_{Muns}	0.01	0.0	0.0	0.0	0				
R_{Muns}	95.41	0.0	0.0	0.0	0				
R_{Muns}	29.92	58.74	27.99	65.87	25				
L_{Muns}	81.26	-2.88	71.56	71.62	92				
C_{Muns}	52.23	-82.41	13.6	44.55	162				
R_{Muns}	30.57	1.41	-85.45	45.45	274				

