

Input: Colorimetric Television Luminous System TL5000a

with xy_tZ_t data of the four device hues

(1 0 0)_d = Red R_d

(1 1 0)_d = Yellow Y_d

(0 1 0)_d = Green G_d

(0 0 1)_d = Blue B_d



$L^*a^*_d b^*_d$	L^*	a^*	b^*	C^*_{ab}	h^*_ab
R_{d01}	50.5	36.92	64.35	100.42	40
Y_{d01}	92.66	-20.69	90.75	93.08	103
G_{d01}	83.63	-82.75	79.9	115.64	136
C_{d01}	86.88	-46.16	-13.35	48.12	196
B_{d01}	30.39	76.06	-103.59	128.52	266
R_{d25}	57.3	94.35	-58.41	110.97	328
Y_{d25}	0.01	0.0	0.0	0.0	0
G_{d25}	95.41	0.0	0.0	0.0	0
B_{d25}	29.92	58.74	27.99	65.07	25
L^*_{cm}	81.26	-2.88	71.56	71.62	92
C^*_{cm}	52.23	-82.61	13.6	44.35	162
h^*_{cm}	30.57	1.41	-86.46	46.49	272

Output: Colorimetric Television Luminous System TL5000a

with hue number

n : 01 to 32

01 = Red R_d

09 = Yellow Y_d

17 = Green G_d

25 = Blue B_d

with hue position

(row and column)

of test chart ISO 9241-300:AEF49



$L^*a^*_d b^*_d$	L^*	a^*	b^*	C^*_{ab}	h^*_ab
R_{d01}	50.5	36.92	64.35	100.42	40
Y_{d01}	92.66	-20.69	90.75	93.08	103
G_{d01}	83.63	-82.75	79.9	115.64	136
C_{d01}	86.88	-46.16	-13.35	48.12	196
B_{d01}	30.39	76.06	-103.59	128.52	266
R_{d25}	57.3	94.35	-58.41	110.97	328
Y_{d25}	0.01	0.0	0.0	0.0	0
G_{d25}	95.41	0.0	0.0	0.0	0
B_{d25}	29.92	58.74	27.99	65.07	25
L^*_{cm}	81.26	-2.88	71.56	71.62	92
C^*_{cm}	52.23	-82.61	13.6	44.35	162
h^*_{cm}	30.57	1.41	-86.46	46.49	272

