

Input: Colorimetric Television Luminous System TL500a

with xyY data of the
four device hues

(1 0 0)_d = Red R_d

(1 1 0)_d = Yellow Y_d

(0 1 0)_d = Green G_d

(0 0 1)_d = Blue B_d



TL500a: adapted (q) CIECAM data						
L^*	a^*	b^*	C^*_{ab}	h^*_{ab}		
R_{M0}	50.5	76.92	64.55	100.42	49	
Y_{M0}	92.65	-20.69	90.75	93.08	103	
G_{M0}	83.63	-82.75	79.9	115.84	136	
C_{M0}	86.88	-66.16	-13.55	48.13	196	
B_{M0}	30.39	76.05	-103.59	128.52	266	
W_{M0}	57.3	94.75	-58.41	110.97	328	
R_{M0}	0.01	0.0	0.0	0.0	0	
W_{M0}	95.41	0.0	0.0	0.0	0	
R_{C0}	39.92	58.74	27.99	65.87	25	
L_{C0}	81.26	-2.88	71.56	71.62	92	
G_{C0}	52.23	-82.41	13.6	44.55	162	
C_{C0}	30.57	1.41	-65.45	65.45	273	

Output: Colorimetric Television Luminous System TL500a

with hue number

$n = 01$ to 32

01 = Red R_d

09 = Yellow Y_d

17 = Green G_d

25 = Blue B_d

with hue position

(row and column)

of test chart ISO 5241-300:AEF7



TL500a: adapted (q) CIECAM data						
L^*	a^*	b^*	C^*_{ab}	h^*_{ab}		
R_{M0}	50.5	76.92	64.55	100.42	49	
Y_{M0}	92.65	-20.69	90.75	93.08	103	
G_{M0}	83.63	-82.75	79.9	115.84	136	
C_{M0}	86.88	-66.16	-13.55	48.13	196	
B_{M0}	30.39	76.05	-103.59	128.52	266	
W_{M0}	57.3	94.75	-58.41	110.97	328	
R_{M0}	0.01	0.0	0.0	0.0	0	
W_{M0}	95.41	0.0	0.0	0.0	0	
R_{C0}	39.92	58.74	27.99	65.87	25	
L_{C0}	81.26	-2.88	71.56	71.62	92	
G_{C0}	52.23	-82.41	13.6	44.55	162	
C_{C0}	30.57	1.41	-65.45	65.45	273	

