

Colour-device (d) data according to ISO/IEC 15775 (offset) for $Y_W=88,6$ and an illuminant approximately D65										
Device (d) colours, see names in CIE R8-09, and ISO/IEC 15775	Offset print normalized XYZ-device data					Offset print normalized CIELAB-device data				
	$X_{d,089}$	$Y_{d,089}$	$Z_{d,089}$	$x_{d,089}$	$y_{d,089}$	$L^*_{d,089}$	$a^*_{d,089}$	$b^*_{d,089}$	$C^*_{ab,d,089}$	$h_{ab,d,089}$
$C=C_d$ cyan blue (cyan)	18,74	26,62	68,54	0,164	0,233	58,62	-30,01	-47,10	55,85	237
$M=M_d$ magenta red (magenta)	33,06	16,90	22,01	0,459	0,234	48,13	75,93	-9,78	76,56	352
$Y=Y_d$ yellow	68,06	77,10	9,03	0,441	0,500	90,36	-10,21	93,95	94,51	96
$O=R_d$ orange red (red)	33,13	16,75	2,68	0,630	0,318	47,94	77,00	50,59	92,13	33
$L=G_d$ leaf green (green)	8,71	19,18	6,62	0,252	0,555	50,89	-62,45	34,69	71,44	150
$V=B_d$ violet blue (blue)	7,17	4,65	21,41	0,215	0,139	25,71	31,91	-47,33	57,09	303
W white	83,69	88,60	89,47	0,319	0,338	95,41	0,01	-0,00	0,01	354
N black	2,42	2,52	2,81	0,312	0,325	18,00	0,81	-1,97	2,13	292
Source: Kittelmann (2005), Diploma work, TU Berlin, $KR=0$, $YF=0$, $K=0$										