

Colour-device (d) data according to ISO/IEC 15775 (offset) for $Y_W=88,6$ and standard illuminant D65										
Device (d) colours, see names in CIE R8-09, and ISO/IEC 15775	Offset print normalized XYZ-device data					Offset print normalized CIELAB-device data				
	$X_{d,089}$	$Y_{d,089}$	$Z_{d,089}$	$x_{d,089}$	$y_{d,089}$	$L^*_{d,089}$	$a^*_{d,089}$	$b^*_{d,089}$	$C^*_{ab,d,089}$	$h_{ab,d,089}$
$C=C_d$ cyan blue (cyan)	18,74	26,27	69,02	0,164	0,230	58,30	-29,20	-43,70	52,55	236
$M=M_d$ magenta red (magenta)	32,46	16,95	23,04	0,448	0,233	48,20	72,80	-8,50	73,29	353
$Y=Y_d$ yellow	63,74	72,69	8,27	0,440	0,502	88,30	-11,90	95,10	95,84	97
$O=R_d$ orange red (red)	29,01	16,24	4,26	0,585	0,328	47,30	63,80	41,20	75,94	32
$L=G_d$ leaf green (green)	8,53	20,05	9,58	0,223	0,525	51,90	-68,80	28,10	74,31	157
$V=B_d$ violet blue (blue)	6,22	4,51	22,65	0,186	0,135	25,30	23,50	-47,30	52,81	296
W white	84,18	88,56	96,45	0,312	0,329	95,40	0,00	0,00	0,00	0
N black	2,39	2,51	2,74	0,312	0,328	18,00	0,00	0,00	0,00	0
Source: Richter (2012), Colour and Colour Vision, see table of end cover, $KR=1$, $YF=0$, $K=1$										