

Ostwald optimal colours (o), maximum (m) C _{AB} for D50, Y _N =0, Y _W =90, Y _m =520_770													
i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code		
1	405	32 564	29.26	53.83	73.48	0.1869	0.3438	0.4692	185.2	17 486	38 592	Cm	
7	435	33 565	26.01	53.61	57.83	0.1892	0.39	0.4207	168.6	18 490	46 631		
10	450	33 566	23.26	54.16	39.66	0.1986	0.4625	0.3387	144.6	19 497	-1 497c		
12	460	33 567	22.04	54.86	27.4	0.2113	0.5259	0.2626	128.7	21 506	-1 506c		
13	465	33 568	22.01	55.56	22.12	0.2208	0.5572	0.2218	122.1	22 512	-1 512c		
14	470	34 570	22.15	56.11	17.7	0.2308	0.5846	0.1844	116.9	23 519	-1 519c	Gm	
15	475	34 573	23.92	58.04	14.12	0.2489	0.604	0.1469	111.4	25 527	-1 527c		
15	480	35 578	27.41	61.49	14.13	0.266	0.5968	0.1371	108.4	26 532	-1 532c		
17	485	37 587	33.99	66.01	9.3	0.3109	0.6039	0.0851	98.0	28 544	-1 544c		
18	490	44 620	59.95	79.56	7.75	0.407	0.5402	0.0526	71.3	32 561	-1 561c		
19	495	-1 495c	75.28	84.51	6.54	0.4525	0.5081	0.0393	54.4	33 568	12 463	max	
20	500	-1 500c	75.26	83.07	5.58	0.4591	0.5067	0.034	52.5	33 569	13 466		
22	510	-1 510c	75.16	79.06	4.31	0.4741	0.4986	0.0272	47.4	34 571	14 471		
23	520	-1 519c	74.98	76.43	3.93	0.4826	0.492	0.0253	44.2	34 572	14 473	Ym	
25	530	-1 529c	74.05	69.95	3.45	0.5021	0.4743	0.0234	36.4	35 575	15 477		
27	540	-1 539c	72.16	62.35	3.2	0.524	0.4527	0.0232	27.8	35 579	16 480		
28	545	-1 544c	70.81	58.33	3.13	0.5353	0.4409	0.0236	23.4	36 581	16 481		
29	550	-1 549c	69.15	54.19	3.08	0.5469	0.4286	0.0244	19.1	36 583	16 483		
30	555	-1 554c	67.17	50.01	3.05	0.5586	0.4159	0.0254	15.0	37 585	16 484		
32	560	-1 560c	62.28	41.85	3.02	0.5812	0.3905	0.0281	7.7	38 590	17 486		
32	564	1 405	67.15	46.16	9.01	0.5489	0.3773	0.0736	5.2	38 592	17 486	Rm	
33	565	7 435	70.4	46.38	24.66	0.4977	0.3279	0.1743	348.6	46 631	18 490		
33	566	10 450	73.15	45.83	42.83	0.452	0.2832	0.2646	324.7	-1 497c	19 497		
33	567	12 460	74.37	45.13	55.09	0.4259	0.2585	0.3155	308.7	-1 506c	21 506		
33	568	13 465	74.4	44.43	60.37	0.4151	0.2479	0.3368	302.1	-1 512c	22 512		
34	570	14 470	74.26	43.88	64.78	0.4059	0.2398	0.3541	296.9	-1 519c	23 519	Mm	
34	573	15 475	72.5	41.95	68.37	0.3965	0.2294	0.3739	291.5	-1 527c	25 527		
35	578	15 480	69.0	38.5	68.36	0.3923	0.2189	0.3887	288.5	-1 532c	26 532		
37	587	17 485	62.42	33.98	73.19	0.368	0.2003	0.4315	278.0	-1 544c	28 544		
44	620	18 490	36.46	20.43	74.74	0.277	0.1552	0.5677	251.3	-1 561c	32 561		
-1 495c	19 495	21.14	15.48	75.95	0.1877	0.1375	0.6746	234.4	12 463	33 568	min		
-1 500c	20 500	21.15	16.92	76.91	0.1839	0.1471	0.6688	232.5	13 466	33 569			
-1 510c	22 510	21.25	20.93	78.18	0.1765	0.1739	0.6494	227.5	14 471	34 571			
-1 519c	23 520	21.44	23.56	78.56	0.1735	0.1907	0.6357	224.2	14 473	34 572	Bm		
-1 529c	25 530	22.36	30.04	79.04	0.1701	0.2285	0.6013	216.5	15 477	35 575			
-1 539c	27 540	24.25	37.64	79.29	0.1717	0.2666	0.5615	207.8	16 480	35 579			
-1 544c	28 545	25.6	41.66	79.36	0.1746	0.2841	0.5412	203.5	16 481	36 581			
-1 549c	29 550	27.26	45.8	79.41	0.1788	0.3004	0.5207	199.2	16 483	36 583			
-1 554c	30 555	29.24	49.98	79.44	0.1843	0.315	0.5006	195.0	16 484	37 585			
-1 560c	32 560	34.13	58.14	79.47	0.1987	0.3385	0.4627	187.7	17 486	38 590			
W0	380	770	86.78	90.0	74.24	0.3457	0.3585	0.2957	0.0				
N0	380	770	3.47	3.6	2.96	0.3457	0.3585	0.2957	0.0				