

Ostwald optimal colours (o), maximum (m) C_{AB} for P60, $Y_N=0$, $Y_W=90$, $Y_m=520_770$

i_1, λ_1	i_2, λ_2	X	Y	Z	x	y	z	h_{xy}	i_d, λ_d	i_c, λ_c	Code
0 405	32 563	31.65	53.56	93.3	0.1773	0.3	0.5226	192.2	16 483	38 590	Cm
6 435	32 563	28.3	54.12	74.65	0.1801	0.3445	0.4752	174.7	17 487	44 621	
10 450	33 565	22.96	54.2	45.12	0.1877	0.4432	0.3689	140.1	19 497	-1 497c	
11 460	33 566	22.85	55.45	37.84	0.1967	0.4774	0.3258	130.5	20 502	-1 502c	
13 465	33 568	21.78	56.12	24.97	0.2117	0.5455	0.2427	117.2	22 513	-1 513c	
14 470	34 570	22.2	57.09	19.98	0.2236	0.575	0.2012	111.9	24 521	-1 521c	Gm
15 475	34 574	24.59	59.7	16.0	0.2451	0.5952	0.1595	106.1	25 529	-1 529c	
15 480	36 580	28.98	63.87	16.01	0.2662	0.5866	0.147	102.2	27 535	-1 535c	
17 485	39 595	39.81	70.8	10.63	0.3283	0.5839	0.0877	88.4	29 549	-1 549c	
18 490	-1 490c	72.35	85.0	8.89	0.4352	0.5113	0.0534	57.7	33 566	11 459	max
19 495	-1 495c	72.31	83.76	7.55	0.4419	0.5119	0.0461	56.3	33 567	12 461	
20 500	-1 500c	72.29	82.2	6.51	0.449	0.5105	0.0404	54.5	33 568	12 464	
22 510	-1 510c	72.19	77.89	5.14	0.465	0.5017	0.0331	49.9	34 570	13 469	
24 520	-1 520c	71.62	71.91	4.45	0.4839	0.4859	0.0301	43.5	34 572	14 473	Ym
25 530	-1 529c	71.04	68.43	4.25	0.4943	0.4761	0.0295	39.9	34 574	15 475	
27 540	-1 539c	69.15	60.8	3.99	0.5162	0.4539	0.0298	32.1	35 578	15 478	
29 545	-1 545c	66.16	52.69	3.87	0.539	0.4293	0.0315	24.2	36 582	16 480	
29 550	-1 549c	66.16	52.69	3.87	0.539	0.4293	0.0315	24.2	36 582	16 480	
30 555	-1 554c	64.21	48.59	3.84	0.5504	0.4165	0.0329	20.3	36 584	16 481	
32 560	-1 560c	59.36	40.5	3.81	0.5725	0.3906	0.0367	13.2	37 589	16 483	
32 563	0 405	65.41	46.43	11.27	0.5312	0.3771	0.0915	12.2	38 590	16 483	Rm
32 563	6 435	68.76	45.87	29.92	0.4756	0.3173	0.2069	354.7	44 621	17 487	
33 565	10 450	74.1	45.79	59.44	0.4131	0.2553	0.3314	320.2	-1 497c	19 497	
33 566	11 460	74.21	44.54	66.72	0.4001	0.2401	0.3597	310.6	-1 502c	20 502	
33 568	13 465	75.28	43.87	79.59	0.3787	0.2207	0.4004	297.2	-1 513c	22 513	
34 570	14 470	74.86	42.9	84.59	0.3699	0.212	0.418	291.9	-1 521c	24 521	Mm
34 574	15 475	72.47	40.29	88.56	0.3599	0.2001	0.4398	286.2	-1 529c	25 529	
36 580	15 480	68.08	36.12	88.55	0.3531	0.1874	0.4594	282.3	-1 535c	27 535	
39 595	17 485	57.25	29.19	93.93	0.3173	0.1618	0.5207	268.5	-1 549c	29 549	
-1 490c	18 490	24.71	14.99	95.68	0.1825	0.1107	0.7067	237.7	11 459	33 566	min
-1 495c	19 495	24.75	16.23	97.02	0.1793	0.1176	0.7029	236.3	12 461	33 567	
-1 500c	20 500	24.77	17.79	98.05	0.1761	0.1265	0.6972	234.6	12 464	33 568	
-1 510c	22 510	24.87	22.1	99.42	0.1699	0.1509	0.679	229.9	13 469	34 570	
-1 520c	24 520	25.44	28.08	100.11	0.1655	0.1827	0.6516	223.6	14 473	34 572	Bm
-1 529c	25 530	26.02	31.56	100.32	0.1647	0.1999	0.6353	219.9	15 475	34 574	
-1 539c	27 540	27.91	39.19	100.57	0.1664	0.2337	0.5997	212.2	15 478	35 578	
-1 545c	29 545	30.9	47.3	100.69	0.1727	0.2644	0.5628	204.2	16 480	36 582	
-1 549c	29 550	30.9	47.3	100.69	0.1727	0.2644	0.5628	204.2	16 480	36 582	
-1 554c	30 555	32.85	51.4	100.72	0.1776	0.2778	0.5445	200.4	16 481	36 584	
-1 560c	32 560	37.7	59.49	100.75	0.1904	0.3005	0.5089	193.2	16 483	37 589	
W0 380	770	87.36	89.99	94.11	0.3218	0.3315	0.3466	0.0			
N0 380	770	3.49	3.59	3.76	0.3218	0.3315	0.3466	0.0			