




http://farbe.li.tu-berlin.de/AEZ4/AEZ4L0N1.TXT /PS; only vector graphic VG; start output
N: no 3D-linearization (OL) in file (F) or PS-startup (S), page 1/1





VG → VG

Original VG with standard gamma $g_p=1,000$



File graphic ISO step gamma g_p
AEZ41-1N PG $C_{YpB}=C_{YnB}$ 1,000

Application: luminance contrast of sRGB displays:
 $Y_W : Y_N = 90 : 0,31 = 288 : 1$ according to ISO 9241-306.
(contrast without display reflection of room light)









Output test of colour devices at the work places
The visual colours change by the software and:
on displays with the reflection of the room light,
in print with the printer driver and the workflow.
The luminance contrast ratio between White W and Black N determines,
if the 9 gray steps between N and W appear equally spaced.
Equal spacing shall appear for the intended device output:
on displays for the output within the broken and rectangle,
in print for the output within the continuous and rectangle.
If this is NOT the case, then determine visually with the next page
the ISO-contrast step which gives the intended result.
You may ask the device manufacturer for software solutions.
You may change the PDF-file gamma to produce the intended result.
Different gamma-change methods in VG or PG graphics are available.

Ergonomics of human-system interaction ISO 9241-306:2018
Part 306: Field assessment methods for electronic visual displays
For test charts see
<http://standards.iso.org/iso/9241/306/ed-2/index.html>
For similar ISO-test charts in A4 size see
<http://standards.iso.org/iso/9241/306/ed-2/AE49/AE49.HTM>
For similar ISO-test charts with output questions see
<http://standards.iso.org/iso/9241/306/ed-2/AE49/AE49F0P.XPDF>
For similar ISO/IEC test charts according to ISO/IEC 15775,
and ISO/IEC TR 24705 see
<http://farbe.li.tu-berlin.de/A/24705TE.html>
For the relation and links to many other standards see
<http://farbe.li.tu-berlin.de/EE68/EE68LONP.PDF>



PDF- and PS-test files for relative colour image reproduction according to DIN 33872-1 to -6:2010
These DIN-test charts serve for the colorimetric specification,
and the visual assessment of the display and print output.
For free download of the test charts see
<http://farbe.li.tu-berlin.de/A/33872.html>
For similar DIN-test charts according to DIN 33866-1 to -5:2000 see
<http://farbe.li.tu-berlin.de/A/DE13/DE13.HTM>
For more test charts, standards and applications see
<http://farbe.li.tu-berlin.de/A/INFOALAE.html>

Ergonomic and colorimetric colour image reproduction
For the ergonomic and colorimetric colour image reproduction see
Richter, Klaus (2016), Output linearization method OLM36 for
displays, printers, and offset, 61 pages, 1.4MB.
http://farbe.li.tu-berlin.de/OC/TLN16_01.PDF
(Consistent similar to CIE R09-2015, free download for CIE-members.)
For a list of publications of Klaus Richter see
<http://farbe.li.tu-berlin.de/X/91/FEN.html>
For basic information in 6 languages (EN, GE, FR, IT, SP, NO):
Klaus Richter (2015), Colour, colour vision, and elementary colours
in colour information technology, 86 pages, 2.2 MB, see
<http://standards.iso.org/iso/9241/306/ed-2/ES15.PDF>



TUB-test chart AEZ4; all colour figures in vector graphic VG
1 VG[0-1], 5 VG gamma transfer, similar ISO 9241-306:AE49

input: w/rgb/cmyk → rgb (1MR)
output: change of gamma g_p

TUB registration: 20200201-AEZ4/AEZ4L0N1.TXT / PS
application for evaluation and measurement of display or print output

TUB material: code=thadta