

T	i	LAB*a,ref			hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref			ΔH^*	ΔE^*	Start-Ausgabe S1
R _d	1	35.9	60.7	44.5	36	35.9	60.7	44.5	36	0.0	0.0	0.0	0.0	0.0		Kennzeichnung nach
	2	39.5	56.9	41.7	36	40.2	58.0	36.9	32	0.7	1.1	-4.7	4.9	5.0		ISO/IEC 15775:1999 Anhang G
	3	43.0	53.1	39.0	36	45.1	53.5	29.9	29	2.1	0.4	-9.0	9.1	9.3		& DIN 33866-1:2000 Anhang G
	4	46.6	49.3	36.2	36	49.9	48.2	26.2	29	3.3	-1.0	-9.9	10.0	10.6		relative CIELAB Daten für "aus"
	5	50.1	45.5	33.4	36	54.4	43.2	21.4	26	4.3	-2.2	-11.9	12.2	12.9		$\Delta L^* = 92.71 - 35.94$
	6	53.7	41.7	30.6	36	58.0	38.5	20.0	27	4.3	-3.1	-10.5	11.1	11.9		Gleichmäßigkeit
	7	57.2	37.9	27.9	36	61.6	34.7	16.8	26	4.3	-3.1	-10.9	11.5	12.3		$g^* = 41.7$
	8	60.8	34.1	25.1	36	65.9	29.7	14.8	26	5.1	-4.3	-10.2	11.2	12.3		
Z _d	9	64.3	30.3	22.3	36	69.8	25.4	12.6	26	5.4	-4.8	-9.6	10.9	12.2		Helligkeitsumfang relativ zu Offset
	10	67.9	26.5	19.5	36	73.7	21.2	10.2	26	5.8	-5.2	-9.2	10.7	12.2		$f^* = 73.3$
	11	71.4	22.7	16.8	36	77.6	17.1	7.5	24	6.2	-5.5	-9.2	10.8	12.4		
	12	75.0	18.9	14.0	36	81.3	13.1	5.2	22	6.4	-5.7	-8.7	10.5	12.3		Rot – Weiß
	13	78.5	15.1	11.2	37	85.0	8.9	3.2	20	6.5	-6.1	-7.9	10.1	12.0		rgb: (R – W) _d
	14	82.1	11.3	8.4	37	88.7	4.5	2.1	25	6.7	-6.7	-6.2	9.3	11.4		
	15	85.6	7.5	5.6	37	92.1	0.0	1.5	90	6.5	-7.4	-4.0	8.6	10.7		Mittlerer CIELAB-Abstand (17 Stufen)
	16	89.2	3.7	2.9	38	92.6	0.0	0.1	90	3.4	-3.6	-2.7	4.6	5.8		$\Delta H^*_{CIELAB} = 8.6$
W _d	17	92.7	0.0	0.1	135	92.7	0.0	0.1	135	0.0	0.0	0.0	0.0	0.0		$\Delta E^*_{CIELAB} = 9.6$
R _d	18	35.9	60.7	44.5	36	35.9	60.7	44.5	36	0.0	0.0	0.0	0.0	0.0		
	19	50.1	45.5	33.4	36	54.4	43.2	21.4	26	4.3	-2.2	-11.9	12.2	12.9		
Z _d	20	64.3	30.3	22.3	36	69.8	25.4	12.6	26	5.4	-4.8	-9.6	10.9	12.2		Mittlerer CIELAB-Abstand (5 Stufen)
	21	78.5	15.1	11.2	37	85.0	8.9	3.2	20	6.5	-6.1	-7.9	10.1	12.0		$\Delta H^*_{CIELAB} = 6.6$
W _d	22	92.7	0.0	0.1	135	92.7	0.0	0.1	135	0.0	0.0	0.0	0.0	0.0		$\Delta E^*_{CIELAB} = 7.4$
Mittlerer Farbwiedergabe-Index:															$R^*_{ab,m} = 58$	