

	i	LAB*a,ref			hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref			ΔH^*	ΔE^*	Start-Ausgabe S1
R _d	1	46.3	60.0	40.4	34		46.3	60.0	40.4	34	0.0	0.0	0.0	0.0	0.0	Kennzeichnung nach
	2	49.4	56.3	37.9	34		46.3	60.2	39.3	33	-3.0	4.0	1.4	4.2	5.2	ISO/IEC 15775:1999 Anhang G
	3	52.4	52.5	35.4	34		46.2	60.6	37.3	32	-6.2	8.1	1.9	8.3	10.4	& DIN 33866-1:2000 Anhang G
	4	55.5	48.8	32.8	34		47.1	60.0	34.0	30	-8.3	11.3	1.2	11.3	14.1	relative CIELAB Daten für "aus"
	5	58.6	45.0	30.3	34		48.6	58.4	30.4	27	-9.9	13.4	0.1	13.4	16.7	$\Delta L^* = 95.41 - 46.31$
	6	61.7	41.3	27.8	34		50.7	55.6	26.0	25	-10.8	14.3	-1.7	14.5	18.1	Gleichmäßigkeit
	7	64.7	37.5	25.3	34		53.3	51.8	22.8	24	-11.3	14.3	-2.4	14.5	18.5	$g^* = 11.8$
	8	67.8	33.8	22.7	34		56.9	46.7	20.7	24	-10.8	13.0	-1.9	13.1	17.1	
Z _d	9	70.9	30.0	20.2	34		60.7	41.1	18.9	25	-10.1	11.1	-1.2	11.2	15.1	Helligkeitsumfang relativ zu Offset
	10	73.9	26.3	17.7	34		64.9	34.8	17.4	27	-8.9	8.5	-0.2	8.6	12.4	$f^* = 63.4$
	11	77.0	22.5	15.2	34		70.6	27.0	14.4	28	-6.3	4.5	-0.7	4.6	7.9	
	12	80.1	18.8	12.6	34		75.6	21.2	10.6	27	-4.4	2.5	-1.9	3.2	5.5	Rot – Weiß
	13	83.1	15.0	10.1	34		80.1	15.9	8.3	28	-2.9	0.9	-1.7	2.0	3.6	rgb: (R – W) _d
	14	86.2	11.3	7.6	34		84.1	11.4	6.3	29	-2.0	0.1	-1.2	1.3	2.4	
	15	89.3	7.5	5.0	34		88.4	6.7	4.0	31	-0.8	-0.7	-0.9	1.3	1.6	Mittlerer CIELAB-Abstand (17 Stufen)
	16	92.3	3.8	2.5	34		90.0	3.2	1.9	31	-2.3	-0.4	-0.5	0.8	2.5	$\Delta H^*_{CIELAB} = 6.6$
W _d	17	95.4	0.0	0.0	0		95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 8.9$
R _d	18	46.3	60.0	40.4	34		46.3	60.0	40.4	34	0.0	0.0	0.0	0.0	0.0	
	19	58.6	45.0	30.3	34		48.6	58.4	30.4	27	-9.9	13.4	0.1	13.4	16.7	
Z _d	20	70.9	30.0	20.2	34		60.7	41.1	18.9	25	-10.1	11.1	-1.2	11.2	15.1	Mittlerer CIELAB-Abstand (5 Stufen)
	21	83.1	15.0	10.1	34		80.1	15.9	8.3	28	-2.9	0.9	-1.7	2.0	3.6	$\Delta H^*_{CIELAB} = 5.3$
W _d	22	95.4	0.0	0.0	0		95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 7.1$
Mittlerer Farbwiedergabe-Index:															$R^*_{ab,m} = 61$	