

Eingabe: Farbmetrisches Fernseh-Licht-System TL500a

mitrgb-Daten der vier Gerätefunktionen

(1 0 0)_d = Rot R_d

(1 1 0)_d = Gelb Y_d

(0 1 0)_d = Grün G_d

(0 0 1)_d = Blau B_d



TL500a: adaptierte CIECAM-Data									
L*	a*	b*	C*	h _{cb}	L*	a*	b*	C*	h _{cb}
R ₉₀	50.5	76.92	64.35	100.42	49				
Y ₉₀	92.65	-20.69	90.75	93.08	103				
G ₉₀	83.63	-82.75	79.9	115.84	136				
C ₉₀	86.88	-46.16	-13.55	48.12	196				
B ₉₀	30.39	76.05	-103.59	128.52	206				
M ₉₀	57.3	94.75	-58.41	110.97	129				
N ₉₀	0.01	0.0	0.0	0.0	0				
W ₉₀	95.41	0.0	0.0	0.0	0				
R ₂₀₀	29.92	58.74	27.99	65.87	25				
L ₂₀₀	81.26	-2.88	71.52	71.62	92				
C ₂₀₀	52.23	-82.41	13.6	44.55	162				
h ₂₀₀	30.57	1.41	-85.45	45.49	272				

Ausgabe: Farbmetrisches Fernseh-Licht-System TL500a

mit Barcodenummer

n= 01 bis 16

01 = Rot R_d

05 = Gelb Y_d

09 = Grün G_d

13 = Blau B_d

mit Barcodeposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-306:AG40



TL500a: adaptierte CIECAM-Data									
L*	a*	b*	C*	h _{cb}	L*	a*	b*	C*	h _{cb}
R ₉₀	50.5	76.92	64.35	100.42	49				
Y ₉₀	92.65	-20.69	90.75	93.08	103				
G ₉₀	83.63	-82.75	79.9	115.84	136				
C ₉₀	86.88	-46.16	-13.55	48.12	196				
B ₉₀	30.39	76.05	-103.59	128.52	206				
M ₉₀	57.3	94.75	-58.41	110.97	129				
N ₉₀	0.01	0.0	0.0	0.0	0				
W ₉₀	95.41	0.0	0.0	0.0	0				
R ₂₀₀	29.92	58.74	27.99	65.87	25				
L ₂₀₀	81.26	-2.88	71.52	71.62	92				
C ₂₀₀	52.23	-82.41	13.6	44.55	162				
h ₂₀₀	30.57	1.41	-85.45	45.49	272				

