

Eingabe: Farbmetrisches Fernseh-Licht-System TL500a

mitrgb₀-Daten der vier Gerätefunktionen

(1 0 0)₀ = Rot R₀

(1 1 0)₀ = Gelb Y₀

(0 1 0)₀ = Grün G₀

(0 0 1)₀ = Blau B₀



TL500a: adaptierte CIE1931-Daten									
L^*	a^*	b^*	C^*_{90}	h^*_{90}	L^*	a^*	b^*	C^*_{90}	h^*_{90}
R_{000}	50.5	76.92	64.35	100.42	49				
Y_{000}	92.66	-20.69	90.75	93.08	103				
G_{000}	83.63	-82.75	79.9	115.84	136				
B_{000}	86.88	-46.16	-13.55	48.12	196				
R_{000}	30.39	76.06	-103.59	128.52	306				
Y_{000}	57.3	94.75	-58.41	110.97	328				
G_{000}	0.01	0.0	0.0	0.0	0				
B_{000}	95.41	0.0	0.0	0.0	0				
R_{000}	29.92	58.74	27.99	65.87	25				
L_{000}	81.26	-2.88	71.56	71.62	92				
G_{000}	52.23	-82.41	13.6	44.55	162				
B_{000}	30.57	1.41	-85.46	45.49	272				

Ausgabe: Farbmetrisches Fernseh-Licht-System TL500a

mit Funktionsnummer

n= 01 bis 16

01 = Rot R₀

05 = Gelb Y₀

09 = Grün G₀

13 = Blau B₀

mit Funktionsposition

(Zeile und Spalte)

von Prüfvorlage ISO 9241-304:AG40



TL500a: adaptierte CIE1931-Daten									
L^*	a^*	b^*	C^*_{90}	h^*_{90}	L^*	a^*	b^*	C^*_{90}	h^*_{90}
R_{000}	50.5	76.92	64.35	100.42	49				
Y_{000}	92.66	-20.69	90.75	93.08	103				
G_{000}	83.63	-82.75	79.9	115.84	136				
B_{000}	86.88	-46.16	-13.55	48.12	196				
R_{000}	30.39	76.06	-103.59	128.52	306				
Y_{000}	57.3	94.75	-58.41	110.97	328				
G_{000}	0.01	0.0	0.0	0.0	0				
B_{000}	95.41	0.0	0.0	0.0	0				
R_{000}	29.92	58.74	27.99	65.87	25				
L_{000}	81.26	-2.88	71.56	71.62	92				
G_{000}	52.23	-82.41	13.6	44.55	162				
B_{000}	30.57	1.41	-85.46	45.49	272				

