

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für D65, $Y_N=0$, $Y_W=100$, $Y_m=520$, 770

λ_1	λ_2	λ_3	X_{100}	Y_{100}	Z_{100}	x	y	z	h_{xy}	i_d	i_c	i_e	i_c	i_e	Code
0	405	32	561	32.63	58.24	108.12	0.1639	0.2926	0.5433	193.7	16	483	37	589	Cm
6	435	32	562	29.15	58.83	88.75	0.1649	0.3328	0.5021	178.4	17	486	42	610	
10	450	32	563	23.50	59.45	52.42	0.1705	0.4408	0.3886	141.8	19	496	-1	496c	
12	460	33	565	20.95	60.35	34.09	0.1815	0.5229	0.2954	124.0	21	505	-1	505c	
12	465	33	567	22.02	61.7	34.1	0.1869	0.5236	0.2894	122.8	21	506	-1	506c	
14	470	33	569	21.54	62.76	20.07	0.2063	0.6013	0.1922	111.3	24	520	-1	520c	
15	475	34	573	23.83	65.32	15.0	0.2288	0.627	0.144	105.6	25	528	-1	528c	Gm
16	480	36	580	29.06	69.98	11.15	0.2637	0.635	0.1012	99.0	27	537	-1	537c	
17	485	39	595	42.16	78.77	8.33	0.3261	0.6093	0.0644	87.2	29	548	-1	548c	
18	490	-1	490c	77.1	93.81	6.24	0.4352	0.5295	0.0352	58.5	33	565	11	459	max
19	495	-1	495c	77.05	92.31	4.62	0.4428	0.5305	0.0265	57.1	33	566	12	462	
20	500	-1	500c	77.04	90.43	3.37	0.4509	0.5292	0.0197	55.3	33	567	12	464	
22	510	-1	510c	76.91	85.29	1.74	0.4691	0.5202	0.0106	50.6	33	569	13	469	
23	520	-1	519c	76.68	82.0	1.27	0.4793	0.5126	0.0079	47.7	34	570	14	471	Ym
25	530	-1	529c	75.55	74.07	0.68	0.5026	0.4927	0.0045	40.7	34	573	15	475	
27	540	-1	539c	73.28	64.93	0.37	0.5287	0.4685	0.0027	32.8	35	577	15	478	
28	545	-1	544c	71.68	60.16	0.29	0.5424	0.4553	0.0022	28.7	35	579	15	479	
29	550	-1	549c	69.73	55.3	0.23	0.5566	0.4414	0.0019	24.7	36	582	16	480	
30	555	-1	554c	67.43	50.45	0.2	0.571	0.4272	0.0017	20.8	36	584	16	481	
32	560	-1	560c	61.81	41.06	0.16	0.5998	0.3985	0.0016	13.6	37	589	16	483	
32	561	0	405	62.4	41.75	0.76	0.5947	0.3979	0.0072	13.7	37	589	16	483	Rm
32	562	6	435	65.88	41.16	20.14	0.518	0.3236	0.1583	358.4	42	610	17	486	
32	563	10	450	72.04	40.54	56.46	0.4261	0.2398	0.334	321.8	-1	496c	19	496	
33	565	12	460	74.09	39.64	74.79	0.393	0.2102	0.3967	304.0	-1	505c	21	505	
33	567	12	465	73.01	38.29	74.79	0.3923	0.2057	0.4018	302.9	-1	506c	21	506	
33	569	14	470	73.5	37.23	88.82	0.3683	0.1865	0.445	291.3	-1	520c	24	520	
34	573	15	475	71.2	34.67	93.88	0.3564	0.1735	0.4699	285.7	-1	528c	25	528	Mm
36	580	16	480	65.97	30.01	97.73	0.3405	0.1549	0.5044	279.1	-1	537c	27	537	
39	595	17	485	52.88	21.22	100.0	0.3005	0.1215	0.5757	267.2	-1	548c	29	548	
-1	490c	18	490	17.93	6.18	102.65	0.1414	0.0488	0.8097	238.5	-1	459	33	565	min
-1	495c	19	495	17.98	7.68	104.26	0.1384	0.0591	0.8024	237.1	12	462	33	566	
-1	500c	20	500	18.0	9.57	105.51	0.1352	0.0719	0.7928	235.4	12	464	33	567	
-1	510c	22	510	18.13	14.7	107.14	0.1295	0.105	0.7654	230.7	13	469	33	569	
-1	519c	23	520	18.36	17.99	107.61	0.1275	0.1249	0.7474	227.7	14	471	34	570	Bm
-1	529c	25	530	19.48	25.92	108.2	0.1268	0.1687	0.7043	220.7	15	475	34	573	
-1	539c	27	540	21.75	35.06	108.51	0.1315	0.212	0.6563	212.8	15	478	35	577	
-1	544c	28	545	23.36	39.83	108.59	0.1359	0.2318	0.6321	208.8	15	479	35	579	
-1	549c	29	550	25.31	44.69	108.65	0.1416	0.2501	0.6081	204.7	16	480	36	582	
-1	554c	30	555	27.61	49.54	108.68	0.1485	0.2666	0.5848	200.8	16	481	36	584	
-1	560c	32	560	33.23	58.93	108.72	0.1654	0.2933	0.5412	193.6	16	483	37	589	
W0	380	770	95.04	100.0	108.89	0.3127	0.329	0.3582	0.0						
N0	380	770	0.0	0.0	0.01	0.01	0.3127	0.329	0.3582	0.0					

