

Optimalfarben (o) RYGBCM von maximalem (m) CAB; D65, Y_{mc}=520, 770, CIEXYZ

Code, K=1:25 X Y Z x y z h_{xy} l_d a' b' l_c λ_c

R _o	570, 770	53.87	35.11	3.95	0.5796	0.3777	0.0425	237.6	38	592	16	484
Y _{mc}	520, 770	69.65	74.37	4.91	0.4676	0.4993	0.0033	225.2	34	570	14	471
G _o	470, 570	51.45	56.65	26.53	0.205	0.5413	0.2536	22.51	-1	512c		
C _o	380, 570	34.96	58.32	97.96	0.1827	0.3049	0.5122	214.7	16	484	38	592
B _o	380, 520	19.29	19.09	96.98	0.1425	0.141	0.7164	226.8	14	471	34	570
M _o	570, 470	67.34	36.77	75.13	0.3756	0.2051	0.4919	246.3	-1	512c	22	512
R _o	380, 470	16.88	5.25	75.09	0.1736	0.054	0.7722	230.4	9	445	32	563
C _o	470, 520	5.78	17.42	25.56	0.1186	0.3571	0.5241	222.7	17	488	52	663
G _o	520, 570	19.07	42.7	4.88	0.2861	0.6406	0.0732	217.0	28	541	-1	541c
W	380, 770	85.53	90.0	98.0	0.3127	0.329	0.3582	226.4	-1	538c	27	538
N	380, 770	3.42	3.6	3.92	0.3127	0.329	0.3582	226.4	16	482	-1	482c

Optimalfarben (o) RYGBCM von maximalem (m) CAB; D65, Y_{mc}=520, 770, YABJND

Code, K=1:25 Y A B CAB a' b' h_{ab} l_d a' b' l_c λ_c

R _o	570, 770	35.11	51.25	34.27	61.65	1.5342	-0.045	33.7	38	592	16	484
Y _{mc}	520, 770	74.37	-2.58	76.76	61.11	0.9365	-0.0264	91.9	34	570	14	472
G _o	470, 570	56.65	-80.97	35.15	88.27	3.7787	-0.1873	156.5	22	514	-1	514c
C _o	380, 570	58.32	-51.19	-34.44	61.7	0.5993	-0.6718	213.9	16	484	38	592
B _o	380, 520	19.09	28.85	-76.19	76.24	1.0103	-0.2014	272.1	14	471	33	569
M _o	570, 470	36.77	80.97	-36.08	88.25	1.8312	-0.8172	336.5	-1	508c	21	508
R _o	380, 470	5.25	29.72	-69.36	75.46	3.2121	-0.7127	293.1	9	445	32	562
C _o	470, 520	17.42	-26.92	-6.59	27.71	0.3322	-0.5869	193.7	17	488	-1	488c
G _o	520, 570	42.7	-53.77	41.62	68.0	0.4467	-0.0457	142.2	28	541	-1	542c
W	380, 770	90.0	0.0	0.0	0.01	0.9504	-0.4355	346.5	38	591	16	484
N	380, 770	3.6	0.0	0.0	0.01	0.9504	-0.4355	141.1	38	591	16	483

Optimalfarben (o) RYGBCM von maximalem (m) C _{AB} ; D65, Y _{mc} =520, 770, CIELAB 76												
Code, K=1:25	L*	a*	b*	C _{ab}	a'	b'	h _{ab}	l _d	a'	b'	l _c	λ _c
R _o 570, 770	65.84	61.03	74.79	96.54	0.2527	-0.0404	50.7	41	608	15	477	
Y _{mc} 520, 770	89.1	-2.22	109.93	109.95	0.2144	-0.0338	91.1	34	570	14	472	
G _o 470, 570	79.98	-109.2640.55	116.54	0.1585	-0.065	159.6	22	514	-1	514c		
C _o 380, 570	80.92	-59.5	-25.96	64.84	0.1847	-0.0995	203.5	16	482	-1	482c	
B _o 380, 520	50.81	5.92	-77.24	77.46	0.2199	-0.144	274.1	14	471	33	568	
M _o 570, 470	67.11	87.52	-33.43	93.69	0.2681	-0.1063	339.0	-1	514c	22	514	
R _o 380, 470	27.48	93.72	-101.73	138.32	0.3233	-0.2032	312.6	11	455	27	539	
C _o 470, 520	48.79	-82.47	-11.67	83.29	0.1517	-0.0952	188.0	17	487	-1	487c	
G _o 520, 570	71.36	-83.75	79.52	115.49	0.1675	-0.0406	136.4	27	539	9	448	
W 380, 770	96.0	0.0	0.0	0.0	0.2154	-0.0861	329.4	-1	524c	24	524	
N 380, 770	22.33	0.0	0.0	0.0	0.2154	-0.0861	279.5	14	472	34	571	

Optimalfarben (o) RYGBCM von maximalem (m) CAB; D65, Y_{mc}=520, 770, LABHNU 79

Code, K=1:25 L* A* B* C_{ab} a' b' h_{ab} l_d a' b' l_c λ_c

R _o	570, 770	65.84	63.71	57.98	86.15	0.1689	-0.0544	42.3	38	594	16	480
Y _{mc}	520, 770	89.1	-1.94	81.22	81.24	0.1291	-0.0512	91.3	34	570	14	472
G _o	470, 570	79.98	-173.38	35.07	81.15	0.0919	-0.0716	154.3	21	508	9	449
C _o	380, 570	80.92	-45.37	-23.89	51.28	0.1066	-0.1022	207.7	16	483	42	613
B _o	380, 520	50.81	5.33	-73.34	73.53	0.134	-0.1447	274.1	14	471	33	569
M _o	570, 470	67.11	97.62	-30.98	102.42	0.1887	-0.1085	342.3	7	438	20	502
R _o	380, 470	27.48	131.08	-98.28	163.83	0.2808	-0.2029	323.1	11	458	24	522
C _o	470, 520	48.79	-53.41	-10.69	54.47	0.0888	-0.0891	191.3	17	488	-1	488c
G _o	520, 570	71.36	-58.68	61.71	85.16	0.0964	-0.0545	133.5	27	538	12	462
W	380, 770	96.0	0.0	0.0	0.0	0.13	-0.0899	345.9	12	461	27	535
N	380, 770	22.33	0.0	0.0	0.0	0.13	-0.0899	156.1	21	505	9	445

