

Ostwald-Optimalfarben (o), maximales (m) C _{AB,10} für D65, Y _{N,10} =0, Y _{W,10} =90, Y _m =520_770																		
i ₁ , λ ₁	i ₂ , λ ₂	Y ₁₀	A _{2,10}	B _{2,10}	C _{AB,2,10}	a _{2,10}	b _{2,10}	h _{xy,2,10}	i _d , λ _d	i _c , λ _c	Code							
0 405	31 556	52.33	−52.91	−31.77	61.72	0.2111	−0.7327	210.9	15 476	37 585	Cm							
6 435	31 557	53.26	−56.05	−15.15	58.06	0.1946	−0.5715	195.1	16 480	44 621								
10 450	31 559	53.56	−58.87	10.74	59.84	0.1759	−0.3289	169.6	18 492	−1 492c								
11 460	32 562	54.81	−58.9	18.19	61.65	0.1857	−0.2632	162.8	19 498	−1 498c								
12 465	33 565	56.0	−58.53	24.95	63.63	0.1975	−0.2064	156.9	21 506	−1 506c								
14 470	34 570	57.89	−55.44	35.53	65.85	0.2325	−0.1223	147.3	24 522	−1 522c	Gm							
15 475	35 579	63.11	−49.55	43.11	65.68	0.3015	−0.0876	138.9	26 534	−1 534c								
16 480	41 606	74.33	−26.68	55.03	61.16	0.472	−0.059	115.8	30 550	−1 550c								
16 485	−1 484c	83.34	1.49	62.76	62.78	0.6227	−0.0526	88.6	32 560	10 454	max							
18 490	−1 490c	80.55	7.16	63.15	63.55	0.6511	−0.0372	83.5	32 562	11 459								
19 495	−1 495c	78.81	10.57	62.5	63.39	0.6692	−0.0326	80.4	32 563	12 461								
19 500	−1 499c	78.81	10.57	62.5	63.39	0.6692	−0.0326	80.4	32 563	12 461								
22 510	−1 510c	71.94	22.69	57.96	62.25	0.7417	−0.0263	68.6	33 566	13 466								
23 520	−1 519c	69.1	27.09	55.75	61.99	0.7724	−0.0258	64.0	33 568	13 468	Ym							
26 530	−1 530c	59.04	39.99	47.48	62.08	0.8865	−0.0271	49.8	34 573	14 472								
27 540	−1 539c	55.35	43.74	44.36	62.3	0.9316	−0.0284	45.4	35 576	14 473								
28 545	−1 544c	51.58	47.01	41.16	62.49	0.9801	−0.0302	41.2	35 578	14 474								
29 550	−1 549c	47.76	49.72	37.9	62.52	1.0319	−0.0324	37.3	36 580	15 475								
31 555	−1 555c	40.2	53.05	31.42	61.66	1.1433	−0.0384	30.6	37 586	15 476								
32 560	10 451	38.17	58.81	−10.44	59.73	1.2318	−0.566	349.9	−1 491c	18 491								
31 556	0 405	47.66	52.92	31.77	61.72	1.0597	−0.0958	30.9	37 585	15 476	Rm							
31 557	6 435	46.73	56.05	15.15	58.06	1.0952	−0.267	15.1	44 621	16 480								
31 559	10 450	46.43	58.86	−10.74	59.83	1.1227	−0.5448	349.6	−1 492c	18 492								
32 562	11 460	45.18	58.89	−18.18	61.63	1.1369	−0.6304	342.8	−1 498c	19 498								
33 565	12 465	43.99	58.51	−24.95	63.61	1.1476	−0.7128	336.9	−1 506c	21 506								
34 570	14 470	42.1	55.42	−35.51	65.82	1.142	−0.8509	327.3	−1 522c	24 522	Mm							
35 579	15 475	36.88	49.54	−43.1	65.66	1.1529	−1.0135	318.9	−1 534c	26 534								
41 606	16 480	25.66	26.67	−55.0	61.13	1.0313	−1.5009	295.8	−1 550c	30 550								
−1 484c	16 485	16.65	−1.49	−62.72	62.74	0.5796	−2.3126	268.6	10 454	32 560					min			
−1 490c	18 490	19.44	−7.16	−63.11	63.52	0.4682	−2.0519	263.5	11 459	32 562								
−1 495c	19 495	21.18	−10.56	−62.47	63.36	0.4161	−1.9035	260.4	12 461	32 563								
−1 499c	19 500	21.18	−10.56	−62.47	63.36	0.4161	−1.9035	260.4	12 461	32 563								
−1 510c	22 510	28.05	−22.68	−57.94	62.22	0.2921	−1.4619	248.6	13 466	33 566								
−1 519c	23 520	30.89	−27.08	−55.73	61.97	0.2648	−1.3312	244.0	13 468	33 568					Bm			
−1 530c	26 530	40.95	−39.98	−47.47	62.06	0.225	−1.0087	229.8	14 472	34 573								
−1 539c	27 540	44.64	−43.73	−44.36	62.29	0.2237	−0.926	225.4	14 473	35 576								
−1 544c	28 545	48.41	−47.01	−41.16	62.48	0.2271	−0.8543	221.2	14 474	35 578								
−1 549c	29 550	52.23	−49.72	−37.9	62.52	0.2348	−0.792	217.3	15 475	36 580								
−1 555c	31 555	59.79	−53.04	−31.42	61.65	0.2607	−0.6919	210.6	15 476	37 586								
10 451	32 560	61.82	−58.82	10.44	59.74	0.2349	−0.3447	169.9	18 491	−1 491c								
W0 380	770	90.0	0.0	0.0	0.0	0.6155	−0.3433	0.0	B _c =0,800									
N0 380	770	3.6	0.0	0.0	0.0	0.6155	−0.3433	0.0	x _c =0,110									