

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =3,6, Y _W =90, Y _m =520_770															
i, λ ₁	i ₂	λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d	λ _d	i _c	λ _c		Code
1	405	32	564	29.26	53.83	73.48	0.1869	0.3438	0.4692	185.2	17	486	38	592	Cm
7	435	33	565	26.01	53.61	57.83	0.1892	0.39	0.4207	168.6	18	490	46	631	
10	450	33	566	23.26	54.16	39.66	0.1986	0.4625	0.3387	144.6	19	497	-1	497c	
12	460	33	567	22.04	54.86	27.4	0.2113	0.5259	0.2626	128.7	21	506	-1	506c	
13	465	33	568	22.01	55.56	22.12	0.2208	0.5572	0.2218	122.1	22	512	-1	512c	
14	470	34	570	22.15	56.11	17.7	0.2308	0.5846	0.1844	116.9	23	519	-1	519c Gm	
15	475	34	573	23.92	58.04	14.12	0.2489	0.604	0.1469	111.4	25	527	-1	527c	
15	480	35	578	27.41	61.49	14.13	0.266	0.5968	0.1371	108.4	26	532	-1	532c	
17	485	37	587	33.99	66.01	9.3	0.3109	0.6039	0.0851	98.0	28	544	-1	544c	
18	490	44	620	59.95	79.56	7.5	0.407	0.5402	0.0526	71.3	32	561	-1	561c	
19	495	-1	495c	75.28	84.51	6.54	0.4525	0.5081	0.0393	54.4	33	568	12	463	max
20	500	-1	500c	75.26	83.07	5.58	0.4591	0.5067	0.034	52.5	33	569	13	466	
22	510	-1	510c	75.16	79.06	4.31	0.4741	0.4986	0.0272	47.4	34	571	14	471	
23	520	-1	519c	74.98	76.43	3.93	0.4826	0.492	0.0253	44.2	34	572	14	473	Ym
25	530	-1	529c	74.05	69.95	3.45	0.5021	0.4743	0.0234	36.4	35	575	15	477	
27	540	-1	539c	72.16	62.35	3.2	0.524	0.4527	0.0232	27.8	35	579	16	480	
28	545	-1	544c	70.81	58.33	3.13	0.5353	0.4409	0.0236	23.4	36	581	16	481	
29	550	-1	549c	69.15	54.19	3.08	0.5469	0.4286	0.0244	19.1	36	583	16	483	
30	555	-1	554c	67.17	50.01	3.05	0.5586	0.4159	0.0254	15.0	37	585	16	484	
32	560	-1	560c	62.28	41.85	3.02	0.5812	0.3905	0.0281	7.7	38	590	17	486	
32	564	1	405	67.15	46.16	9.01	0.5489	0.3773	0.0736	5.2	38	592	17	486	Rm
33	565	7	435	70.4	46.38	24.66	0.4977	0.3279	0.1743	348.6	46	631	18	490	
33	566	10	450	73.15	45.83	42.83	0.452	0.2832	0.2646	324.7	-1	497c	19	497	
33	567	12	460	74.37	45.13	55.09	0.4259	0.2585	0.3155	308.7	-1	506c	21	506	
33	568	13	465	74.4	44.43	60.37	0.4151	0.2479	0.3368	302.1	-1	512c	22	512	
34	570	14	470	74.26	43.88	64.78	0.4059	0.2398	0.3541	296.9	-1	519c	23	519	Mm
34	573	15	475	72.5	41.95	68.37	0.3965	0.2294	0.3739	291.5	-1	527c	25	527	
35	578	15	480	69.0	38.5	68.36	0.3923	0.2189	0.3887	288.5	-1	532c	26	532	
37	587	17	485	62.42	33.98	73.19	0.368	0.2003	0.4315	278.0	-1	544c	28	544	
44	620	18	490	36.46	20.43	74.74	0.277	0.1552	0.5677	251.3	-1	561c	32	561	
-1	495c	19	495	21.14	15.48	75.95	0.1877	0.1375	0.6746	234.2	12	463	33	568	min
-1	500c	20	500	21.15	16.92	76.91	0.1839	0.1471	0.6688	232.5	13	466	33	569	
-1	510c	22	510	21.25	20.93	78.18	0.1765	0.1739	0.6494	227.5	14	471	34	571	
-1	519c	23	520	21.44	23.56	78.56	0.1735	0.1907	0.6357	224.2	14	473	34	572	Bm
-1	529c	25	530	22.36	30.04	79.04	0.1701	0.2285	0.6013	216.5	15	477	35	575	
-1	539c	27	540	24.25	37.64	79.29	0.1717	0.2666	0.5615	207.8	16	480	35	579	
-1	544c	28	545	25.6	41.66	79.36	0.1746	0.2841	0.5412	203.5	16	481	36	581	
-1	549c	29	550	27.26	45.8	79.41	0.1788	0.3004	0.5207	199.2	16	483	36	583	
-1	554c	30	555	29.24	49.98	79.44	0.1843	0.315	0.5006	195.0	16	484	37	585	
-1	560c	32	560	34.13	58.14	79.47	0.1987	0.3385	0.4627	187.7	17	486	38	590	
W0	380	770	86.78	90.0	74.24	0.3457	0.3585	0.2957	0.0						
N0	380	770	3.47	3.6	2.96	0.3457	0.3585	0.2957	0.0						

AGU7/0-7N

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für D50, Y _N =3,6, Y _W =90, Y _m =520_770															
i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d , λ _d	i _c , λ _c	Code				
1 405 32 564	53.83	-56.59	-29.05	63.62	0.5434	-0.5457	207.1	17 486 38 592	Cm						
7 435 33 565	53.61	-64.17	-13.59	65.6	0.4851	-0.4313	191.9	18 490 46 631							
10 450 33 566	54.16	-72.38	50.1	72.56	0.4294	-0.2928	176.0	19 497 -1 497c							
12 460 33 567	54.86	-77.11	17.85	79.14	0.4017	-0.1997	166.9	21 506 -1 506c							
13 465 33 568	55.56	-78.87	23.7	82.35	0.3961	-0.1592	163.2	22 512 -1 512c							
14 470 34 570	56.11	-79.85	28.57	84.81	0.3947	-0.1261	160.3	23 519 -1 519c Gm							
15 475 34 573	58.04	-80.09	33.75	86.91	0.412	-0.0973	157.1	25 527 -1 527c							
15 480 35 578	61.49	-79.68	36.59	87.68	0.4456	-0.0919	155.3	26 532 -1 532c							
17 485 37 587	66.01	-74.12	45.14	86.79	0.5148	-0.0563	148.6	28 544 -1 544c							
18 490 44 620	79.56	-41.87	57.86	71.42	0.7534	-0.0389	125.8	32 561 -1 561c							
19 495 -1 495c	84.51	-15.51	63.16	65.04	0.8905	-0.0309	103.7	33 568 12 463	max						
20 500 -1 500c	83.07	-12.07	62.93	64.08	0.9058	-0.0268	100.8	33 569 13 466							
22 510 -1 510c	79.06	-2.65	60.89	69.04	0.9505	-0.0218	92.4	34 571 14 471							
23 520 -1 519c	76.43	3.22	59.1	59.18	0.9808	-0.0205	86.8	34 572 14 473	Ym						
25 530 -1 529c	69.95	16.52	54.23	56.7	1.0584	-0.0197	73.0	35 575 15 477							
27 540 -1 539c	62.35	30.11	48.22	56.85	1.1571	-0.0210	58.0	35 579 16 480							
28 545 -1 544c	58.33	36.43	44.97	57.87	1.2137	-0.0204	50.9	36 581 16 481							
29 550 -1 549c	54.19	42.24	41.6	59.29	1.2758	-0.0227	44.5	36 583 16 483							
30 555 -1 554c	50.01	47.36	38.19	60.84	1.3427	-0.0244	38.8	37 585 16 484							
32 560 -1 560c	41.85	54.81	31.49	63.21	1.4878	-0.0288	29.8	38 590 17 486							
32 564 1 405	46.16	56.59	29.05	63.62	1.4543	-0.078	27.1	38 592 17 486	Rm						
33 565 7 435	46.38	64.17	13.59	65.59	1.5173	-0.2126	11.9	46 631 18 490							
33 566 10 450	45.83	72.37	-5.01	72.55	1.5956	-0.3736	356.0	-1 497c 19 497							
33 567 12 460	45.13	77.09	-17.84	79.13	1.6471	-0.488	346.9	-1 506c 21 506							
33 568 13 465	44.43	78.85	-23.7	82.33	1.6737	-0.5432	343.2	-1 512c 22 512							
34 570 14 470	43.88	79.83	-28.57	84.79	1.6917	-0.5903	340.3	-1 519c 23 519	Mm						
34 573 15 475	41.95	80.07	-33.74	86.89	1.7274	-0.6516	337.1	-1 527c 25 527							
35 578 15 480	38.5	79.66	-36.57	87.65	1.7916	-0.7099	335.3	-1 532c 26 532							
37 587 17 485	33.98	74.1	-45.12	86.76	1.8361	-0.861	328.6	-1 544c 28 544							
44 620 18 490	20.43	41.86	-57.83	71.39	1.7832	-1.4618	305.8	-1 561c 32 561							
-1 495c 19 495	15.48	15.5	-63.13	65.0	1.3645	-1.9609	283.7	12 463 33 568	min						
-1 500c 20 500	16.92	12.07	-62.9	64.04	1.2492	-1.8165	280.8	13 466 33 569							
-1 510c 22 510	20.93	2.64	-60.86	60.92	1.0145	-1.4926	272.4	14 471 34 571							
-1 519c 23 520	23.56	-3.22	-59.08	59.17	0.9092	-1.3327	266.8	14 473 34 572	Bm						
-1 529c 25 530	30.04	-16.51	-54.22	56.68	0.744	-1.0518	253.0	15 477 35 575							
-1 539c 27 540	37.64	-30.11	-48.21	56.84	0.644	-0.8422	238.0	16 480 35 579							
-1 544c 28 545	41.66	-36.42	-44.97	57.87	0.6142	-0.7615	230.9	16 481 36 581							
-1 549c 29 550	45.8	-42.24	-41.6	59.29	0.595	-0.6931	224.5	16 483 36 583							
-1 554c 30 555	49.98	-47.36	-38.19	60.84	0.5849	-0.6355	218.8	16 484 37 585							
-1 560c 32 560	58.14	-54.81	-31.49	63.21	0.5869	-0.5465	209.8	17 486 38 590							
W0 380	770	90	0.0	0.0	0.0	0.9639	-0.3298	0.0	B _c =1,000						
N0 380	770	3.6	0.0	0.0	0.0	0.9639	-0.3298	0.0	Y _c =0.000						