

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =3,6, Y _W =90, Y _m =520_770															
i, λ _i	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code				
0 405	32 563	31.65	53.56	93.3	0.1773	0.3	0.5226	19.22	16 483	38 590	Cm				
6 435	32 563	28.3	54.12	74.65	0.1801	0.3445	0.4752	17.47	17 487	44 621					
10 450	33 565	22.96	54.2	45.12	0.1877	0.4432	0.3689	14.01	19 497	-1 497c					
11 460	33 566	22.85	55.45	37.84	0.1967	0.4774	0.3258	13.05	20 502	-1 502c					
13 465	33 568	21.78	56.12	24.97	0.2117	0.5455	0.2427	11.72	22 513	-1 513c					
14 470	34 570	22.2	57.09	19.98	0.2236	0.575	0.2012	11.19	24 521	-1 521c	Gm				
15 475	34 574	24.59	59.7	16.0	0.2451	0.5952	0.1595	10.61	25 529	-1 529c					
15 480	36 580	28.98	63.87	16.01	0.2662	0.5866	0.147	10.22	27 535	-1 535c					
17 485	39 595	39.81	70.8	10.63	0.3283	0.5839	0.0877	8.84	29 549	-1 549c					
18 490	-1 490c	72.35	85.0	8.89	0.4352	0.5113	0.0534	5.73	33 566	11 459	max				
19 495	-1 495c	72.31	83.76	7.55	0.4419	0.5109	0.0461	5.67	33 567	12 461					
20 500	-1 500c	72.29	82.2	6.51	0.449	0.5105	0.0404	5.45	33 568	12 464					
22 510	-1 510c	72.19	77.89	5.14	0.465	0.5017	0.0331	4.99	34 570	13 469					
24 520	-1 520c	71.62	71.91	4.45	0.4839	0.4859	0.0301	4.35	34 572	14 473	Ym				
25 530	-1 529c	71.04	68.43	4.25	0.4943	0.4761	0.0295	3.99	34 574	15 475					
27 540	-1 539c	69.15	60.8	3.99	0.5162	0.4539	0.0298	3.21	35 578	15 478					
29 545	-1 545c	66.16	52.69	3.87	0.539	0.4293	0.0315	2.42	36 582	16 480					
29 550	-1 549c	66.16	52.69	3.87	0.539	0.4293	0.0315	2.42	36 582	16 480					
30 555	-1 554c	64.21	48.59	3.84	0.5504	0.4165	0.0329	2.03	36 584	16 481					
32 560	-1 560c	59.36	40.5	3.81	0.5725	0.3906	0.0367	1.32	37 589	16 483					
32 563	0 405	65.41	46.43	11.27	0.5312	0.3771	0.0915	12.2	38 590	16 483	Rm				
32 563	6 435	68.76	45.87	29.92	0.4756	0.3173	0.2069	35.47	44 621	17 487					
33 565	10 450	74.1	45.79	59.44	0.4131	0.2553	0.3314	32.02	-1 497c	19 497					
33 566	11 460	74.21	44.54	66.72	0.4001	0.2401	0.3597	31.06	-1 502c	20 502					
33 568	13 465	75.28	43.87	79.59	0.3787	0.2207	0.4004	29.72	-1 513c	22 513					
34 570	14 470	74.86	42.9	84.59	0.3699	0.212	0.418	29.19	-1 521c	24 521	Mm				
34 574	15 475	72.7	40.29	88.56	0.3599	0.2001	0.4398	28.62	-1 529c	25 529					
36 580	15 480	68.08	36.12	88.55	0.3531	0.1874	0.4594	28.23	-1 535c	27 535					
39 595	17 485	27.5	29.19	93.93	0.3173	0.1618	0.5207	26.85	-1 549c	29 549					
-1 490c	18 490	24.71	14.99	95.68	0.1825	0.1107	0.7067	23.77	11 459	33 566	min				
-1 495c	19 495	24.75	16.23	97.02	0.1793	0.1176	0.7029	23.63	12 461	33 567					
-1 500c	20 500	24.77	17.79	98.05	0.1761	0.1265	0.6972	23.46	12 464	33 568					
-1 510c	22 510	24.87	22.1	99.42	0.1699	0.1509	0.679	22.99	13 469	34 570					
-1 520c	24 520	25.44	28.08	100.11	0.1655	0.1827	0.6516	22.36	14 473	34 572	Bm				
-1 529c	25 530	26.02	31.56	100.32	0.1647	0.1999	0.6353	21.99	15 475	34 574					
-1 539c	27 540	29.91	39.19	100.57	0.1664	0.2337	0.5997	21.22	15 478	35 578					
-1 545c	29 545	30.9	47.3	100.69	0.1727	0.2644	0.5628	20.42	16 480	36 582					
-1 549c	29 550	30.9	47.3	100.69	0.1727	0.2644	0.5628	20.42	16 480	36 582					
-1 554c	30 555	32.85	51.4	100.72	0.1776	0.2778	0.5445	20.04	16 481	36 584					
-1 560c	32 560	37.7	59.49	100.75	0.1904	0.3005	0.5089	19.32	16 483	37 589					
W0	380	770	87.36	89.99	94.11	0.3218	0.3315	0.3466	0.0						
N0	380	770	3.49	3.59	3.76	0.3218	0.3315	0.3466	0.0						

AGV7-7N

Ostwald-Optimalfarben (o), maximales (m) C _{AB} für P60, Y _N =3,6, Y _W =90, Y _m =520_770															
i, λ _i	i ₂	λ ₂	Y	A	B	C _{AB}	a	b	h _{xy}	i _d	λ _d	i _c	λ _c	Code	
0	405	32	563	53.56	-50.83	-37.27	63.03	0.5907	-0.6965	21.62	16	483	38	590	Cm
6	435	32	563	54.12	-60.57	-18.04	63.2	0.5227	-0.5515	19.65	17	487	44	621	
10	450	33	565	54.2	-74.1	11.55	74.99	0.4236	-0.3329	17.11	19	497	-1	497c	
11	460	33	566	55.45	-77.42	20.13	79.99	0.4119	-0.2729	16.54	20	502	-1	502c	
13	465	33	568	56.12	-81.71	33.7	88.38	0.388	-0.1779	15.75	22	513	-1	513c	
14	470	34	570	57.09	-83.01	39.7	92.02	0.3888	-0.1399	15.44	24	521	-1	521c	Gm
15	475	34	574	59.7	-83.37	46.41	95.41	0.4118	-0.1072	15.08	25	529	-1	529c	
15	480	36	580	63.87	-82.5	50.76	96.86	0.4537	-0.1002	14.83	27	535	-1	535c	
17	485	39	595	70.8	-72.25	63.39	96.12	0.5622	-0.06	13.87	29	549	-1	549c	
18	490	-1	490c	85.0	-25.38	79.98	83.91	0.8509	-0.0418	10.76	33	566	11	459	max
19	495	-1	495c	83.76	-22.46	80.01	83.11	0.8631	-0.036	10.56	33	567	12	461	
20	500	-1	500c	82.2	-18.71	79.42	81.59	0.8793	-0.0316	10.32	33	568	12	464	
22	510	-1	510c	77.89	-8.53	76.28	76.76	0.9265	-0.0264	9.63	34	570	13	469	
24	520	-1	520c	71.91	4.55	70.72	70.87	0.9957	-0.0247	8.63	34	572	14	473	Ym
25	530	-1	529c	68.43	11.56	67.29	68.27	1.038	-0.0248	8.02	34	574	15	475	
27	540	-1	539c	60.8	25.33	59.67	64.73	1.137	-0.0262	6.69	35	578	15	478	
29	545	-1	545c	52.69	37.52	51.21	63.48	1.2552	-0.0294	5.37	36	582	16	480	
29	550	-1	549c	52.69	37.52	51.21	63.48	1.2552	-0.0294	5.37	36	582	16	480	
30	555	-1	554c	48.59	42.61	46.95	63.4	1.3211	-0.0316	4.77	36	584	16	481	
32	560	-1	560c	40.5	50.12	38.52	63.21	1.4654	-0.0376	3.75	37	589	16	483	
32	563	0	405	46.43	50.84	37.27	63.04	1.4083	-0.097	3.62	38	590	16	483	Rm
32	563	6	435	45.87	60.57	18.04	63.2	1.4985	-0.2608	16.5	44	621	17	487	
33	565	10	450	45.79	74.08	-11.55	74.98	1.6175	-0.519	35.11	-1	497c	19	497	
33	566	11	460	44.54	77.4	-20.13	79.98	1.6655	-0.5989	34.54	-1	502c	20	502	
33	568	13	465	43.87	81.68	-33.69	88.36	1.7151	-0.7253	33.75	-1	513c	22	513	
34	570	14	470	42.9	82.98	-39.69	91.99	1.7441	-0.7882	33.44	-1	521c	24	521	Mm
34	574	15	475	40.29	83.34	-46.39	95.38	1.7977	-0.8786	33.08	-1	529c	25	529	
36	580	15	480	36.12	82.47	-50.74	96.83	1.8835	-0.9799	32.83	-1	535c	27	535	
39	595	17	485	29.19	72.22	-63.36	96.08	1.9601	-1.2864	31.87	-1	549c	29	549	
-1	490c	18	490	19.49	25.36	-79.92	83.85	1.6471	-2.5507	28.76	11	459	33	566	min
-1	495c	19	495	16.23	22.44	-79.96	83.05	1.5234	-2.3881	28.56	12	461	33	567	
-1	500c	20	500	17.79	18.7	-79.37	81.54	1.3907	-2.2019	28.32	12	464	33	568	
-1	510c	22	510	22.1	8.53	-76.24	76.72	1.1247	-1.7979	27.63	13	469	34	570	
-1	520c	24	520	28.08	-4.55	-70.7	70.84	0.9055	-1.4253	26.63	14	473	34	572	Bm
-1	529c	25	530	31.56	-11.56	-67.27	68.25	0.8238	-1.2706	26.02	15	475	34	574	
-1	539c	27	540	39.19	-25.32	-59.55	64.72	0.7119	-1.0259	24.69	15	478	35	578	
-1	545c	29	545	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	23.37	16	480	36	582	
-1	549c	29	550	47.3	-37.51	-51.2	63.47	0.6531	-0.8511	23.37	16	480	36	582	
-1	554c	30	555	51.4	-42.6	-46.94	63.4	0.6388	-0.7834	22.77	16	481	36	584	
-1	560c	32	560	59.49	-50.11	-38.52	63.21	0.6334	-0.6771	21.75	16	483	37	589	
W0	380	770	89.99	0.0	0.0	0.0	0.0	0.9704	-0.4181	0.0				Bc=1,000	
N0	380	770	3.59	0.0	0.0	0.0	0.0	0.9704	-0.4181	0.0				Yc=0,000	