

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1
O	1	46.3	60.1	47.0	38	46.3	60.1	47.0	38	0.0	0.0	0.0	0.0	0.0	Specification according to
	2	49.4	56.3	44.1	38	48.0	57.7	46.4	39	-1.3	1.4	2.3	2.7	3.0	ISO/IEC 15775:1999 Annex G
	3	52.4	52.6	41.1	38	49.4	55.6	45.1	39	-3.0	3.0	4.0	5.0	5.9	and DIN 33866-1:2000 Annex G
	4	55.5	48.8	38.2	38	51.6	52.3	41.3	38	-3.8	3.5	3.1	4.7	6.1	relative CIELAB data used for "out"
	5	58.6	45.1	35.3	38	53.2	49.9	39.4	38	-5.2	4.8	4.2	6.4	8.3	$\Delta L^* = 95.3 - 46.32$
	6	61.6	41.3	32.3	38	56.0	45.6	37.5	39	-5.5	4.3	5.2	6.7	8.8	Regularity
	7	64.7	37.6	29.4	38	58.5	41.5	36.2	41	-6.0	3.9	6.8	7.9	10.0	$g^* = 41.7$
	8	67.7	33.8	26.4	38	62.8	34.9	35.0	45	-4.9	1.1	8.6	8.6	10.0	
	9	70.8	30.1	23.5	38	66.3	28.5	33.0	49	-4.4	-1.4	9.5	9.6	10.6	Lightness gamut relative to offset
	10	73.9	26.3	20.6	38	70.3	21.3	31.9	56	-3.5	-4.9	11.3	12.4	12.9	$f^* = 63.3$
	11	76.9	22.5	17.6	38	72.5	15.9	30.7	63	-4.3	-6.5	13.1	14.7	15.3	
	12	80.0	18.8	14.7	38	75.9	10.2	28.2	70	-4.0	-8.5	13.5	16.0	16.5	Orange red – White
	13	83.1	15.0	11.8	38	78.8	7.6	21.7	71	-4.2	-7.3	10.0	12.4	13.1	cmy0: O – W
	14	86.1	11.3	8.8	38	81.9	5.3	16.2	72	-4.2	-5.9	7.4	9.5	10.4	
	15	89.2	7.5	5.9	38	85.2	2.6	12.2	78	-3.9	-4.8	6.3	8.0	8.9	Mean CIELAB difference (17 steps)
	16	92.2	3.8	2.9	38	88.3	2.8	5.5	63	-3.8	-0.9	2.6	2.7	4.8	$\Delta H^*_{CIELAB} = 7.5$
W	17	95.3	0.0	0.0	0	95.3	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 8.5$
O	18	46.3	60.1	47.0	38	46.3	60.1	47.0	38	0.0	0.0	0.0	0.0	0.0	
	19	58.6	45.1	35.3	38	53.2	49.9	39.4	38	-5.2	4.8	4.2	6.4	8.3	
	20	70.8	30.1	23.5	38	66.3	28.5	33.0	49	-4.4	-1.4	9.5	9.6	10.6	Mean CIELAB difference (5 steps)
	21	83.1	15.0	11.8	38	78.8	7.6	21.7	71	-4.2	-7.3	10.0	12.4	13.1	$\Delta H^*_{CIELAB} = 5.7$
W	22	95.3	0.0	0.0	0	95.3	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 6.4$
Mean colour reproduction index: $R^*_{ab,m} = 63$															

T	i	LAB*a,ref		hab,ref	LAB*a,out		hab,out	LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1			
Y	1	90.7	-16.8	112.8	99	90.7	-16.8	112.8	99	0.0	0.0	0.0	0.0	0.0	Specification according to
	2	91.0	-15.7	105.8	99	90.8	-17.1	109.7	99	-0.1	-1.3	3.9	4.2	4.2	ISO/IEC 15775:1999 Annex G
	3	91.3	-14.7	98.7	99	91.0	-17.2	105.5	99	-0.1	-2.4	6.8	7.2	7.2	and DIN 33866-1:2000 Annex G
	4	91.6	-13.6	91.7	99	91.0	-17.3	99.3	100	-0.5	-3.6	7.6	8.4	8.5	relative CIELAB data used for "out"
	5	91.9	-12.6	84.7	99	91.3	-17.0	91.1	101	-0.4	-4.3	6.4	7.8	7.8	$\Delta L^* = 95.43 - 90.68$
	6	92.2	-11.5	77.6	99	91.8	-16.2	78.9	102	-0.3	-4.6	1.3	4.8	4.9	Regularity
	7	92.5	-10.5	70.6	99	92.0	-15.4	70.5	102	-0.4	-4.8	0.0	4.9	5.0	$g^* = 43.8$
	8	92.8	-9.4	63.6	99	92.2	-14.9	65.2	103	-0.5	-5.4	1.6	5.7	5.8	
	9	93.1	-8.4	56.6	98	92.6	-13.9	57.1	104	-0.3	-5.5	0.5	5.6	5.6	Lightness gamut relative to offset
	10	93.4	-7.3	49.5	98	92.8	-13.0	50.5	105	-0.4	-5.6	1.0	5.8	5.8	$f^* = 6.1$
	11	93.6	-6.2	42.5	98	93.1	-12.1	44.8	105	-0.5	-5.8	2.3	6.3	6.3	
	12	93.9	-5.2	35.5	98	93.6	-10.6	37.0	106	-0.3	-5.3	1.5	5.6	5.6	Yellow – White
	13	94.2	-4.1	28.4	98	94.0	-8.4	27.5	107	-0.2	-4.2	-0.8	4.4	4.4	cmy0: Y – W
	14	94.5	-3.1	21.4	98	94.3	-6.4	20.0	108	-0.2	-3.2	-1.3	3.6	3.6	
	15	94.8	-2.0	14.4	98	94.7	-4.6	13.9	109	0.0	-2.5	-0.4	2.6	2.6	Mean CIELAB difference (17 steps)
	16	95.1	-1.0	7.3	98	95.1	-2.3	6.7	110	0.0	-1.2	-0.5	1.5	1.5	$\Delta H^*_{CIELAB} = 4.6$
W	17	95.4	0.0	0.3	90	95.4	0.0	0.3	90	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 4.6$
Y	18	90.7	-16.8	112.8	99	90.7	-16.8	112.8	99	0.0	0.0	0.0	0.0	0.0	
	19	91.9	-12.6	84.7	99	91.3	-17.0	91.1	101	-0.4	-4.3	6.4	7.8	7.8	
	20	93.1	-8.4	56.6	98	92.6	-13.9	57.1	104	-0.3	-5.5	0.5	5.6	5.6	Mean CIELAB difference (5 steps)
	21	94.2	-4.1	28.4	98	94.0	-8.4	27.5	107	-0.2	-4.2	-0.8	4.4	4.4	$\Delta H^*_{CIELAB} = 3.6$
W	22	95.4	0.0	0.3	90	95.4	0.0	0.3	90	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 3.6$
Mean colour reproduction index:												$R^*_{ab,m} = 80$			

T	i	LAB*a,ref		hab,ref	LAB*a,out		hab,out	LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1		
L	1	48.9	-63.5	33.0	153	48.9	-63.5	33.0	153	0.0	0.0	0.0	0.0	Specification according to
	2	51.8	-59.5	30.9	153	51.5	-57.8	30.8	152	-0.2	1.7	0.0	1.7	ISO/IEC 15775:1999 Annex G
	3	54.7	-55.6	28.9	153	54.0	-53.6	27.4	153	-0.7	1.9	-1.4	2.4	and DIN 33866-1:2000 Annex G
	4	57.6	-51.6	26.8	153	55.4	-47.5	21.0	156	-2.1	4.1	-5.7	7.1	relative CIELAB data used for "out"
	5	60.5	-47.6	24.8	153	58.2	-41.9	20.1	154	-2.3	5.7	-4.5	7.4	$\Delta L^* = 95.38 - 48.9$
	6	63.4	-43.6	22.7	153	60.1	-37.5	17.9	155	-3.2	6.1	-4.7	7.8	Regularity
	7	66.3	-39.7	20.6	153	62.0	-32.4	17.6	152	-4.2	7.3	-2.9	7.9	$g^* = 62.1$
	8	69.2	-35.7	18.6	153	64.5	-28.1	18.0	147	-4.6	7.6	-0.5	7.6	
	9	72.1	-31.7	16.5	153	67.2	-24.7	17.4	145	-4.8	7.0	0.9	7.1	Lightness gamut relative to offset
	10	75.0	-27.7	14.4	153	70.0	-21.8	17.1	142	-5.0	5.9	2.7	6.5	$f^* = 60.1$
	11	78.0	-23.7	12.4	153	73.1	-19.2	18.2	137	-4.8	4.5	5.8	7.4	
	12	80.9	-19.8	10.3	153	76.3	-16.9	14.1	140	-4.5	2.9	3.8	4.8	Leaf green – White
W	13	83.8	-15.8	8.3	153	80.8	-15.3	12.0	142	-2.9	0.5	3.8	3.8	cmY0: L – W
	14	86.7	-11.8	6.2	153	84.3	-11.8	9.0	143	-2.3	0.0	2.8	2.8	
	15	89.6	-7.9	4.1	153	87.5	-8.7	6.7	143	-2.0	-0.7	2.6	2.7	Mean CIELAB difference (17 steps)
	16	92.5	-3.9	2.1	153	90.2	-5.0	2.0	159	-2.2	-1.0	0.0	1.1	$\Delta H^*_{CIELAB} = 4.6$
	17	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 5.5$
	18	48.9	-63.5	33.0	153	48.9	-63.5	33.0	153	0.0	0.0	0.0	0.0	
	19	60.5	-47.6	24.8	153	58.2	-41.9	20.1	154	-2.3	5.7	-4.5	7.4	
	20	72.1	-31.7	16.5	153	67.2	-24.7	17.4	145	-4.8	7.0	0.9	7.1	Mean CIELAB difference (5 steps)
	21	83.8	-15.8	8.3	153	80.8	-15.3	12.0	142	-2.9	0.5	3.8	3.8	$\Delta H^*_{CIELAB} = 3.6$
	22	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 4.2$
	Mean colour reproduction index:												$R^*_{ab,m} = 76$	

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1
C	1	55.7	-19.4	-41.4	245	55.7	-19.4	-41.4	245	0.0	0.0	0.0	0.0	0.0	Specification according to
	2	58.1	-18.2	-38.8	245	56.7	-20.0	-39.0	243	-1.4	-1.7	-0.1	1.8	2.3	ISO/IEC 15775:1999 Annex G
	3	60.6	-17.0	-36.2	245	58.1	-20.2	-36.8	241	-2.4	-3.1	-0.5	3.3	4.1	and DIN 33866-1:2000 Annex G
	4	63.1	-15.7	-33.6	245	60.0	-20.9	-33.6	238	-3.0	-5.1	0.0	5.2	6.0	relative CIELAB data used for "out"
	5	65.6	-14.5	-31.0	245	61.4	-19.7	-31.8	238	-4.1	-5.1	-0.7	5.2	6.7	$\Delta L^* = 95.41 - 55.66$
	6	68.1	-13.3	-28.4	245	63.3	-18.1	-29.4	238	-4.7	-4.7	-0.9	4.9	6.8	Regularity
	7	70.6	-12.1	-25.8	245	65.9	-16.4	-26.1	238	-4.5	-4.2	-0.2	4.3	6.3	$g^* = 49.5$
	8	73.1	-10.9	-23.2	245	69.6	-15.7	-22.8	235	-3.3	-4.7	0.4	4.9	5.9	
	9	75.5	-9.7	-20.7	245	72.6	-13.9	-19.1	234	-2.8	-4.2	1.5	4.5	5.4	Lightness gamut relative to offset
	10	78.0	-8.4	-18.1	245	77.3	-12.6	-15.3	230	-0.6	-4.1	2.8	5.0	5.1	$f^* = 51.4$
	11	80.5	-7.2	-15.5	245	80.2	-10.5	-13.6	232	-0.2	-3.2	1.9	3.8	3.8	
	12	83.0	-6.0	-12.9	245	81.9	-9.0	-11.9	233	-1.0	-2.9	1.0	3.2	3.3	Cyan blue – White
	13	85.5	-4.8	-10.3	245	83.9	-7.1	-10.3	235	-1.5	-2.2	0.0	2.3	2.8	cmy0: C – W
	14	88.0	-3.6	-7.7	245	85.9	-5.4	-8.1	236	-1.9	-1.7	-0.3	1.9	2.8	
	15	90.4	-2.3	-5.1	245	88.7	-3.7	-6.0	238	-1.6	-1.3	-0.8	1.6	2.4	Mean CIELAB difference (17 steps)
	16	92.9	-1.1	-2.5	245	90.8	-2.2	-3.4	237	-2.0	-1.0	-0.8	1.4	2.5	$\Delta H^*_{CIELAB} = 3.1$
W	17	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 3.9$
C	18	55.7	-19.4	-41.4	245	55.7	-19.4	-41.4	245	0.0	0.0	0.0	0.0	0.0	
	19	65.6	-14.5	-31.0	245	61.4	-19.7	-31.8	238	-4.1	-5.1	-0.7	5.2	6.7	
	20	75.5	-9.7	-20.7	245	72.6	-13.9	-19.1	234	-2.8	-4.2	1.5	4.5	5.4	Mean CIELAB difference (5 steps)
	21	85.5	-4.8	-10.3	245	83.9	-7.1	-10.3	235	-1.5	-2.2	0.0	2.3	2.8	$\Delta H^*_{CIELAB} = 2.4$
W	22	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 3.0$
Mean colour reproduction index: $R^*_{ab,m} = 83$															

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1
V	1	25.6	21.1	-35.5	301	25.6	21.1	-35.5	301	0.0	0.0	0.0	0.0	0.0	Specification according to
	2	29.9	19.8	-33.3	301	28.2	19.7	-36.0	299	-1.7	0.0	-2.6	2.7	3.3	ISO/IEC 15775:1999 Annex G
	3	34.3	18.5	-31.0	301	31.2	18.6	-36.2	297	-3.0	0.1	-5.1	5.2	6.0	and DIN 33866-1:2000 Annex G
	4	38.7	17.1	-28.8	301	34.3	17.8	-35.5	297	-4.3	0.7	-6.6	6.7	8.0	relative CIELAB data used for "out"
	5	43.1	15.8	-26.5	301	37.2	17.9	-34.4	297	-5.7	2.1	-7.8	8.1	10.0	$\Delta L^* = 95.48 - 25.58$
	6	47.4	14.5	-24.3	301	40.7	15.5	-33.4	295	-6.7	1.0	-9.0	9.1	11.4	Regularity
	7	51.8	13.2	-22.1	301	45.0	15.4	-31.3	296	-6.7	2.2	-9.1	9.5	11.7	$g^* = 49.8$
	8	56.2	11.9	-19.8	301	49.5	12.9	-28.4	294	-6.6	1.0	-8.5	8.6	10.9	
	9	60.5	10.6	-17.6	301	53.9	11.8	-24.7	295	-6.5	1.3	-7.0	7.2	9.8	Lightness gamut relative to offset
	10	64.9	9.2	-15.4	301	58.9	10.5	-20.4	297	-5.9	1.3	-4.9	5.2	8.0	$f^* = 90.3$
	11	69.3	7.9	-13.1	301	63.2	9.3	-17.1	298	-6.0	1.4	-3.9	4.2	7.4	
	12	73.6	6.6	-10.9	301	67.9	6.5	-13.7	295	-5.6	0.0	-2.7	2.8	6.4	Violet blue – White
	13	78.0	5.3	-8.7	301	72.1	5.3	-11.8	294	-5.8	0.0	-3.0	3.2	6.7	cmy0: V – W
	14	82.4	4.0	-6.4	301	76.9	3.9	-8.3	295	-5.3	0.0	-1.8	1.9	5.8	
	15	86.7	2.6	-4.2	302	82.5	2.2	-5.7	291	-4.2	-0.3	-1.4	1.6	4.6	Mean CIELAB difference (17 steps)
16	91.1	1.3	-1.9	303	85.9	2.3	-3.7	301	-5.1	1.0	-1.7	2.0	5.6	$\Delta H^*_{CIELAB} = 4.6$	
W	17	95.5	0.0	0.2	90	95.5	0.0	0.2	90	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 6.8$
V	18	25.6	21.1	-35.5	301	25.6	21.1	-35.5	301	0.0	0.0	0.0	0.0	0.0	
	19	43.1	15.8	-26.5	301	37.2	17.9	-34.4	297	-5.7	2.1	-7.8	8.1	10.0	
	20	60.5	10.6	-17.6	301	53.9	11.8	-24.7	295	-6.5	1.3	-7.0	7.2	9.8	Mean CIELAB difference (5 steps)
	21	78.0	5.3	-8.7	301	72.1	5.3	-11.8	294	-5.8	0.0	-3.0	3.2	6.7	$\Delta H^*_{CIELAB} = 3.7$
W	22	95.5	0.0	0.2	90	95.5	0.0	0.2	90	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 5.3$
Mean colour reproduction index:														$R^*_{ab,m} = 70$	

T	i	LAB*a,ref			hab,ref	LAB*a,out			hab,out	LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1
M	1	46.9	62.6	-5.2	355	46.9	62.6	-5.2	355	0.0	0.0	0.0	0.0	0.0	Specification according to
	2	49.9	58.7	-4.9	355	48.6	59.1	-5.9	354	-1.2	0.4	-0.9	1.1	1.7	ISO/IEC 15775:1999 Annex G
	3	52.9	54.8	-4.5	355	51.2	53.6	-5.7	354	-1.6	-1.1	-1.1	1.7	2.4	and DIN 33866-1:2000 Annex G
	4	56.0	50.9	-4.2	355	53.8	49.1	-5.6	353	-2.1	-1.7	-1.3	2.2	3.1	relative CIELAB data used for "out"
	5	59.0	46.9	-3.9	355	55.8	45.8	-5.8	353	-3.1	-1.0	-1.8	2.2	3.9	$\Delta L^* = 95.39 - 46.88$
	6	62.0	43.0	-3.5	355	59.2	39.3	-4.7	353	-2.7	-3.6	-1.1	3.9	4.8	Regularity
	7	65.1	39.1	-3.2	355	62.3	34.2	-3.9	353	-2.7	-4.8	-0.6	5.0	5.7	$g^* = 61.1$
	8	68.1	35.2	-2.9	355	65.6	28.9	-2.6	355	-2.4	-6.2	0.3	6.3	6.8	
	9	71.1	31.3	-2.6	355	69.1	24.6	-1.7	356	-1.9	-6.6	0.9	6.8	7.1	Lightness gamut relative to offset
	10	74.2	27.4	-2.2	355	72.0	20.6	-1.3	356	-2.1	-6.7	0.9	6.8	7.2	$f^* = 62.7$
	11	77.2	23.5	-1.9	355	74.7	17.6	-0.5	358	-2.4	-5.8	1.4	6.0	6.6	
	12	80.2	19.6	-1.6	355	78.2	14.4	-0.2	359	-2.0	-5.1	1.4	5.3	5.7	Magenta red – White
	13	83.3	15.7	-1.2	355	80.9	11.6	-0.2	359	-2.3	-4.0	1.0	4.2	4.8	cmY0: M – W
	14	86.3	11.7	-0.9	355	83.7	8.6	0.0	0	-2.5	-3.0	1.0	3.3	4.2	
	15	89.3	7.8	-0.6	355	86.4	6.6	-0.3	357	-2.9	-1.1	0.3	1.3	3.2	Mean CIELAB difference (17 steps)
	16	92.4	3.9	-0.2	355	88.5	4.9	-0.2	356	-3.8	1.0	0.0	1.0	4.0	$\Delta H^*_{CIELAB} = 3.4$
W	17	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 4.2$
M	18	46.9	62.6	-5.2	355	46.9	62.6	-5.2	355	0.0	0.0	0.0	0.0	0.0	
	19	59.0	46.9	-3.9	355	55.8	45.8	-5.8	353	-3.1	-1.0	-1.8	2.2	3.9	
	20	71.1	31.3	-2.6	355	69.1	24.6	-1.7	356	-1.9	-6.6	0.9	6.8	7.1	Mean CIELAB difference (5 steps)
	21	83.3	15.7	-1.2	355	80.9	11.6	-0.2	359	-2.3	-4.0	1.0	4.2	4.8	$\Delta H^*_{CIELAB} = 2.6$
W	22	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 3.2$
Mean colour reproduction index: $R^*_{ab,m} = 82$															

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	26.9	0.0	0.0	0	26.9	0.0	0.0	0	0.0	0.0	0.0	0.0	Specification according to
	2	31.2	0.0	0.0	0	29.2	-0.6	1.1	122	-1.9	-0.6	1.1	1.3	ISO/IEC 15775:1999 Annex G
	3	35.5	0.0	0.0	0	31.4	-1.5	1.0	148	-4.0	-1.5	1.0	1.9	and DIN 33866-1:2000 Annex G
	4	39.8	0.0	0.0	0	34.1	-1.7	0.5	164	-5.6	-1.7	0.5	1.9	relative CIELAB data used for "out"
	5	44.1	0.0	0.0	0	36.2	-1.9	2.0	135	-7.7	-1.9	2.0	2.8	$\Delta L^* = 95.41 - 26.94$
	6	48.3	0.0	0.0	0	38.8	-1.7	2.1	131	-9.4	-1.7	2.1	2.8	Regularity
	7	52.6	0.0	0.0	0	42.6	-1.3	3.0	115	-9.9	-1.3	3.0	3.3	$g^* = 36.6$
	8	56.9	0.0	0.0	0	47.3	-2.5	4.6	119	-9.5	-2.5	4.6	5.3	
Z	9	61.2	0.0	0.0	0	51.9	-1.7	6.1	106	-9.2	-1.7	6.1	6.4	Lightness gamut relative to offset
	10	65.5	0.0	0.0	0	56.7	-1.3	7.2	101	-8.6	-1.3	7.2	7.3	$f^* = 88.5$
	11	69.7	0.0	0.0	0	61.3	-0.7	7.2	96	-8.3	-0.7	7.2	7.2	
	12	74.0	0.0	0.0	0	65.4	-0.8	6.5	98	-8.6	-0.8	6.5	6.6	Black – White
	13	78.3	0.0	0.0	0	70.0	-0.3	6.3	94	-8.2	-0.3	6.3	6.3	cmy0: N – W
	14	82.6	0.0	0.0	0	75.3	-0.1	5.9	92	-7.2	-0.1	5.9	5.9	
	15	86.9	0.0	0.0	0	80.8	-1.2	5.2	104	-6.0	-1.2	5.2	5.4	Mean CIELAB difference (17 steps)
	16	91.1	0.0	0.0	0	85.1	0.3	1.9	81	-5.9	0.3	1.9	1.9	$\Delta H^*_{CIELAB} = 3.9$
W	17	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 7.7$
N	18	26.9	0.0	0.0	0	26.9	0.0	0.0	0	0.0	0.0	0.0	0.0	
	19	44.1	0.0	0.0	0	36.2	-1.9	2.0	135	-7.7	-1.9	2.0	2.8	
Z	20	61.2	0.0	0.0	0	51.9	-1.7	6.1	106	-9.2	-1.7	6.1	6.4	Mean CIELAB difference (5 steps)
	21	78.3	0.0	0.0	0	70.0	-0.3	6.3	94	-8.2	-0.3	6.3	6.3	$\Delta H^*_{CIELAB} = 3.1$
W	22	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 6.0$
Mean colour reproduction index: $R^*_{ab,m} = 66$														

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1	
N	1	28.0	2.1	0.8	21	28.0	2.1	0.8	21	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to		
	2	29.2	5.7	3.6	32	28.9	5.1	3.0	30	-0.2	-0.5	-0.5	0.9	0.9	ISO/IEC 15775:1999 Annex G					
	3	30.3	9.3	6.5	35	30.0	11.0	4.8	24	-0.2	1.7	-1.6	2.4	2.4	and DIN 33866-1:2000 Annex G					
	4	31.5	12.9	9.3	36	31.3	14.6	7.8	28	-0.1	1.7	-1.4	2.2	2.3	relative CIELAB data used for "out"					
	5	32.7	16.5	12.1	36	32.2	19.3	11.1	30	-0.4	2.8	-0.9	3.0	3.0	$\Delta L^* = 46.67 - 27.99$					
	6	33.8	20.1	15.0	37	32.8	23.1	13.8	31	-0.9	3.0	-1.1	3.2	3.4	Regularity					
	7	35.0	23.7	17.8	37	33.9	27.8	17.2	32	-1.0	4.1	-0.5	4.1	4.2	$g^* = 59.4$					
	8	36.2	27.3	20.6	37	35.0	30.8	19.3	32	-1.1	3.5	-1.2	3.7	3.9						
	9	37.3	31.0	23.4	37	36.4	34.3	21.4	32	-0.8	3.3	-1.9	3.9	4.0	Lightness gamut relative to offset					
	10	38.5	34.6	26.3	37	37.3	37.8	24.9	33	-1.1	3.2	-1.3	3.5	3.7	$f^* = 24.1$					
	11	39.7	38.2	29.1	37	38.3	41.1	27.3	34	-1.3	2.9	-1.7	3.5	3.7						
	12	40.8	41.8	31.9	37	38.8	43.7	30.1	35	-1.9	1.9	-1.7	2.7	3.3	Black – Orange red					
	13	42.0	45.4	34.8	37	40.2	47.2	33.6	35	-1.7	1.8	-1.1	2.2	2.8	cmy0: N – O					
	14	43.2	49.0	37.6	38	42.1	51.4	37.4	36	-1.0	2.4	-0.1	2.4	2.7						
	15	44.3	52.6	40.4	38	43.4	54.5	39.6	36	-0.9	1.9	-0.7	2.1	2.3	Mean CIELAB difference (17 steps)					
	16	45.5	56.2	43.3	38	44.4	56.9	42.2	37	-1.0	0.7	-1.0	1.3	1.7	$\Delta H^*_{CIELAB} = 2.4$					
	O	17	46.7	59.8	46.1	38	46.7	59.8	46.1	38	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 2.6$				
N	18	28.0	2.1	0.8	21	28.0	2.1	0.8	21	0.0	0.0	0.0	0.0	0.0						
	19	32.7	16.5	12.1	36	32.2	19.3	11.1	30	-0.4	2.8	-0.9	3.0	3.0						
	20	37.3	31.0	23.4	37	36.4	34.3	21.4	32	-0.8	3.3	-1.9	3.9	4.0	Mean CIELAB difference (5 steps)					
	21	42.0	45.4	34.8	37	40.2	47.2	33.6	35	-1.7	1.8	-1.1	2.2	2.8	$\Delta H^*_{CIELAB} = 1.8$					
O	22	46.7	59.8	46.1	38	46.7	59.8	46.1	38	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 2.0$					
Mean colour reproduction index:																		$R^*_{ab,m} = 89$		

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1	
N	1	28.3	3.9	1.3	18	28.3	3.9	1.3	18	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to		
	2	32.2	2.6	8.2	73	30.6	1.5	4.9	73	-1.4	-1.0	-3.2	3.5	3.8	ISO/IEC 15775:1999 Annex G					
	3	36.1	1.3	15.2	85	33.3	-1.4	9.5	99	-2.7	-2.7	-5.6	6.3	6.9	and DIN 33866-1:2000 Annex G					
	4	40.0	0.0	22.1	90	36.3	-3.5	15.1	103	-3.6	-3.5	-6.9	7.8	8.7	relative CIELAB data used for "out"					
	5	43.9	-1.2	29.0	93	38.7	-4.1	22.3	101	-5.1	-2.8	-6.6	7.3	9.0	$\Delta L^* = 90.8 - 28.27$					
	6	47.8	-2.6	36.0	94	41.4	-6.7	29.5	103	-6.3	-4.0	-6.4	7.7	10.0	Regularity					
	7	51.7	-3.9	42.9	95	44.1	-6.2	36.9	100	-7.5	-2.2	-5.9	6.4	9.9	$g^* = 43.4$					
	8	55.6	-5.2	49.8	96	47.7	-7.1	42.3	100	-7.9	-1.8	-7.4	7.8	11.1						
	9	59.5	-6.5	56.7	97	51.3	-7.4	48.7	99	-8.2	-0.8	-7.9	8.1	11.6	Lightness gamut relative to offset					
	10	63.4	-7.8	63.7	97	55.1	-7.7	55.4	98	-8.2	0.1	-8.2	8.3	11.7	$f^* = 80.8$					
	11	67.4	-9.1	70.6	97	58.4	-7.8	61.0	97	-8.9	1.3	-9.5	9.7	13.2						
	12	71.3	-10.4	77.5	98	62.6	-9.5	68.2	98	-8.5	0.9	-9.2	9.4	12.8	Black – Yellow					
	13	75.2	-11.8	84.5	98	66.8	-10.2	75.7	98	-8.3	1.6	-8.7	8.9	12.3	cmy0: N – Y					
	14	79.1	-13.1	91.4	98	71.3	-11.2	82.6	98	-7.7	1.9	-8.7	9.0	11.9						
	15	83.0	-14.4	98.3	98	76.6	-13.3	90.7	98	-6.3	1.1	-7.5	7.7	10.0	Mean CIELAB difference (17 steps)					
	16	86.9	-15.7	105.3	99	81.0	-13.2	97.5	98	-5.8	2.5	-7.7	8.2	10.1	$\Delta H^*_{CIELAB} = 6.8$					
Y	17	90.8	-17.0	112.2	99	90.8	-17.0	112.2	99	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 9.0$					
N	18	28.3	3.9	1.3	18	28.3	3.9	1.3	18	0.0	0.0	0.0	0.0	0.0						
	19	43.9	-1.2	29.0	93	38.7	-4.1	22.3	101	-5.1	-2.8	-6.6	7.3	9.0						
	20	59.5	-6.5	56.7	97	51.3	-7.4	48.7	99	-8.2	-0.8	-7.9	8.1	11.6	Mean CIELAB difference (5 steps)					
	21	75.2	-11.8	84.5	98	66.8	-10.2	75.7	98	-8.3	1.6	-8.7	8.9	12.3	$\Delta H^*_{CIELAB} = 4.9$					
Y	22	90.8	-17.0	112.2	99	90.8	-17.0	112.2	99	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 6.6$					
Mean colour reproduction index:																		$R^*_{ab,m} = 61$		

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	29.0	3.9	1.6	22	29.0	3.9	1.6	22	0.0	0.0	0.0	0.0	Specification according to
	2	30.2	-0.3	3.5	96	31.3	-2.6	3.1	131	1.1	-2.2	-0.3	2.4	ISO/IEC 15775:1999 Annex G
	3	31.4	-4.6	5.4	131	32.7	-9.3	4.7	153	1.4	-4.6	-0.6	4.8	and DIN 33866-1:2000 Annex G
	4	32.6	-8.8	7.3	141	33.5	-15.8	6.8	157	1.0	-6.9	-0.4	7.0	relative CIELAB data used for "out"
	5	33.8	-13.1	9.2	145	34.2	-20.0	8.8	156	0.5	-6.8	-0.3	6.9	$\Delta L^* = 48.19 - 28.95$
	6	35.0	-17.4	11.1	148	35.6	-25.7	11.0	157	0.7	-8.2	0.0	8.3	Regularity
	7	36.2	-21.7	13.0	149	36.6	-29.4	13.0	156	0.4	-7.6	0.0	7.8	$g^* = 83.4$
	8	37.4	-25.9	14.9	150	37.6	-33.5	15.5	155	0.3	-7.5	0.6	7.6	
	9	38.6	-30.2	16.8	151	38.7	-36.3	17.0	155	0.1	-6.0	0.3	6.1	Lightness gamut relative to offset
	10	39.8	-34.5	18.6	152	40.0	-40.5	18.5	156	0.2	-5.9	0.0	6.0	$f^* = 24.9$
	11	41.0	-38.8	20.5	152	41.4	-44.1	20.9	155	0.4	-5.3	0.4	5.4	
	12	42.2	-43.0	22.4	153	42.4	-47.2	21.7	155	0.2	-4.1	-0.6	4.2	Black – Leaf green
	13	43.4	-47.3	24.3	153	43.3	-50.8	24.2	155	0.0	-3.4	0.0	3.5	cmy0: N – L
	14	44.6	-51.6	26.2	153	44.2	-53.7	24.4	156	-0.3	-2.0	-1.7	2.8	
	15	45.8	-55.9	28.1	153	45.4	-56.5	26.6	155	-0.3	-0.5	-1.4	1.6	Mean CIELAB difference (17 steps)
	16	47.0	-60.1	30.0	154	46.9	-60.8	29.6	154	0.0	-0.6	-0.3	0.8	$\Delta H^*_{CIELAB} = 4.4$
L	17	48.2	-64.4	31.9	154	48.2	-64.4	31.9	154	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 4.5$
N	18	29.0	3.9	1.6	22	29.0	3.9	1.6	22	0.0	0.0	0.0	0.0	
	19	33.8	-13.1	9.2	145	34.2	-20.0	8.8	156	0.5	-6.8	-0.3	6.9	
	20	38.6	-30.2	16.8	151	38.7	-36.3	17.0	155	0.1	-6.0	0.3	6.1	Mean CIELAB difference (5 steps)
	21	43.4	-47.3	24.3	153	43.3	-50.8	24.2	155	0.0	-3.4	0.0	3.5	$\Delta H^*_{CIELAB} = 3.3$
L	22	48.2	-64.4	31.9	154	48.2	-64.4	31.9	154	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 3.3$
Mean colour reproduction index: $R^*_{ab,m} = 81$														

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1	
N	1	29.2	3.2	0.3	5	29.2	3.2	0.3	5	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to		
	2	30.8	1.7	-2.2	307	30.8	-1.6	-0.2	190	0.0	-3.3	2.0	3.9	3.9	ISO/IEC 15775:1999 Annex G					
	3	32.4	0.2	-4.7	272	32.2	-6.5	-1.6	194	-0.1	-6.7	3.1	7.5	7.5	and DIN 33866-1:2000 Annex G					
	4	34.1	-1.2	-7.3	260	33.1	-12.1	-3.1	195	-0.9	-10.8	4.2	11.7	11.7	relative CIELAB data used for "out"					
	5	35.7	-2.7	-9.8	254	34.3	-15.5	-3.9	194	-1.3	-12.7	5.9	14.1	14.2	$\Delta L^* = 55.36 - 29.15$					
	6	37.3	-4.2	-12.4	251	35.4	-18.6	-6.0	198	-1.9	-14.3	6.4	15.7	15.8	Regularity					
	7	39.0	-5.7	-14.9	249	36.4	-21.0	-7.4	200	-2.4	-15.2	7.5	17.0	17.2	$g^* = 61.5$					
	8	40.6	-7.2	-17.5	247	38.1	-23.7	-8.6	200	-2.4	-16.4	8.9	18.7	18.9						
	9	42.3	-8.8	-20.1	246	40.0	-25.1	-10.3	202	-2.2	-16.3	9.8	19.0	19.2	Lightness gamut relative to offset					
	10	43.9	-10.3	-22.6	245	41.6	-25.9	-13.2	207	-2.2	-15.5	9.4	18.3	18.4	$f^* = 33.9$					
	11	45.5	-11.8	-25.2	245	43.6	-26.7	-15.1	210	-1.9	-14.8	10.1	18.0	18.1						
	12	47.2	-13.3	-27.7	244	45.3	-25.9	-19.5	217	-1.8	-12.5	8.2	15.1	15.2	Black – Cyan blue					
	13	48.8	-14.8	-30.3	244	47.0	-25.2	-24.0	224	-1.7	-10.3	6.3	12.2	12.3	cmy0: N – C					
	14	50.4	-16.3	-32.8	244	48.5	-23.6	-28.3	230	-1.9	-7.2	4.5	8.6	8.8						
	15	52.1	-17.8	-35.4	243	50.1	-22.7	-31.1	234	-1.9	-4.8	4.3	6.5	6.8	Mean CIELAB difference (17 steps)					
	16	53.7	-19.3	-37.9	243	52.2	-21.4	-36.2	239	-1.4	-2.0	1.7	2.7	3.1	$\Delta H^*_{CIELAB} = 11.1$					
	C	17	55.4	-20.8	-40.5	243	55.4	-20.8	-40.5	243	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 11.2$				
N	18	29.2	3.2	0.3	5	29.2	3.2	0.3	5	0.0	0.0	0.0	0.0	0.0						
	19	35.7	-2.7	-9.8	254	34.3	-15.5	-3.9	194	-1.3	-12.7	5.9	14.1	14.2						
	20	42.3	-8.8	-20.1	246	40.0	-25.1	-10.3	202	-2.2	-16.3	9.8	19.0	19.2	Mean CIELAB difference (5 steps)					
	21	48.8	-14.8	-30.3	244	47.0	-25.2	-24.0	224	-1.7	-10.3	6.3	12.2	12.3	$\Delta H^*_{CIELAB} = 9.1$					
C	22	55.4	-20.8	-40.5	243	55.4	-20.8	-40.5	243	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 9.1$					
Mean colour reproduction index:																		$R^*_{ab,m} = 51$		

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1	
N	1	28.9	2.7	0.4	8	28.9	2.7	0.4	8	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to		
	2	28.7	3.7	-1.8	333	28.7	3.9	-1.8	334	0.0	0.2	0.0	0.2	0.2	ISO/IEC 15775:1999 Annex G					
	3	28.6	4.8	-4.0	319	28.7	4.1	-4.6	311	0.1	-0.6	-0.5	0.9	0.9	and DIN 33866-1:2000 Annex G					
	4	28.4	5.8	-6.3	312	28.1	5.2	-6.2	310	-0.2	-0.5	0.1	0.6	0.7	relative CIELAB data used for "out"					
	5	28.2	6.8	-8.6	308	27.7	6.7	-8.5	308	-0.5	0.0	0.1	0.1	0.6	$\Delta L^* = 26.19 - 28.92$					
	6	28.1	7.9	-10.8	306	27.0	7.3	-11.0	303	-1.0	-0.5	-0.1	0.6	1.2	Regularity					
	7	27.9	8.9	-13.1	304	26.7	8.1	-12.6	303	-1.1	-0.7	0.5	0.9	1.5	$g^* = 34.7$					
	8	27.7	9.9	-15.3	303	26.3	8.5	-15.4	299	-1.4	-1.3	0.0	1.4	2.0						
	9	27.6	11.0	-17.6	302	26.5	9.9	-17.8	299	-1.0	-1.0	-0.1	1.1	1.5	Lightness gamut relative to offset					
	10	27.4	12.0	-19.9	301	26.2	11.1	-20.8	298	-1.1	-0.8	-0.8	1.3	1.8	$f^* = -3.4$					
	11	27.2	13.0	-22.1	300	25.9	12.5	-22.6	299	-1.2	-0.4	-0.4	0.7	1.5						
	12	27.0	14.0	-24.4	300	26.0	12.8	-25.1	297	-0.9	-1.1	-0.6	1.4	1.8	Black – Violet blue					
V	13	26.9	15.1	-26.7	299	25.8	13.9	-27.1	297	-1.0	-1.1	-0.3	1.3	1.7	cmy0: N – V					
	14	26.7	16.1	-28.9	299	25.8	14.9	-29.4	297	-0.8	-1.1	-0.4	1.3	1.6						
	15	26.5	17.1	-31.2	299	26.1	16.2	-31.5	297	-0.4	-0.8	-0.2	1.0	1.1	Mean CIELAB difference (17 steps)					
	16	26.4	18.2	-33.4	298	26.1	17.3	-33.0	298	-0.2	-0.8	0.4	1.0	1.0	$\Delta H^*_{CIELAB} = 0.8$					
	17	26.2	19.2	-35.7	298	26.2	19.2	-35.7	298	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.1$					
	18	28.9	2.7	0.4	8	28.9	2.7	0.4	8	0.0	0.0	0.0	0.0	0.0						
	19	28.2	6.8	-8.6	308	27.7	6.7	-8.5	308	-0.5	0.0	0.1	0.1	0.6						
	20	27.6	11.0	-17.6	302	26.5	9.9	-17.8	299	-1.0	-1.0	-0.1	1.1	1.5	Mean CIELAB difference (5 steps)					
	21	26.9	15.1	-26.7	299	25.8	13.9	-27.1	297	-1.0	-1.1	-0.3	1.3	1.7	$\Delta H^*_{CIELAB} = 0.5$					
	22	26.2	19.2	-35.7	298	26.2	19.2	-35.7	298	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 0.8$					
	Mean colour reproduction index:																	$R^*_{ab,m} = 95$		

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1	
N	1	29.3	1.6	0.7	24	29.3	1.6	0.7	24	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to		
	2	30.5	5.3	0.4	4	30.3	6.1	-0.1	358	0.0	0.8	-0.5	1.0	1.0				ISO/IEC 15775:1999 Annex G		
	3	31.6	9.1	0.0	0	30.4	10.9	-1.4	352	-1.0	1.8	-1.4	2.4	2.6				and DIN 33866-1:2000 Annex G		
	4	32.7	12.8	-0.2	359	31.4	16.4	-1.7	354	-1.2	3.6	-1.4	3.9	4.1				relative CIELAB data used for "out"		
	5	33.8	16.5	-0.6	358	31.9	21.5	-1.8	355	-1.8	5.0	-1.1	5.1	5.5				$\Delta L^* = 47.2 - 29.34$		
	6	34.9	20.2	-0.9	357	33.0	24.9	-1.2	357	-1.8	4.7	-0.2	4.7	5.1				Regularity		
	7	36.0	24.0	-1.3	357	33.9	29.6	-1.0	358	-2.0	5.6	0.3	5.7	6.0				$g^* = 40.0$		
	8	37.2	27.7	-1.6	356	35.1	33.7	-1.4	357	-2.0	6.0	0.2	6.0	6.4						
	9	38.3	31.4	-2.0	356	35.9	37.8	-1.7	357	-2.2	6.4	0.3	6.4	6.8				Lightness gamut relative to offset		
	10	39.4	35.1	-2.3	356	38.4	43.2	-2.7	356	-0.9	8.1	-0.3	8.1	8.1				$f^* = 23.1$		
	11	40.5	38.9	-2.6	356	39.8	47.9	-4.1	355	-0.6	9.1	-1.4	9.2	9.2						
	12	41.6	42.6	-3.0	356	41.6	50.9	-5.2	354	0.0	8.3	-2.1	8.6	8.6				Black – Magenta red		
	13	42.7	46.3	-3.3	356	42.3	55.1	-4.7	355	-0.4	8.8	-1.3	8.9	8.9				cmy0: N – M		
	14	43.9	50.0	-3.7	356	43.2	57.5	-4.8	355	-0.6	7.5	-1.0	7.6	7.6						
	15	45.0	53.8	-4.0	356	44.7	58.6	-4.8	355	-0.2	4.8	-0.7	4.9	4.9				Mean CIELAB difference (17 steps)		
	16	46.1	57.5	-4.4	356	45.5	60.1	-5.5	355	-0.5	2.6	-1.0	2.9	2.9				$\Delta H^*_{CIELAB} = 5.0$		
	M	17	47.2	61.2	-4.7	356	47.2	61.2	-4.7	356	0.0	0.0	0.0	0.0	0.0				$\Delta E^*_{CIELAB} = 5.2$	
N	18	29.3	1.6	0.7	24	29.3	1.6	0.7	24	0.0	0.0	0.0	0.0	0.0						
	19	33.8	16.5	-0.6	358	31.9	21.5	-1.8	355	-1.8	5.0	-1.1	5.1	5.5						
	20	38.3	31.4	-2.0	356	35.9	37.8	-1.7	357	-2.2	6.4	0.3	6.4	6.8				Mean CIELAB difference (5 steps)		
	21	42.7	46.3	-3.3	356	42.3	55.1	-4.7	355	-0.4	8.8	-1.3	8.9	8.9				$\Delta H^*_{CIELAB} = 4.1$		
	M	22	47.2	61.2	-4.7	356	47.2	61.2	-4.7	356	0.0	0.0	0.0	0.0	0.0				$\Delta E^*_{CIELAB} = 4.2$	
Mean colour reproduction index:																		$R^*_{ab,m} = 77$		

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	22.6	0.2	7.1	88	22.6	0.2	7.1	88	0.0	0.0	0.0	0.0	Specification according to
	2	27.2	0.2	6.7	88	25.1	0.3	7.2	88	-2.0	0.1	0.5	0.5	ISO/IEC 15775:1999 Annex G
	3	31.7	0.2	6.2	88	28.1	0.3	6.9	88	-3.5	0.1	0.7	0.7	and DIN 33866-1:2000 Annex G
	4	36.3	0.2	5.8	88	33.3	0.2	6.3	88	-2.9	0.0	0.5	0.5	relative CIELAB data used for "out"
	5	40.8	0.2	5.4	88	37.9	0.2	5.9	88	-2.8	0.1	0.5	0.5	$\Delta L^* = 95.42 - 22.63$
	6	45.4	0.1	4.9	88	43.2	0.1	5.3	89	-2.0	0.0	0.4	0.4	Regularity
	7	49.9	0.1	4.5	88	47.2	0.1	4.8	89	-2.6	0.0	0.3	0.3	$g^* = 74.4$
	8	54.5	0.1	4.1	88	52.6	0.1	4.4	89	-1.8	0.0	0.3	0.3	
Z	9	59.0	0.1	3.7	88	58.4	0.0	3.9	90	-0.5	0.0	0.3	0.3	Lightness gamut relative to offset
	10	63.6	0.1	3.2	88	63.4	0.1	3.2	88	0.0	0.0	0.0	0.0	$f^* = 94.0$
	11	68.1	0.1	2.8	88	68.8	0.0	2.7	90	0.7	0.0	0.0	0.1	
	12	72.7	0.1	2.4	88	73.5	0.0	2.5	90	0.8	0.0	0.1	0.2	Black – White
	13	77.2	0.1	1.9	89	76.9	0.1	1.9	87	-0.3	0.1	0.0	0.1	000n: N – W
	14	81.8	0.0	1.5	89	81.7	0.0	1.6	90	0.0	0.0	0.1	0.1	
	15	86.3	0.0	1.1	89	85.4	0.0	1.0	90	-0.9	0.0	0.0	0.1	Mean CIELAB difference (17 steps)
	16	90.9	0.0	0.6	89	88.9	0.0	0.7	90	-1.9	0.0	0.1	0.1	$\Delta H^*_{CIELAB} = 0.2$
W	17	95.4	0.0	0.2	90	95.4	0.0	0.2	90	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.4$
N	18	22.6	0.2	7.1	88	22.6	0.2	7.1	88	0.0	0.0	0.0	0.0	
	19	40.8	0.2	5.4	88	37.9	0.2	5.9	88	-2.8	0.1	0.5	0.5	
Z	20	59.0	0.1	3.7	88	58.4	0.0	3.9	90	-0.5	0.0	0.3	0.3	Mean CIELAB difference (5 steps)
	21	77.2	0.1	1.9	89	76.9	0.1	1.9	87	-0.3	0.1	0.0	0.1	$\Delta H^*_{CIELAB} = 0.2$
W	22	95.4	0.0	0.2	90	95.4	0.0	0.2	90	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 0.8$
Mean colour reproduction index: $R^*_{ab,m} = 94$														

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
O	1	48.3	58.2	45.6	38	48.3	58.2	45.6	38	0.0	0.0	0.0	0.0	Specification according to
	2	48.9	50.7	40.7	39	48.7	51.8	40.6	38	-0.1	1.1	0.0	1.1	ISO/IEC 15775:1999 Annex G
	3	49.5	43.2	35.9	40	49.3	47.3	35.8	37	-0.2	4.1	0.0	4.1	and DIN 33866-1:2000 Annex G
	4	50.2	35.7	31.0	41	50.4	41.2	30.6	37	0.3	5.5	-0.3	5.5	
	5	50.8	28.2	26.2	43	51.3	33.0	26.5	39	0.5	4.8	0.4	4.8	
	6	51.5	20.7	21.3	46	51.5	24.3	21.1	41	0.1	3.6	-0.1	3.6	Regularity
	7	52.1	13.2	16.4	51	52.4	14.4	17.2	50	0.3	1.2	0.8	1.4	$g^* = 17.2$
	8	52.7	5.7	11.6	64	53.3	5.4	11.7	65	0.6	-0.2	0.1	0.3	
Z	9	53.4	-1.7	6.7	105	53.4	-1.7	6.7	105	0.0	0.0	0.0	0.0	
	10	53.6	-4.0	0.8	169	53.5	-8.1	0.8	174	0.0	-4.0	0.0	4.1	
	11	53.9	-6.3	-5.0	218	53.5	-13.0	-3.3	195	-0.3	-6.6	1.7	6.9	
	12	54.1	-8.6	-10.9	232	53.8	-16.8	-9.0	208	-0.3	-8.1	1.9	8.4	Orange red – Cyan blue
	13	54.4	-11.0	-16.8	237	52.9	-20.0	-14.8	217	-1.4	-9.0	2.0	9.3	cmY0: O – Z – C
	14	54.6	-13.3	-22.7	240	53.9	-21.8	-20.3	223	-0.6	-8.4	2.4	8.9	
	15	54.9	-15.6	-28.6	241	53.9	-21.3	-26.5	231	-0.9	-5.6	2.1	6.1	Mean CIELAB difference (17 steps)
	16	55.1	-17.9	-34.5	243	54.5	-21.3	-33.2	237	-0.5	-3.3	1.3	3.7	$\Delta H^*_{CIELAB} = 4.0$
C	17	55.4	-20.2	-40.4	243	55.4	-20.2	-40.4	243	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 4.1$
O	18	48.3	58.2	45.6	38	48.3	58.2	45.6	38	0.0	0.0	0.0	0.0	
	19	50.8	28.2	26.2	43	51.3	33.0	26.5	39	0.5	4.8	0.4	4.8	
Z	20	53.4	-1.7	6.7	105	53.4	-1.7	6.7	105	0.0	0.0	0.0	0.0	Mean CIELAB difference (5 steps)
	21	54.4	-11.0	-16.8	237	52.9	-20.0	-14.8	217	-1.4	-9.0	2.0	9.3	$\Delta H^*_{CIELAB} = 2.8$
C	22	55.4	-20.2	-40.4	243	55.4	-20.2	-40.4	243	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 2.8$

T	i	LAB*a,ref		hab,ref	LAB*a,out		hab,out	LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1			
Y	1	90.9	-17.3	110.7	99	90.9	-17.3	110.7	99	0.0	0.0	0.0	0.0	Specification according to ISO/IEC 15775:1999 Annex G and DIN 33866-1:2000 Annex G	
	2	86.3	-15.2	97.7	99	83.1	-15.0	92.3	99	-3.1	0.2	-5.3	5.4		
	3	81.6	-13.1	84.7	99	79.6	-14.6	82.6	100	-1.9	-1.4	-2.0	2.6		
	4	77.0	-11.0	71.7	99	75.2	-12.1	66.7	100	-1.7	-1.0	-4.9	5.2		
	5	72.3	-8.9	58.8	99	70.5	-9.4	50.7	101	-1.7	-0.5	-7.9	8.1		
	6	67.6	-6.7	45.8	98	65.8	-6.8	36.1	101	-1.7	0.0	-9.6	9.7		
	7	63.0	-4.6	32.8	98	61.8	-4.2	25.2	100	-1.0	0.4	-7.5	7.6		
	8	58.3	-2.5	19.8	98	57.8	-2.1	14.7	99	-0.4	0.4	-5.0	5.1		
Z	9	53.7	-0.4	6.8	94	53.7	-0.4	6.8	94	0.0	0.0	0.0	0.0	Regularity $g^* = 51.7$	
	10	50.3	1.9	1.5	38	49.1	1.8	-0.8	333	-1.0	0.0	-2.3	2.4		
	11	46.9	4.4	-3.7	319	45.3	6.0	-9.4	302	-1.6	1.6	-5.6	6.0		
	12	43.5	6.8	-9.0	307	41.0	8.4	-17.8	295	-2.4	1.6	-8.7	9.0		
	13	40.1	9.3	-14.3	303	37.2	11.5	-22.9	297	-2.9	2.3	-8.6	8.9		
	14	36.8	11.7	-19.5	301	33.8	13.1	-27.4	295	-2.9	1.4	-7.8	8.0		
	15	33.4	14.1	-24.8	300	31.7	15.3	-30.2	297	-1.6	1.2	-5.3	5.5		
	16	30.0	16.6	-30.1	299	28.7	17.4	-32.9	298	-1.2	0.8	-2.7	2.9		
V	17	26.6	19.0	-35.4	298	26.6	19.0	-35.4	298	0.0	0.0	0.0	0.0	Yellow – Violett blue cmy0: Y – Z – V Mean CIELAB difference (17 steps) $\Delta H^*_{CIELAB} = 5.1$ $\Delta E^*_{CIELAB} = 5.4$	
Y	18	90.9	-17.3	110.7	99	90.9	-17.3	110.7	99	0.0	0.0	0.0	0.0		
	19	72.3	-8.9	58.8	99	70.5	-9.4	50.7	101	-1.7	-0.5	-7.9	8.1		
Z	20	53.7	-0.4	6.8	94	53.7	-0.4	6.8	94	0.0	0.0	0.0	0.0		Mean CIELAB difference (5 steps)
	21	40.1	9.3	-14.3	303	37.2	11.5	-22.9	297	-2.9	2.3	-8.6	8.9		
V	22	26.6	19.0	-35.4	298	26.6	19.0	-35.4	298	0.0	0.0	0.0	0.0		
															$\Delta E^*_{CIELAB} = 3.5$

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
L	1	51.5	-61.7	33.8	151	51.5	-61.7	33.8	151	0.0	0.0	0.0	0.0	Specification according to
	2	51.7	-54.2	30.3	151	53.1	-52.9	28.3	152	1.4	1.3	-1.9	2.4	ISO/IEC 15775:1999 Annex G
	3	52.0	-46.7	26.9	150	53.4	-44.7	23.0	153	1.4	2.0	-3.8	4.4	and DIN 33866-1:2000 Annex G
	4	52.2	-39.2	23.4	149	53.9	-38.4	19.0	154	1.6	0.8	-4.3	4.5	4.8
	5	52.5	-31.8	20.0	148	53.3	-31.9	16.6	153	0.8	0.0	-3.3	3.4	3.4
	6	52.8	-24.3	16.5	146	53.1	-25.8	14.0	152	0.4	-1.4	-2.4	2.9	2.9
	7	53.0	-16.8	13.0	142	53.3	-18.8	11.3	149	0.3	-1.9	-1.6	2.7	2.7
	8	53.3	-9.3	9.6	134	53.8	-10.9	9.0	141	0.5	-1.5	-0.5	1.7	1.8
Z	9	53.5	-1.8	6.1	107	53.5	-1.8	6.1	107	0.0	0.0	0.0	0.0	0.0
	10	52.7	6.0	4.8	39	53.3	7.6	3.9	27	0.7	1.6	-0.8	1.8	2.0
	11	51.8	13.9	3.4	14	52.7	18.3	1.8	6	0.8	4.4	-1.5	4.7	4.8
	12	51.0	21.7	2.1	5	53.3	27.5	-1.0	358	2.3	5.8	-3.1	6.6	7.0
	13	50.2	29.6	0.8	1	51.5	37.1	-3.6	354	1.4	7.5	-4.4	8.7	8.8
	14	49.3	37.5	-0.5	359	50.5	43.4	-3.5	355	1.2	5.9	-2.9	6.6	6.7
	15	48.5	45.4	-1.8	358	48.9	49.5	-5.0	354	0.5	4.2	-3.1	5.2	5.2
	16	47.6	53.2	-3.2	356	47.9	55.4	-5.6	354	0.3	2.2	-2.3	3.3	3.3
M	17	46.8	61.1	-4.5	356	46.8	61.1	-4.5	356	0.0	0.0	0.0	0.0	0.0
L	18	51.5	-61.7	33.8	151	51.5	-61.7	33.8	151	0.0	0.0	0.0	0.0	0.0
	19	52.5	-31.8	20.0	148	53.3	-31.9	16.6	153	0.8	0.0	-3.3	3.4	3.4
	20	53.5	-1.8	6.1	107	53.5	-1.8	6.1	107	0.0	0.0	0.0	0.0	0.0
Z	21	50.2	29.6	0.8	1	51.5	37.1	-3.6	354	1.4	7.5	-4.4	8.7	8.8
M	22	46.8	61.1	-4.5	356	46.8	61.1	-4.5	356	0.0	0.0	0.0	0.0	0.0

T	i	LAB*a,ref				hab,ref				LAB*a,out				hab,out				LAB*a,out-ref				ΔH^* ΔE^*				Start output S1			
R	1	46.5	61.0	28.4	25	48.0	58.0	45.8	38	1.5	-2.9	17.4	17.6	17.7	Specification according to														
	2	48.5	56.3	50.2	42	55.5	43.9	55.7	52	7.0	-12.3	5.5	13.5	15.2	ISO/IEC 15775:1999 Annex G														
	3	58.2	39.6	64.6	58	65.4	25.9	70.2	70	7.2	-13.6	5.6	14.8	16.4	and DIN 33866-1:2000 Annex G														
	4	68.8	21.1	80.3	75	77.5	4.3	90.4	87	8.7	-16.7	10.1	19.6	21.5															
J	5	83.0	-3.4	101.4	92	90.8	-17.0	112.2	99	7.8	-13.5	10.8	17.3	19.0															
	6	77.8	-31.2	88.3	110	77.8	-26.2	88.0	107	0.0	5.0	-0.2	5.0	5.0															
	7	64.0	-46.6	61.9	127	66.4	-33.3	62.8	118	2.4	13.3	0.9	13.3	13.5															
	8	53.5	-58.4	41.7	145	59.1	-46.7	45.4	136	5.6	11.7	3.7	12.3	13.5															
G	9	50.3	-54.5	17.7	162	50.5	-60.9	32.9	152	0.3	-6.3	15.2	16.5	16.5															
	10	52.5	-40.0	-6.6	190	53.3	-43.5	-7.3	190	0.8	-3.4	-0.6	3.6	3.7															
C'	11	54.0	-30.4	-22.9	217	57.2	-20.4	-40.0	243	3.3	10.0	-17.0	19.8	20.1															
	12	55.6	-19.6	-41.1	245	44.0	-5.1	-34.8	262	-11.6	14.5	6.3	15.8	19.6	Red-Yellow-Green-Blue														
B	13	40.2	1.3	-38.4	272	27.6	19.1	-35.6	298	-12.6	17.8	2.8	18.0	22.0	cmy0: R-J-G-B-R														
	14	25.8	20.8	-35.5	300	36.4	42.4	-24.9	329	10.6	21.6	10.6	24.1	26.3															
M'	15	34.2	38.0	-23.2	329	47.8	61.3	-5.5	355	13.5	23.3	17.7	29.3	32.2	Mean CIELAB difference (17 steps)														
	16	46.9	62.5	-3.4	357	48.0	60.4	18.5	17	1.1	-2.0	22.0	22.2	22.2	$\Delta H^*_{CIELAB} = 15.4$														
R	17	46.5	61.0	28.4	25	47.1	59.6	44.4	37	0.6	-1.3	16.0	16.0	16.0	$\Delta E^*_{CIELAB} = 17.7$														
R	18	46.5	61.0	28.4	25	48.0	58.0	45.8	38	1.5	-2.9	17.4	17.6	17.7															
J	19	83.0	-3.4	101.4	92	90.8	-17.0	112.2	99	7.8	-13.5	10.8	17.3	19.0															
G	20	50.3	-54.5	17.7	162	50.5	-60.9	32.9	152	0.3	-6.3	15.2	16.5	16.5	Mean CIELAB difference (5 steps)														
B	21	40.2	1.3	-38.4	272	27.6	19.1	-35.6	298	-12.6	17.8	2.8	18.0	22.0	$\Delta H^*_{CIELAB} = 13.9$														
R	22	46.5	61.0	28.4	25	47.1	59.6	44.4	37	0.6	-1.3	16.0	16.0	16.0	$\Delta E^*_{CIELAB} = 18.3$														

T	i	LAB*a,ref			hab,ref		LAB*a,out			hab,out		LAB*a,out-ref			ΔH^*	ΔE^*	Start output S1
R	1	36.7	30.5	14.2	25	39.2	34.5	20.8	31	2.4	4.0	6.6	7.7	8.1	Specification according to		
	2	37.7	28.1	25.1	42	42.0	25.1	27.0	47	4.3	-2.9	1.9	3.6	5.6	ISO/IEC 15775:1999 Annex G		
	3	42.5	19.8	32.3	58	45.8	14.1	34.7	68	3.2	-5.6	2.4	6.2	7.0	and DIN 33866-1:2000 Annex G		
	4	47.9	10.6	40.1	75	50.3	2.2	42.4	87	2.4	-8.3	2.3	8.7	9.0			
J	5	55.0	-1.7	50.7	92	53.5	-8.0	48.6	99	-1.4	-6.2	-2.0	6.7	6.8			
	6	52.4	-15.5	44.1	110	49.7	-15.8	40.0	112	-2.5	-0.2	-4.0	4.1	4.9			
	7	45.5	-23.2	31.0	127	46.5	-22.8	32.1	126	1.0	0.4	1.1	1.2	1.6			
	8	40.2	-29.1	20.9	145	43.1	-29.3	24.1	141	2.9	-0.1	3.2	3.2	4.3			
G	9	38.6	-27.2	8.9	162	40.3	-35.3	15.4	156	1.7	-8.0	6.5	10.4	10.6			
	10	39.7	-19.9	-3.3	190	40.6	-30.5	0.0	180	0.9	-10.5	3.4	11.1	11.1			
C'	11	40.5	-15.1	-11.4	217	41.5	-24.3	-10.5	203	1.0	-9.1	0.9	9.2	9.3			
	12	41.3	-9.7	-20.5	245	34.2	-8.9	-15.0	239	-7.0	0.8	5.5	5.6	9.0	(Red-Yellow-Green-Blue)n		
B	13	33.6	0.7	-19.1	272	27.3	9.4	-19.1	296	-6.2	8.7	0.0	8.7	10.7	cmy0: (R-J-G-B-R)n		
	14	26.4	10.4	-17.7	300	30.8	21.9	-14.1	327	4.4	11.5	3.6	12.1	12.8			
M'	15	30.6	19.0	-11.5	329	36.8	36.5	-3.1	355	6.2	17.5	8.4	19.4	20.4	Mean CIELAB difference (17 steps)		
	16	36.9	31.3	-1.7	357	36.5	35.4	6.7	11	-0.3	4.1	8.5	9.4	9.4	$\Delta H^*_{CIELAB} = 7.5$		
R	17	36.7	30.5	14.2	25	37.0	34.9	18.3	28	0.2	4.4	4.1	6.0	6.0	$\Delta E^*_{CIELAB} = 8.6$		
R	18	36.7	30.5	14.2	25	39.2	34.5	20.8	31	2.4	4.0	6.6	7.7	8.1			
J	19	55.0	-1.7	50.7	92	53.5	-8.0	48.6	99	-1.4	-6.2	-2.0	6.7	6.8			
G	20	38.6	-27.2	8.9	162	40.3	-35.3	15.4	156	1.7	-8.0	6.5	10.4	10.6	Mean CIELAB difference (5 steps)		
B	21	33.6	0.7	-19.1	272	27.3	9.4	-19.1	296	-6.2	8.7	0.0	8.7	10.7	$\Delta H^*_{CIELAB} = 6.7$		
R	22	36.7	30.5	14.2	25	37.0	34.9	18.3	28	0.2	4.4	4.1	6.0	6.0	$\Delta E^*_{CIELAB} = 8.6$		

T	i	LAB*a,ref				hab,ref				LAB*a,out				hab,out				LAB*a,out-ref				ΔH^* ΔE^*				Start output S1			
R	1	71.0	30.5	14.2	25	68.2	26.2	32.5	51	-2.7	-4.2	18.3	18.8	19.0	Specification according to														
	2	72.0	28.1	25.1	42	74.7	15.5	37.8	68	2.7	-12.5	12.7	17.9	18.1	ISO/IEC 15775:1999 Annex G														
	3	76.8	19.8	32.3	58	80.4	4.7	42.7	84	3.6	-15.0	10.4	18.3	18.7	and DIN 33866-1:2000 Annex G														
	4	82.1	10.6	40.1	75	87.3	-5.0	49.1	96	5.2	-15.6	9.0	18.0	18.8															
J	5	89.2	-1.7	50.7	92	92.9	-13.7	54.2	104	3.7	-11.9	3.5	12.5	13.1															
	6	86.6	-15.5	44.1	110	85.5	-17.6	42.2	113	-1.1	-2.0	-1.8	2.8	3.1															
	7	79.7	-23.2	31.0	127	78.5	-18.0	33.0	119	-1.2	5.2	2.0	5.6	5.8															
	8	74.4	-29.1	20.9	145	72.6	-20.5	24.2	130	-1.7	8.6	3.3	9.3	9.5															
G	9	72.8	-27.2	8.9	162	68.6	-24.3	17.9	144	-4.1	2.9	9.0	9.5	10.4															
	10	74.0	-19.9	-3.3	190	70.6	-19.8	1.2	177	-3.2	0.1	4.6	4.6	5.7															
C'	11	74.7	-15.1	-11.4	217	74.1	-13.4	-17.9	233	-0.5	1.7	-6.4	6.7	6.8															
	12	75.5	-9.7	-20.5	245	64.4	-0.6	-19.9	268	-11.1	9.1	0.6	9.2	14.4	(Red-Yellow-Green-Blue)w														
B	13	67.8	0.7	-19.1	272	55.4	10.5	-24.2	293	-12.3	9.8	-5.0	11.1	16.6	(Red-Yellow-Green-Blue)w														
	14	60.6	10.4	-17.7	300	63.0	17.3	-12.5	324	2.4	6.9	5.2	8.7	9.0															
M'	15	64.8	19.0	-11.5	329	70.0	23.0	-1.0	357	5.1	4.0	10.5	11.3	12.4	Mean CIELAB difference (17 steps)														
	16	71.1	31.3	-1.7	357	66.8	24.3	15.9	33	-4.3	-6.9	17.7	19.0	19.5	$\Delta H^*_{\text{CIELAB}} = 10.8$														
R	17	71.0	30.5	14.2	25	66.7	28.2	31.5	48	-4.1	-2.2	17.3	17.4	17.9	$\Delta E^*_{\text{CIELAB}} = 12.9$														
R	18	71.0	30.5	14.2	25	68.2	26.2	32.5	51	-2.7	-4.2	18.3	18.8	19.0															
J	19	89.2	-1.7	50.7	92	92.9	-13.7	54.2	104	3.7	-11.9	3.5	12.5	13.1															
G	20	72.8	-27.2	8.9	162	68.6	-24.3	17.9	144	-4.1	2.9	9.0	9.5	10.4	Mean CIELAB difference (5 steps)														
B	21	67.8	0.7	-19.1	272	55.4	10.5	-24.2	293	-12.3	9.8	-5.0	11.1	16.6	$\Delta H^*_{\text{CIELAB}} = 10.4$														
R	22	71.0	30.5	14.2	25	66.7	28.2	31.5	48	-4.1	-2.2	17.3	17.4	17.9	$\Delta E^*_{\text{CIELAB}} = 14.9$														

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	22.6	0.2	7.1	88	22.6	0.2	7.1	88	0.0	0.0	0.0	0.0	Specification according to
	2	27.2	0.2	6.7	88	25.1	0.3	7.2	88	-2.0	0.1	0.5	0.5	ISO/IEC 15775:1999 Annex G
	3	31.7	0.2	6.2	88	28.1	0.3	6.9	88	-3.5	0.1	0.7	0.7	and DIN 33866-1:2000 Annex G
	4	36.3	0.2	5.8	88	33.3	0.2	6.3	88	-2.9	0.0	0.5	0.5	relative CIELAB data used for "out"
	5	40.8	0.2	5.4	88	37.9	0.2	5.9	88	-2.8	0.1	0.5	0.5	$\Delta L^* = 95.42 - 22.63$
	6	45.4	0.1	4.9	88	43.2	0.1	5.3	89	-2.0	0.0	0.4	0.4	Regularity
	7	49.9	0.1	4.5	88	47.2	0.1	4.8	89	-2.6	0.0	0.3	0.3	$g^* = 74.4$
	8	54.5	0.1	4.1	88	52.6	0.1	4.4	89	-1.8	0.0	0.3	0.3	
Z	9	59.0	0.1	3.7	88	58.4	0.0	3.9	90	-0.5	0.0	0.3	0.3	Lightness gamut relative to offset
	10	63.6	0.1	3.2	88	63.4	0.1	3.2	88	0.0	0.0	0.0	0.0	$f^* = 94.0$
	11	68.1	0.1	2.8	88	68.8	0.0	2.7	90	0.7	0.0	0.0	0.1	
	12	72.7	0.1	2.4	88	73.5	0.0	2.5	90	0.8	0.0	0.1	0.2	Black – White
	13	77.2	0.1	1.9	89	76.9	0.1	1.9	87	-0.3	0.1	0.0	0.1	000n: N – W
	14	81.8	0.0	1.5	89	81.7	0.0	1.6	90	0.0	0.0	0.1	0.1	
	15	86.3	0.0	1.1	89	85.4	0.0	1.0	90	-0.9	0.0	0.0	0.1	Mean CIELAB difference (17 steps)
	16	90.9	0.0	0.6	89	88.9	0.0	0.7	90	-1.9	0.0	0.1	0.1	$\Delta H^*_{CIELAB} = 0.2$
W	17	95.4	0.0	0.2	90	95.4	0.0	0.2	90	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.4$
N	18	22.6	0.2	7.1	88	22.6	0.2	7.1	88	0.0	0.0	0.0	0.0	
	19	40.8	0.2	5.4	88	37.9	0.2	5.9	88	-2.8	0.1	0.5	0.5	
Z	20	59.0	0.1	3.7	88	58.4	0.0	3.9	90	-0.5	0.0	0.3	0.3	Mean CIELAB difference (5 steps)
	21	77.2	0.1	1.9	89	76.9	0.1	1.9	87	-0.3	0.1	0.0	0.1	$\Delta H^*_{CIELAB} = 0.2$
W	22	95.4	0.0	0.2	90	95.4	0.0	0.2	90	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 0.8$
Mean colour reproduction index: $R^*_{ab,m} = 94$														

T	i	LAB*a,ref			hab,ref			LAB*a,out			hab,out			LAB*a,out/c-ref			ΔH^*	ΔE^*	Start output S1
N	1	21.3	0.0	-0.1	243	21.3	0.0	-0.1	243	0.0	0.0	0.0	0.0	0.0	0.0	0.0	0.0	Specification according to	
	2	25.9	0.0	-0.1	242	24.0	0.0	0.0	270	-1.8	0.1	0.1	0.1	1.9	ISO/IEC 15775:1999 Annex G				
	3	30.6	0.0	-0.1	240	26.6	0.0	0.0	0	-3.9	0.1	0.2	0.2	4.0	and DIN 33866-1:2000 Annex G				
	4	35.2	0.0	-0.1	238	32.1	0.0	0.0	0	-3.0	0.1	0.2	0.2	3.1	relative CIELAB data used for "out"				
	5	39.8	0.0	-0.1	236	36.8	0.0	0.1	90	-3.0	0.1	0.3	0.3	3.1	$\Delta L^* = 95.51 - 21.27$				
	6	44.5	0.0	0.0	234	42.6	0.0	0.0	270	-1.8	0.1	0.0	0.1	1.9	Regularity				
	7	49.1	0.0	0.0	231	47.2	0.0	0.0	0	-1.8	0.1	0.1	0.2	1.9	$g^* = 77.3$				
	8	53.8	0.0	0.0	228	51.9	0.0	0.1	90	-1.8	0.1	0.2	0.2	1.9					
Z	9	58.4	0.0	0.0	225	56.8	0.0	0.3	108	-1.5	0.0	0.4	0.4	1.6	Lightness gamut relative to offset				
	10	63.0	0.0	0.0	221	63.2	0.0	0.0	180	0.1	0.0	0.1	0.1	0.2	$f^* = 95.9$				
	11	67.7	0.0	0.0	217	67.4	0.0	0.0	0	-0.2	0.1	0.1	0.1	0.3					
	12	72.3	0.0	0.0	212	71.7	0.0	0.3	90	-0.5	0.1	0.4	0.4	0.7	Black – White				
	13	77.0	0.0	0.0	207	75.9	0.0	0.1	90	-0.9	0.1	0.2	0.2	1.0	w: N – W				
	14	81.6	0.0	0.0	201	81.1	0.0	0.1	90	-0.4	0.1	0.1	0.2	0.5					
	15	86.2	0.0	0.0	194	85.1	0.0	0.1	90	-1.0	0.1	0.1	0.2	1.2	Mean CIELAB difference (17 steps)				
	16	90.9	0.0	0.0	187	89.1	0.0	0.0	0	-1.7	0.1	0.0	0.1	1.8	$\Delta H^*_{CIELAB} = 0.2$				
W	17	95.5	0.0	0.0	180	95.5	0.0	0.0	180	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.5$				
N	18	21.3	0.0	-0.1	243	21.3	0.0	-0.1	243	0.0	0.0	0.0	0.0	0.0					
	19	39.8	0.0	-0.1	236	36.8	0.0	0.1	90	-3.0	0.1	0.3	0.3	3.1					
Z	20	58.4	0.0	0.0	225	56.8	0.0	0.3	108	-1.5	0.0	0.4	0.4	1.6	Mean CIELAB difference (5 steps)				
	21	77.0	0.0	0.0	207	75.9	0.0	0.1	90	-0.9	0.1	0.2	0.2	1.0	$\Delta H^*_{CIELAB} = 0.2$				
W	22	95.5	0.0	0.0	180	95.5	0.0	0.0	180	0.0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.1$				
Mean colour reproduction index:																		$R^*_{ab,m} = 94$	

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	26.9	0.0	0.0	0	26.9	0.0	0.0	0	0.0	0.0	0.0	0.0	Specification according to
	2	31.2	0.0	0.0	0	29.2	-0.6	1.1	122	-1.9	-0.6	1.1	1.3	ISO/IEC 15775:1999 Annex G
	3	35.5	0.0	0.0	0	31.4	-1.5	1.0	148	-4.0	-1.5	1.0	1.9	and DIN 33866-1:2000 Annex G
	4	39.8	0.0	0.0	0	34.1	-1.7	0.5	164	-5.6	-1.7	0.5	1.9	relative CIELAB data used for "out"
	5	44.1	0.0	0.0	0	36.2	-1.9	2.0	135	-7.7	-1.9	2.0	2.8	$\Delta L^* = 95.41 - 26.94$
	6	48.3	0.0	0.0	0	38.8	-1.7	2.1	131	-9.4	-1.7	2.1	2.8	Regularity
	7	52.6	0.0	0.0	0	42.6	-1.3	3.0	115	-9.9	-1.3	3.0	3.3	$g^* = 36.6$
	8	56.9	0.0	0.0	0	47.3	-2.5	4.6	119	-9.5	-2.5	4.6	5.3	
Z	9	61.2	0.0	0.0	0	51.9	-1.7	6.1	106	-9.2	-1.7	6.1	6.4	Lightness gamut relative to offset
	10	65.5	0.0	0.0	0	56.7	-1.3	7.2	101	-8.6	-1.3	7.2	7.3	$f^* = 88.5$
	11	69.7	0.0	0.0	0	61.3	-0.7	7.2	96	-8.3	-0.7	7.2	7.2	
	12	74.0	0.0	0.0	0	65.4	-0.8	6.5	98	-8.6	-0.8	6.5	6.6	Black – White
	13	78.3	0.0	0.0	0	70.0	-0.3	6.3	94	-8.2	-0.3	6.3	6.3	cmy0: N – W
	14	82.6	0.0	0.0	0	75.3	-0.1	5.9	92	-7.2	-0.1	5.9	5.9	
	15	86.9	0.0	0.0	0	80.8	-1.2	5.2	104	-6.0	-1.2	5.2	5.4	Mean CIELAB difference (17 steps)
	16	91.1	0.0	0.0	0	85.1	0.3	1.9	81	-5.9	0.3	1.9	1.9	$\Delta H^*_{CIELAB} = 3.9$
W	17	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 7.7$
N	18	26.9	0.0	0.0	0	26.9	0.0	0.0	0	0.0	0.0	0.0	0.0	
	19	44.1	0.0	0.0	0	36.2	-1.9	2.0	135	-7.7	-1.9	2.0	2.8	
Z	20	61.2	0.0	0.0	0	51.9	-1.7	6.1	106	-9.2	-1.7	6.1	6.4	Mean CIELAB difference (5 steps)
	21	78.3	0.0	0.0	0	70.0	-0.3	6.3	94	-8.2	-0.3	6.3	6.3	$\Delta H^*_{CIELAB} = 3.1$
W	22	95.4	0.0	0.0	0	95.4	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 6.0$
Mean colour reproduction index: $R^*_{ab,m} = 66$														

T	i	LAB*a,ref		hab,ref		LAB*a,out		hab,out		LAB*a,out/c-ref		ΔH^*	ΔE^*	Start output S1
N	1	21.7	0.0	0.0	0	21.7	0.0	0.0	0	0.0	0.0	0.0	0.0	Specification according to
	2	26.3	0.0	0.0	0	22.6	0.0	0.0	0	-3.5	0.0	0.0	3.6	ISO/IEC 15775:1999 Annex G
	3	30.9	0.0	0.0	0	24.8	0.0	0.1	90	-5.9	0.0	0.1	6.0	and DIN 33866-1:2000 Annex G
	4	35.5	0.0	0.0	0	29.1	0.0	0.0	0	-6.3	0.0	0.0	6.4	relative CIELAB data used for "out"
	5	40.1	0.0	0.0	0	34.7	0.0	0.0	0	-5.3	0.0	0.0	5.4	$\Delta L^* = 95.46 - 21.66$
	6	44.7	0.0	0.0	0	40.8	0.0	0.0	0	-3.8	0.0	0.0	3.9	Regularity
	7	49.3	0.0	0.0	0	45.6	0.0	0.2	90	-3.6	0.0	0.2	3.7	$g^* = 54.2$
	8	53.9	0.0	0.0	0	52.5	0.0	0.1	90	-1.3	0.0	0.1	1.4	
Z	9	58.6	0.0	0.0	0	58.7	0.0	0.2	90	0.1	0.0	0.2	0.2	Lightness gamut relative to offset
	10	63.2	0.0	0.0	0	64.5	0.0	0.2	90	1.3	0.0	0.2	1.3	$f^* = 95.3$
	11	67.8	0.0	0.0	0	69.4	0.0	0.2	90	1.6	0.0	0.2	1.6	
	12	72.4	0.0	0.0	0	74.3	0.0	0.2	90	1.9	0.0	0.2	1.9	Black – White
	13	77.0	0.0	0.0	0	79.1	0.0	0.1	90	2.1	0.0	0.1	2.1	rgb: N – W
	14	81.6	0.0	0.0	0	83.0	0.0	0.0	0	1.4	0.0	0.0	1.4	
	15	86.2	0.0	0.0	0	86.4	0.0	0.1	90	0.2	0.0	0.1	0.2	Mean CIELAB difference (17 steps)
	16	90.8	0.0	0.0	0	89.7	0.0	0.2	90	-1.1	0.0	0.2	1.2	$\Delta H^*_{CIELAB} = 0.1$
W	17	95.5	0.0	0.0	0	95.5	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 2.4$
N	18	21.7	0.0	0.0	0	21.7	0.0	0.0	0	0.0	0.0	0.0	0.0	
	19	40.1	0.0	0.0	0	34.7	0.0	0.0	0	-5.3	0.0	0.0	5.4	
Z	20	58.6	0.0	0.0	0	58.7	0.0	0.2	90	0.1	0.0	0.2	0.2	Mean CIELAB difference (5 steps)
	21	77.0	0.0	0.0	0	79.1	0.0	0.1	90	2.1	0.0	0.1	2.1	$\Delta H^*_{CIELAB} = 0.1$
W	22	95.5	0.0	0.0	0	95.5	0.0	0.0	0	0.0	0.0	0.0	0.0	$\Delta E^*_{CIELAB} = 1.6$
Mean colour reproduction index: $R^*_{ab,m} = 90$														