

Input and output:
Colorimetric Printer Reflective System FRS09_92aM
data for any colour:

u^*_d and number $no.$ = 00 .. 15


device hue text:

$u^*_d = 16$ hues 000y, 025y, ..., m50o

contrast reduction factor:

$c_R = 0.9$

FRS09_92aM; adapted (a) CIELAB data					
u^*_d	$L^*=L^*_{ab}$	a^*_a	b^*_a	C^*_{ab}	h^*_{ab}
000y	38.8	53.92	39.68	66.95	36
025y	47.46	42.34	51.25	66.48	50
050y	56.54	30.2	63.39	70.22	65
075y	67.39	15.68	77.9	79.47	79
100c	82.58	-4.64	98.22	98.33	93
150c	70.85	-21.66	80.19	83.07	105
250l	61.91	-34.63	66.45	74.93	118
350l	54.24	-45.77	54.66	71.29	130
450l	46.95	-56.34	43.46	71.15	142
500c	51.91	-36.84	-3.21	36.98	185
600b	54.62	-26.2	-28.68	38.85	228
650v	42.22	-0.61	-37.35	37.36	269
700m	20.01	45.2	-52.87	69.56	311
750m	29.93	57.31	-42.0	71.05	324
800o	40.88	70.68	-29.99	76.78	337
850o	39.77	61.72	7.23	62.15	7



% Gamut

$u^*_{rel} = 88$

% Regularity

$g^*_{H,rel} = 31$

$g^*_{C,rel} = 40$

FRS09_92aM; adapted (a) CIELAB data					
Name	$L^*=L^*_{ab}$	a^*_a	b^*_a	C^*_{ab}	h^*_{ab}
0Ma	38.8	53.92	39.68	66.95	36
YMa	82.58	-4.64	98.22	98.33	93
LMa	46.95	-56.34	43.46	71.15	142
CMa	54.62	-26.2	-28.68	38.85	228
VMa	20.01	45.2	-52.87	69.56	311
MMa	40.88	70.68	-29.99	76.78	337
NMa	15.0	0.0	0.0	0.0	0
WMa	90.0	0.0	0.0	0.0	0
OCie	39.92	58.74	27.99	65.07	25
YCie	81.26	-2.89	71.56	71.62	92
LCie	52.23	-42.42	13.6	44.55	162
VCie	30.57	1.41	-46.47	46.49	272

