





Siehe ähnliche Dateien: <http://www.ps.bam.de/Eg50/>; <http://www.ps.bam.de/Eg50/HTM>
Technische Information: <http://www.ps.bam.de> Version 2.1, io=1, ColSpX=1




Farb und Helligkeit: Farbmetrik-Systeme (D50, 2°) und Helligkeit (L*)

Farbmetrik-Systeme (D50, 2°)	Helligkeit (L*)
1	39.12
2	65.43
3	49.87
4	44.26
5	55.56
6	70.82
7	63.51
8	39.92
9	28.86
10	16.19
11	8.29
12	3.44
13	31.41
14	72.46
15	72.05
16	29.37
17	54.91
18	82.02
19	52.24
20	97.06
21	82.02
22	52.24
23	29.37
24	16.19
25	8.29
26	3.44
27	31.41
28	72.46
29	72.05
30	29.37
31	54.91
32	82.02
33	52.24
34	97.06
35	82.02
36	52.24
37	29.37
38	16.19
39	8.29
40	3.44
41	31.41
42	72.46
43	72.05
44	29.37
45	54.91
46	82.02
47	52.24
48	97.06
49	82.02
50	52.24
51	29.37
52	16.19
53	8.29
54	3.44
55	31.41
56	72.46
57	72.05
58	29.37
59	54.91
60	82.02
61	52.24
62	97.06
63	82.02
64	52.24
65	29.37
66	16.19
67	8.29
68	3.44
69	31.41
70	72.46
71	72.05
72	29.37
73	54.91
74	82.02
75	52.24
76	97.06
77	82.02
78	52.24
79	29.37
80	16.19
81	8.29
82	3.44
83	31.41
84	72.46
85	72.05
86	29.37
87	54.91
88	82.02
89	52.24
90	97.06
91	82.02
92	52.24
93	29.37
94	16.19
95	8.29
96	3.44
97	31.41
98	72.46
99	72.05
100	29.37
101	54.91
102	82.02
103	52.24
104	97.06
105	82.02
106	52.24
107	29.37
108	16.19
109	8.29
110	3.44
111	31.41
112	72.46
113	72.05
114	29.37
115	54.91
116	82.02
117	52.24
118	97.06
119	82.02
120	52.24
121	29.37
122	16.19
123	8.29
124	3.44
125	31.41
126	72.46
127	72.05
128	29.37
129	54.91
130	82.02
131	52.24
132	97.06
133	82.02
134	52.24
135	29.37
136	16.19
137	8.29
138	3.44
139	31.41
140	72.46
141	72.05
142	29.37
143	54.91
144	82.02
145	52.24
146	97.06
147	82.02
148	52.24
149	29.37
150	16.19
151	8.29
152	3.44
153	31.41
154	72.46
155	72.05
156	29.37
157	54.91
158	82.02
159	52.24
160	97.06






Farb und Helligkeit: Farbmetrik-Systeme (D50, 2°) und Helligkeit (L*)

Farbmetrik-Systeme (D50, 2°)	Helligkeit (L*)
1	39.12
2	65.43
3	49.87
4	44.26
5	55.56
6	70.82
7	63.51
8	39.92
9	28.86
10	16.19
11	8.29
12	3.44
13	31.41
14	72.46
15	72.05
16	29.37
17	54.91
18	82.02
19	52.24
20	97.06
21	82.02
22	52.24
23	29.37
24	16.19
25	8.29
26	3.44
27	31.41
28	72.46
29	72.05
30	29.37
31	54.91
32	82.02
33	52.24
34	97.06
35	82.02
36	52.24
37	29.37
38	16.19
39	8.29
40	3.44
41	31.41
42	72.46
43	72.05
44	29.37
45	54.91
46	82.02
47	52.24
48	97.06
49	82.02
50	52.24
51	29.37
52	16.19
53	8.29
54	3.44
55	31.41
56	72.46
57	72.05
58	29.37
59	54.91
60	82.02
61	52.24
62	97.06
63	82.02
64	52.24
65	29.37
66	16.19
67	8.29
68	3.44
69	31.41
70	72.46
71	72.05
72	29.37
73	54.91
74	82.02
75	52.24
76	97.06
77	82.02
78	52.24
79	29.37
80	16.19
81	8.29
82	3.44
83	31.41
84	72.46
85	72.05
86	29.37
87	54.91
88	82.02
89	52.24
90	97.06
91	82.02
92	52.24
93	29.37
94	16.19
95	8.29
96	3.44
97	31.41
98	72.46
99	72.05
100	29.37
101	54.91
102	82.02
103	52.24
104	97.06
105	82.02
106	52.24
107	29.37
108	16.19
109	8.29
110	3.44
111	31.41
112	72.46
113	72.05
114	29.37
115	54.91
116	82.02
117	52.24
118	97.06
119	82.02
120	52.24
121	29.37
122	16.19
123	8.29
124	3.44
125	31.41
126	72.46
127	72.05
128	29.37
129	54.91
130	82.02
131	52.24
132	97.06
133	82.02
134	52.24
135	29.37
136	16.19
137	8.29
138	3.44
139	31.41
140	72.46
141	72.05
142	29.37
143	54.91
144	82.02
145	52.24
146	97.06
147	82.02
148	52.24
149	29.37
150	16.19
151	8.29
152	3.44
153	31.41
154	72.46
155	72.05
156	29.37
157	54.91
158	82.02
159	52.24
160	97.06



Farb und Helligkeit: Farbmetrik-Systeme (D50, 2°) und Helligkeit (L*)

Farbmetrik-Systeme (D50, 2°)	Helligkeit (L*)
1	39.12
2	65.43
3	49.87
4	44.26
5	55.56
6	70.82
7	63.51
8	39.92
9	28.86
10	16.19
11	8.29
12	3.44
13	31.41
14	72.46
15	72.05
16	29.37
17	54.91
18	82.02
19	52.24
20	97.06
21	82.02
22	52.24
23	29.37
24	16.19
25	8.29
26	3.44
27	31.41
28	72.46
29	72.05
30	29.37
31	54.91
32	82.02
33	52.24
34	97.06
35	82.02
36	52.24
37	29.37
38	16.19
39	8.29
40	3.44
41	31.41
42	72.46
43	72.05
44	29.37
45	54.91
46	82.02
47	52.24
48	97.06
49	82.02
50	52.24
51	29.37
52	16.19
53	8.29
54	3.44
55	31.41
56	72.46
57	72.05
58	29.37
59	54.91
60	82.02
61	52.24
62	97.06
63	82.02
64	52.24
65	29.37
66	16.19
67	8.29
68	3.44
69	31.41
70	72.46
71	72.05
72	29.37
73	54.91
74	82.02
75	52.24
76	97.06
77	82.02
78	52.24
79	29.37
80	16.19
81	8.29
82	3.44
83	31.41
84	72.46
85	72.05
86	29.37
87	54.91
88	82.02
89	52.24
90	97.06
91	82.02
92	52.24
93	29.37
94	16.19
95	8.29
96	3.44
97	31.41
98	72.46
99	72.05
100	29.37
101	54.91
102	82.02
103	52.24
104	97.06
105	82.02
106	52.24
107	29.37
108	16.19
109	8.29
110	3.44
111	31.41
112	72.46
113	72.05
114	29.37
115	54.91
116	82.02
117	52.24
118	97.06
119	82.02
120	52.24
121	29.37
122	16.19
123	8.29
124	3.44
125	31.41
126	72.46
127	72.05
128	29.37
129	54.91
130	82.02
131	52.24
132	97.06
133	82.02
134	52.24
135	29.37
136	16.19
137	8.29
138	3.44
139	31.41
140	72.46
141	72.05
142	29.37
143	54.91
144	82.02
145	52.24
146	97.06
147	82.02
148	52.24
149	29.37
150	16.19
151	8.29
152	3.44
153	31.41
154	72.46
155	72.05
156	29.37
157	54.91
158	82.02
159	52.24
160	97.06



BAM-Registrierung: 20080901-Eg50/L50G00N1.PS/.TXT
Anwendung für Beurteilung und Messung von Drucker- oder Monitorsystemen