
www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe37-1_Picture BA1: 16-equidistant steps W=K, W=M, W=Y, W=N, W=Z, PS operator olv* setrgbcolor
Fe370-3_Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sl); PS operators setrunrefer, 4 colorimage
Fe371-3_Picture B2: Script and Landolt-rings N, C, M, Y, Z; PS operator olv* setrgbcolor
Fe371-5_Picture B2: Radial gratings W=C, W=M, W=Y, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-5_Picture B1C: Landolt-rings W=C, W=M; PS operator olv* setrgbcolor
Fe371-5_Picture B1Z: Landolt-rings Z=C, Z=M; PS operator olv* setrgbcolor
Fe371-7_Picture B3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator olv* setrgbcolor
Fe371-7_Picture B7: Landolt-rings W=C, W=M, W=Y, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-7_Picture B7Z: Landolt-rings Z=C, Z=M, Z=Y, Z=N, Z=Z; PS operator olv* setrgbcolor
Fe370-7_Picture B7N: Landolt-rings N=C, N=M, N=Y, N=N, N=Z; PS operator olv* setrgbcolor
Fe37–2; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe370-3_Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sl); PS operators setrunrefer, 4 colorimage
Fe371-3_Picture B2: Script and Landolt-rings N, C, M, Y, Z; PS operator olv* setrgbcolor
Fe371-5_Picture B2: Radial gratings W=C, W=M, W=Y, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-5_Picture B1C: Landolt-rings N=C, N=M; PS operator olv* setrgbcolor
Fe371-5_Picture B1Z: Landolt-rings Z=C, Z=M; PS operator olv* setrgbcolor
Fe371-7_Picture B3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator olv* setrgbcolor
Fe371-7_Picture B7: Landolt-rings W=C, W=M, W=Y, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-7_Picture B7Z: Landolt-rings Z=C, Z=M, Z=Y, Z=N, Z=Z; PS operator olv* setrgbcolor
Fe370-7_Picture B7N: Landolt-rings N=C, N=M, N=Y, N=N, N=Z; PS operator olv* setrgbcolor
Fe37–2; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe370-3_Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sl); PS operators setrunrefer, 4 colorimage
Fe371-3_Picture D2: Script and Landolt-rings N, O, L, V, Z; PS operator olv* setrgbcolor
Fe371-5_Picture D2: Radial gratings W=O, W=L, W=V, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-5_Picture D1C: Landolt-rings W=O, W=L; PS operator olv* setrgbcolor
Fe371-5_Picture D1Z: Landolt-rings Z=O, Z=L; PS operator olv* setrgbcolor
Fe371-7_Picture D3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator olv* setrgbcolor
Fe371-7_Picture D7: Landolt-rings W=O, W=L, W=V, W=N, W=Z; PS operator olv* setrgbcolor
Fe371-7_Picture D7Z: Landolt-rings Z=O, Z=L, Z=V, Z=N, Z=Z; PS operator olv* setrgbcolor
Fe370-7_Picture D7N: Landolt-rings N=O, N=L, N=V, N=N, N=Z; PS operator olv* setrgbcolor
Fe37–3; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe370-3_Picture D1N: Script and Landolt-rings W, O, L, V, Z; PS operator olv* setrgbcolor
Fe371-3_Picture D2Z: Script and Landolt-rings N, O, L, V, W; PS operator olv* setrgbcolor
Fe371-5_Picture D2N: Landolt-rings N=O, N=L; PS operator olv* setrgbcolor
Fe371-5_Picture D1Z: Landolt-rings Z=O, Z=L; PS operator olv* setrgbcolor
Fe371-7_Picture D7: Landolt-rings W=O, W=L; PS operator olv* setrgbcolor
Fe371-7_Picture D7Z: Landolt-rings Z=W, Z=O, Z=L; PS operator olv* setrgbcolor
Fe370-7_Picture D7N: Landolt-rings N=W, N=O, N=L; PS operator olv* setrgbcolor
Fe37–4; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


A B C D E F G H I J K L M N O P Q R S T U V W X Y Z a b c d e f g h i j k l m n
01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27
Fe37–x_olv* CalSpot=1 column=0 nchart=1 xcharts=4 DiLimp=8, (A=a, K=q), DiLimp=1, (b=j)


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe370-3_Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sl); PS operators setrunrefer, 4 colorimage
Fe371-3_Picture B2: Script and Landolt-rings N, C, M, Y, Z; PS operator rgb* setrgbcolor
Fe371-5_Picture B2: Radial gratings W=C, W=M, W=Y, W=N, W=Z; PS operator rgb* setrgbcolor
Fe371-5_Picture B1C: Landolt-rings W=C, W=M; PS operator rgb* setrgbcolor
Fe371-5_Picture B1Z: Landolt-rings Z=C, Z=M; PS operator rgb* setrgbcolor
Fe371-7_Picture B3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator rgb* setrgbcolor
Fe371-7_Picture B7: Landolt-rings W=C, W=M, W=Y, W=N, W=Z; PS operator rgb* setrgbcolor
Fe371-7_Picture B7Z: Landolt-rings Z=C, Z=M, Z=Y, Z=N, Z=Z; PS operator rgb* setrgbcolor
Fe370-7_Picture B7N: Landolt-rings N=C, N=M, N=Y, N=N, N=Z; PS operator rgb* setrgbcolor
Fe37–5; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe370-3_Picture B1N: Script and Landolt-rings W, C, M, J, Z; PS operator rgb* setrgbcolor
Fe371-3_Picture B2Z: Script and Landolt-rings N, C, M, J, W; PS operator rgb* setrgbcolor
Fe371-5_Picture B2N: Landolt-rings N=C, N=M; PS operator rgb* setrgbcolor
Fe371-5_Picture B1Z: Landolt-rings Z=C, Z=M; PS operator rgb* setrgbcolor
Fe371-7_Picture B3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator rgb* setrgbcolor
Fe371-7_Picture B7: Landolt-rings W=C, W=M, W=Y, W=N, W=Z; PS operator rgb* setrgbcolor
Fe371-7_Picture B7Z: Landolt-rings Z=C, Z=M, Z=Y, Z=N, Z=Z; PS operator rgb* setrgbcolor
Fe370-7_Picture B7N: Landolt-rings N=C, N=M, N=Y, N=N, N=Z; PS operator rgb* setrgbcolor
Fe37–7; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe370-3_Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sl); PS operators setrunrefer, 4 colorimage
Fe371-3_Picture D2: Script and Landolt-rings N, R, G, B, Z; PS operator rgb* setrgbcolor
Fe371-5_Picture D2: Radial gratings W=R, W=G, W=B, W=N, W=Z; PS operator rgb* setrgbcolor
Fe371-5_Picture D1C: Landolt-rings W=R, W=G; PS operator rgb* setrgbcolor
Fe371-5_Picture D1Z: Landolt-rings Z=R, Z=G; PS operator rgb* setrgbcolor
Fe371-7_Picture D3: 14 CIE-test colours and 2 + 16 grey steps; Use of PS operator rgb* setrgbcolor
Fe371-7_Picture D7: Landolt-rings W=R, W=G, W=B, W=N, W=Z; PS operator rgb* setrgbcolor
Fe371-7_Picture D7Z: Landolt-rings Z=R, Z=G, Z=B, Z=N, Z=Z; PS operator rgb* setrgbcolor
Fe370-7_Picture D7N: Landolt-rings N=R, N=G, N=B, N=N, N=Z; PS operator rgb* setrgbcolor
Fe37–8; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/


www.ps.bam.de/Fe37/10L/L26e00NP.PDF/ .PS, Page 2/6; ORS22_96, L*=22_96; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe370-3_Picture D1N: Script and Landolt-rings W, R, G, B, Z; PS operator rgb* setrgbcolor
Fe371-3_Picture D2Z: Script and Landolt-rings N, R, G, B, W; PS operator rgb* setrgbcolor
Fe371-5_Picture D2N: Landolt-rings N=R, N=G; PS operator rgb* setrgbcolor
Fe371-5_Picture D1Z: Landolt-rings Z=R, Z=G; PS operator rgb* setrgbcolor
Fe371-7_Picture D7: Landolt-rings W=R, W=G; PS operator rgb* setrgbcolor
Fe371-7_Picture D7Z: Landolt-rings Z=W, Z=R, Z=G; PS operator rgb* setrgbcolor
Fe370-7_Picture D7N: Landolt-rings N=W, N=R, N=G; PS operator rgb* setrgbcolor
Fe37–9; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe37/10L/L26e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code= tbdata
Technical information: http://www.ps.bam.de
Version 2.1, 1st L1 GSRxe1
Seven files installed files: http://www.ps.bam.de/Fe37/