
www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39-1; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39-2; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39-3; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39-4; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


Fe39-5, olv* CellSpx=1 colorm=0 xchart=0 xcharts=4 DEmg=0, (A - a, k - n), DEimg=1, (b - j)


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39-6; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39-7; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39-8; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1


www.ps.bam.de/Fe39/10Y/Y10100NP.PS./PDF, Page 1/6; ORS20_95, L*=20_95; start output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39-9; Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb-->olv* setrgbcolor
output: no change compared to input
BAM registration: 2008/10[F] | Fe39/10Y/Y10100NP.PS./PDF
BAM material: code=ba4a
application for evaluation and measurement of printer or monitor systems
See for sample files: http://www.ps.bam.de/Fe39/ www.ps.bam.de/Fe-TDM
Technical information: http://www.ps.bam.de
Version 2.1.1-rc11.1, colSpec=1