
www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39–1, Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sf); PS operators setxrmatfer, 4 colorimage
Fe39–2, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39–2, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39–1, Picture B1: Flower motif, 14 CIE-test colours, 16 grey steps (sf); PS operators setxrmatfer, 4 colorimage
Fe39–2, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39–4, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, olv* interpretation
input: rgb−>olv* setrgbcolor
output: olv*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


A B C D E F G H I J K L M N O P Q R S T U V W X Y Z a b c d e f g h i j k l m n
01 02 03 04 05 06 07 08 09 10 11 12 13 14 15 16 17 18 19 20 21 22 23 24 25 26 27


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39–6, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B1 to B7 similar ISO/IEC-Test chart 2, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39–7, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. B4 to B7 similar ISO/IEC-Test chart 2, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
image pixel: 192 x 128
384 x 256
768 x 512
1536 x 1024
3072 x 2048
Fe39–8, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D1 to D7 similar ISO/IEC-Test chart 4, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS


www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS, Page 2/6; ORS20_95, L*=20_95; transfer and output
N: No Output Linearization (OL) data in File (F), Startup (S) or Device (D)
Fe39–9, Test elements of ISO/IEC 15775 and ISO/IEC TR 24705
Fig. D4 to D7 similar ISO/IEC-Test chart 4, rgb* interpretation
input: rgb−>rgb* setrgbcolor
output: rgb*−>cmyn6* setcmyk
BAM registration: 20081001-Fe39/10L/L39e00NP.PDF/ .PS
application for evaluation and measurement of printer or monitor systems
BAM material- code- tbaka
Version 2.1e-1-LG3Sw1
Technical information: http://www.ps.bam.de
Specified files: http://www.ps.bam.de/Fe39/10L/L39e00NP.PDF/ .PS