

Ostwald optimal colours (o) of maximum (m) C_{AB} for P60, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X	Y	Z	x	y	z	h _{xy}	i _d , λ _d	i _c , λ _c	Code
0 405	32 563	28.82	51.16	91.8	0.1678	0.2978	0.5343	192.3	16 483	38 590	Cm
6 435	32 563	25.32	51.64	72.68	0.1692	0.345	0.4856	174.9	17 487	44 621	
10 450	33 565	20.2	52.18	42.4	0.1759	0.4545	0.3694	139.8	19 497	-1 497c	
11 460	33 566	19.92	53.26	34.94	0.1842	0.4925	0.3231	130.4	20 502	-1 502c	
13 465	33 568	18.67	53.76	21.75	0.1982	0.5707	0.2309	117.2	22 513	-1 513c	
14 470	34 570	19.4	55.08	16.63	0.2129	0.6045	0.1825	111.7	24 521	-1 521c	
15 475	34 574	21.44	57.31	12.55	0.2348	0.6277	0.1374	106.3	25 529	-1 529c	Gm
15 480	36 580	26.34	61.97	12.56	0.2611	0.6143	0.1245	102.0	27 535	-1 535c	
17 485	39 595	37.55	69.1	7.04	0.3303	0.6077	0.0619	88.2	29 549	-1 549c	
18 490	-1 490c	70.6	83.47	5.25	0.4431	0.5238	0.0329	57.7	33 566	11 459	max
19 495	-1 495c	70.56	82.19	3.88	0.4504	0.5247	0.0247	56.3	33 567	12 461	
20 500	-1 500c	70.54	80.59	2.81	0.4582	0.5234	0.0183	54.5	33 568	12 464	
22 510	-1 510c	70.43	76.17	1.41	0.4758	0.5145	0.0095	49.9	34 570	13 469	
24 520	-1 520c	69.86	70.05	0.71	0.4967	0.4981	0.005	43.5	34 572	14 473	Ym
25 530	-1 529c	69.26	66.47	0.49	0.5084	0.4879	0.0036	39.9	34 574	15 475	
27 540	-1 539c	67.32	58.65	0.23	0.5334	0.4647	0.0018	32.1	35 578	15 478	
29 545	-1 545c	64.25	50.34	0.11	0.5601	0.4388	0.001	24.2	36 582	16 480	
29 550	-1 549c	64.25	50.34	0.11	0.5601	0.4388	0.001	24.2	36 582	16 480	
30 555	-1 554c	62.26	46.13	0.08	0.5739	0.4252	0.0007	20.3	36 584	16 481	
32 560	-1 560c	57.28	37.83	0.05	0.6019	0.3975	0.0005	13.2	37 589	16 483	
32 563	0 405	68.24	48.83	12.76	0.5255	0.3761	0.0983	12.3	38 590	16 483	Rm
32 563	6 435	71.74	48.35	31.89	0.472	0.3181	0.2098	354.9	44 621	17 487	
33 565	10 450	76.86	47.81	62.16	0.4113	0.2559	0.3327	319.8	-1 497c	19 497	
33 566	11 460	77.14	46.73	69.62	0.3986	0.2415	0.3598	310.5	-1 502c	20 502	
33 568	13 465	78.39	46.23	82.82	0.3778	0.2228	0.3992	297.3	-1 513c	22 513	
34 570	14 470	77.66	44.91	87.94	0.3689	0.2133	0.4177	291.7	-1 521c	24 521	
34 574	15 475	75.62	42.68	92.02	0.3595	0.2029	0.4375	286.4	-1 529c	25 529	Mm
36 580	15 480	70.72	38.02	92.01	0.3522	0.1894	0.4583	282.1	-1 535c	27 535	
39 595	17 485	59.51	30.89	97.52	0.3166	0.1644	0.5189	268.2	-1 549c	29 549	
-1 490c	18 490	26.46	16.52	99.31	0.1859	0.1161	0.6978	237.7	11 459	33 566	min
-1 495c	19 495	26.5	17.8	100.69	0.1828	0.1227	0.6944	236.3	12 461	33 567	
-1 500c	20 500	26.52	19.4	101.75	0.1795	0.1314	0.6889	234.6	12 464	33 568	
-1 510c	22 510	26.63	23.82	103.15	0.1733	0.155	0.6715	229.9	13 469	34 570	
-1 520c	24 520	27.2	29.94	103.86	0.1689	0.1859	0.645	223.6	14 473	34 572	Bm
-1 529c	25 530	27.8	33.52	104.07	0.168	0.2026	0.6292	219.9	15 475	34 574	
-1 539c	27 540	29.74	41.34	104.33	0.1695	0.2356	0.5947	212.2	15 478	35 578	
-1 545c	29 545	32.81	49.65	104.45	0.1755	0.2656	0.5587	204.2	16 480	36 582	
-1 549c	29 550	32.81	49.65	104.45	0.1755	0.2656	0.5587	204.2	16 480	36 582	
-1 554c	30 555	34.8	53.86	104.48	0.1802	0.2788	0.5409	200.4	16 481	36 584	
-1 560c	32 560	39.78	62.16	104.52	0.1926	0.301	0.5062	193.2	16 483	37 589	
380	770	85.99	88.58	92.64	0.3218	0.3315	0.3466	0.0			