

Ostwald optimal colours (o) of maximum (m) C_{AB} for P60, $Y_w=88,6$, $Y_m=520_770$

i_1, λ_1	i_2, λ_2	Y	A	B	C_{AB}	a	b	h_{AB}	i_d, λ_d	i_c, λ_c	Code
0 405	32 563	51.16	−20.83	−15.32	25.86	0.5634	−0.7177	216.3	16 483	38 590	Cm
6 435	32 563	51.64	−24.8	−7.47	25.9	0.4903	−0.5629	196.7	17 487	44 621	
10 450	33 565	52.18	−30.45	4.86	30.83	0.3871	−0.325	170.9	19 497	−1 497c	
11 460	33 566	53.26	−31.78	8.3	32.84	0.374	−0.2624	165.3	20 502	−1 502c	
13 465	33 568	53.76	−33.5	13.78	36.23	0.3474	−0.1618	157.6	22 513	−1 513c	
14 470	34 570	55.08	−34.07	16.39	37.8	0.3521	−0.1207	154.3	24 521	−1 521c	
15 475	34 574	57.31	−34.19	18.95	39.09	0.374	−0.0875	151.0	25 529	−1 529c	Gm
15 480	36 580	61.97	−33.81	20.89	39.74	0.4251	−0.081	148.2	27 535	−1 535c	
17 485	39 595	69.1	−29.51	26.08	39.39	0.5435	−0.0407	138.5	29 549	−1 549c	
18 490	−1 490c	83.47	−10.42	32.81	34.42	0.8458	−0.0251	107.6	33 566	11 459	max
19 495	−1 495c	82.19	−9.22	32.82	34.1	0.8584	−0.0188	105.6	33 567	12 461	
20 500	−1 500c	80.59	−7.68	32.58	33.47	0.8753	−0.0139	103.2	33 568	12 464	
22 510	−1 510c	76.17	−3.5	31.29	31.49	0.9246	−0.0074	96.3	34 570	13 469	
24 520	−1 520c	70.05	1.86	29.01	29.07	0.9972	−0.004	86.3	34 572	14 473	Ym
25 530	−1 529c	66.47	4.73	27.6	28.01	1.0419	−0.0029	80.2	34 574	15 475	
27 540	−1 539c	58.65	10.38	24.43	26.55	1.1478	−0.0016	66.9	35 578	15 478	
29 545	−1 545c	50.34	15.38	21.01	26.04	1.2763	−0.0009	53.7	36 582	16 480	
29 550	−1 549c	50.34	15.38	21.01	26.04	1.2763	−0.0009	53.7	36 582	16 480	
30 555	−1 554c	46.13	17.47	19.26	26.01	1.3495	−0.0007	47.7	36 584	16 481	
32 560	−1 560c	37.83	20.56	15.8	25.93	1.5141	−0.0005	37.5	37 589	16 483	
32 563	0 405	48.83	20.83	15.32	25.86	1.3973	−0.1045	36.3	38 590	16 483	Rm
32 563	6 435	48.35	24.8	7.47	25.9	1.4836	−0.2637	16.7	44 621	17 487	
33 565	10 450	47.81	30.45	−4.86	30.83	1.6076	−0.52	350.9	−1 497c	19 497	
33 566	11 460	46.73	31.78	−8.3	32.84	1.6506	−0.5959	345.3	−1 502c	20 502	
33 568	13 465	46.23	33.5	−13.78	36.23	1.6954	−0.7165	337.6	−1 513c	22 513	
34 570	14 470	44.91	34.07	−16.38	37.8	1.7292	−0.7832	334.3	−1 521c	24 521	
34 574	15 475	42.68	34.19	−18.95	39.09	1.7719	−0.8624	331.0	−1 529c	25 529	Mm
36 580	15 480	38.02	33.81	−20.89	39.74	1.8599	−0.9679	328.2	−1 535c	27 535	
39 595	17 485	30.89	29.51	−26.08	39.39	1.9259	−1.2624	318.5	−1 549c	29 549	
−1 490c	18 490	16.52	10.42	−32.81	34.42	1.6012	−2.4036	287.6	11 459	33 566	min
−1 495c	19 495	17.8	9.22	−32.82	34.09	1.4887	−2.262	285.6	12 461	33 567	
−1 500c	20 500	19.4	7.68	−32.58	33.47	1.3667	−2.0973	283.2	12 464	33 568	
−1 510c	22 510	23.82	3.5	−31.29	31.49	1.1179	−1.732	276.3	13 469	34 570	
−1 520c	24 520	29.94	−1.86	−29.01	29.07	0.9085	−1.3871	266.3	14 473	34 572	Bm
−1 529c	25 530	33.52	−4.73	−27.6	28.01	0.8293	−1.2418	260.2	15 475	34 574	
−1 539c	27 540	41.34	−10.38	−24.43	26.55	0.7194	−1.0093	246.9	15 478	35 578	
−1 545c	29 545	49.65	−15.38	−21.01	26.04	0.6608	−0.8413	233.7	16 480	36 582	
−1 549c	29 550	49.65	−15.38	−21.01	26.04	0.6608	−0.8413	233.7	16 480	36 582	
−1 554c	30 555	53.86	−17.47	−19.26	26.01	0.6462	−0.7758	227.7	16 481	36 584	
−1 560c	32 560	62.16	−20.56	−15.8	25.93	0.6399	−0.6725	217.5	16 483	37 589	
380	770	88.58	0.0	0.0	0.01	0.9706	−0.4182	0.0			