

Ostwald optimal colours (o) of maximum (m) C_{AB} for D65, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	32 561	51.56	−20.15	−15.85	25.64	0.5596	−0.743	218.1	16 483	37 589	Cm
6 435	32 562	52.08	−23.73	−8.75	25.29	0.4948	−0.6036	200.2	17 486	42 610	
10 450	32 563	52.64	−29.71	4.36	30.03	0.3859	−0.3525	171.6	19 496	−1 496c	
12 460	33 565	53.43	−32.29	11.21	34.18	0.3461	−0.2256	160.8	21 505	−1 505c	
12 465	33 567	54.62	−32.47	11.73	34.52	0.356	−0.2207	160.1	21 506	−1 506c	
14 470	33 569	55.56	−33.79	17.12	37.88	0.3422	−0.1274	153.1	24 520	−1 520c	
15 475	34 573	57.84	−33.91	19.9	39.33	0.364	−0.0913	149.5	25 528	−1 528c	Gm
16 480	36 580	61.97	−33.2	23.07	40.43	0.4146	−0.0632	145.2	27 537	−1 537c	
17 485	39 595	69.76	−29.0	27.46	39.94	0.5347	−0.0418	136.5	29 548	−1 548c	
18 490	−1 490c	83.1	−10.68	34.02	35.66	0.8218	−0.0261	107.4	33 565	11 459	max
19 495	−1 495c	81.77	−9.46	34.01	35.3	0.8346	−0.0195	105.5	33 566	12 462	
20 500	−1 500c	80.1	−7.9	33.73	34.64	0.8518	−0.0144	103.1	33 567	12 464	
22 510	−1 510c	75.54	−3.68	32.32	32.53	0.9016	−0.0076	96.5	33 569	13 469	
23 520	−1 519c	72.63	−1.11	31.22	31.24	0.935	−0.0056	92.0	34 570	14 471	Ym
25 530	−1 529c	65.59	4.57	28.36	28.73	1.0201	−0.0031	80.8	34 573	15 475	
27 540	−1 539c	57.49	10.25	24.94	26.97	1.1288	−0.0016	67.6	35 577	15 478	
28 545	−1 544c	53.27	12.85	23.13	26.46	1.1917	−0.0012	60.9	35 579	15 479	
29 550	−1 549c	48.96	15.22	21.27	26.16	1.2613	−0.0009	54.4	36 582	16 480	
30 555	−1 554c	44.65	17.27	19.41	25.98	1.3372	−0.0007	48.3	36 584	16 481	
32 560	−1 560c	36.33	20.2	15.8	25.64	1.5064	−0.0005	38.0	37 589	16 483	
32 561	0 405	48.43	20.15	15.85	25.64	1.3665	−0.1081	38.1	37 589	16 483	Rm
32 562	6 435	47.91	23.73	8.75	25.29	1.4458	−0.2528	20.2	42 610	17 486	
32 563	10 450	47.35	29.71	−4.36	30.03	1.5779	−0.5277	351.6	−1 496c	19 496	
33 565	12 460	46.56	32.29	−11.21	34.18	1.6439	−0.6765	340.8	−1 505c	21 505	
33 567	12 465	45.37	32.47	−11.73	34.52	1.666	−0.6942	340.1	−1 506c	21 506	
33 569	14 470	44.43	33.79	−17.12	37.88	1.711	−0.8209	333.1	−1 520c	24 520	
34 573	15 475	42.15	33.91	−19.9	39.33	1.755	−0.9078	329.5	−1 528c	25 528	Mm
36 580	16 480	38.02	33.2	−23.07	40.43	1.8237	−1.0424	325.2	−1 537c	27 537	
39 595	17 485	30.23	29.0	−27.46	39.94	1.9097	−1.3442	316.5	−1 548c	29 548	
−1 490c	18 490	16.89	10.68	−34.02	35.66	1.5831	−2.4491	287.4	11 459	33 565	min
−1 495c	19 495	18.22	9.46	−34.01	35.3	1.4699	−2.3016	285.5	12 462	33 566	
−1 500c	20 500	19.89	7.9	−33.73	34.64	1.3475	−2.1309	283.1	12 464	33 567	
−1 510c	22 510	24.45	3.68	−32.32	32.53	1.101	−1.7576	276.5	13 469	33 569	
−1 519c	23 520	27.36	1.11	−31.22	31.24	0.9912	−1.5765	272.0	14 471	34 570	Bm
−1 529c	25 530	34.4	−4.57	−28.36	28.73	0.8175	−1.2601	260.8	15 475	34 573	
−1 539c	27 540	42.5	−10.25	−24.94	26.97	0.7091	−1.0225	247.6	15 478	35 577	
−1 544c	28 545	46.72	−12.85	−23.13	26.46	0.6753	−0.9306	240.9	15 479	35 579	
−1 549c	29 550	51.03	−15.22	−21.27	26.16	0.6522	−0.8524	234.4	16 480	36 582	
−1 554c	30 555	55.34	−17.27	−19.41	25.98	0.6383	−0.7863	228.3	16 481	36 584	
−1 560c	32 560	63.66	−20.2	−15.8	25.64	0.6331	−0.6837	218.0	16 483	37 589	
380	770	88.59	0.0	0.0	0.01	0.9504	−0.4355	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for D50, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	32 564	51.21	−23.13	−12.01	26.07	0.5124	−0.5646	207.4	17 486	38 592	Cm
7 435	33 565	51.54	−26.37	−5.49	26.93	0.4526	−0.4365	191.7	18 490	46 634	
10 450	33 566	51.98	−29.72	2.1	29.79	0.3925	−0.2895	175.9	19 497	−1 497c	
12 460	33 567	52.53	−31.63	7.31	32.46	0.3621	−0.1907	166.9	21 506	−1 506c	
13 465	33 568	53.11	−32.33	9.67	33.74	0.3555	−0.1478	163.3	22 511	−1 511c	
14 470	34 570	54.07	−32.77	11.8	34.83	0.3581	−0.1117	160.1	23 519	−1 519c	
15 475	34 573	55.72	−32.85	13.81	35.64	0.3745	−0.0821	157.2	25 527	−1 527c	Gm
15 480	35 578	59.28	−32.7	14.98	35.97	0.4125	−0.0772	155.3	26 531	−1 531c	
17 485	37 587	64.0	−30.41	18.52	35.6	0.489	−0.0405	148.6	28 544	−1 544c	
18 490	44 620	77.97	−17.06	23.76	29.25	0.7454	−0.0251	125.6	32 561	−1 561c	max
19 495	−1 495c	82.96	−6.37	25.91	26.68	0.8874	−0.0176	103.8	33 568	12 463	
20 500	−1 500c	81.49	−4.96	25.81	26.29	0.9033	−0.0131	100.8	33 569	13 466	
22 510	−1 510c	77.37	−1.09	24.98	25.0	0.95	−0.0071	92.5	34 571	14 471	
23 520	−1 519c	74.67	1.31	24.24	24.28	0.9818	−0.0053	86.8	34 572	14 473	Ym
25 530	−1 529c	68.03	6.77	22.25	23.26	1.0637	−0.0029	73.0	35 575	15 477	
27 540	−1 539c	60.24	12.35	19.78	23.32	1.1692	−0.0015	58.0	35 579	16 480	
28 545	−1 544c	56.11	14.94	18.45	23.74	1.2304	−0.0011	50.9	36 581	16 481	
29 550	−1 549c	51.87	17.32	17.07	24.32	1.2983	−0.0009	44.5	36 583	16 483	
30 555	−1 554c	47.59	19.42	15.67	24.96	1.3724	−0.0007	38.8	37 585	16 484	
32 560	−1 560c	39.22	22.48	12.92	25.93	1.5375	−0.0005	29.8	38 590	17 486	
32 564	1 405	48.78	23.13	12.01	26.07	1.4385	−0.0836	27.4	38 592	17 486	Rm
33 565	7 435	48.45	26.37	5.49	26.93	1.5084	−0.2166	11.7	46 634	18 490	
33 566	10 450	48.01	29.72	−2.1	29.79	1.5832	−0.3738	355.9	−1 497c	19 497	
33 567	12 460	47.46	31.63	−7.31	32.46	1.6306	−0.4841	346.9	−1 506c	21 506	
33 568	13 465	46.88	32.33	−9.67	33.74	1.6538	−0.5362	343.3	−1 511c	22 511	
34 570	14 470	45.92	32.77	−11.8	34.83	1.6779	−0.5869	340.1	−1 519c	23 519	
34 573	15 475	44.27	32.85	−13.81	35.64	1.7062	−0.6419	337.2	−1 527c	25 527	Mm
35 578	15 480	40.71	32.7	−14.98	35.97	1.7673	−0.6979	335.3	−1 531c	26 531	
37 587	17 485	35.99	30.41	−18.52	35.6	1.809	−0.8444	328.6	−1 544c	28 544	
44 620	18 490	22.02	17.06	−23.76	29.25	1.739	−1.4092	305.6	−1 561c	32 561	min
−1 495c	19 495	17.03	6.37	−25.91	26.68	1.3382	−1.8515	283.8	12 463	33 568	
−1 500c	20 500	18.5	4.96	−25.81	26.29	1.2322	−1.7248	280.8	13 466	33 569	
−1 510c	22 510	22.62	1.09	−24.98	25.0	1.0125	−1.434	272.5	14 471	34 571	
−1 519c	23 520	25.32	−1.31	−24.24	24.28	0.9122	−1.2875	266.8	14 473	34 572	Bm
−1 529c	25 530	31.96	−6.77	−22.25	23.26	0.7523	−1.0261	253.0	15 477	35 575	
−1 539c	27 540	39.75	−12.35	−19.78	23.32	0.6535	−0.8276	238.0	16 480	35 579	
−1 544c	28 545	43.88	−14.94	−18.45	23.74	0.6237	−0.7504	230.9	16 481	36 581	
−1 549c	29 550	48.12	−17.32	−17.07	24.32	0.6041	−0.6846	224.5	16 483	36 583	
−1 554c	30 555	52.4	−19.42	−15.67	24.96	0.5934	−0.6289	218.8	16 484	37 585	
−1 560c	32 560	60.77	−22.48	−12.92	25.93	0.5942	−0.5425	209.8	17 486	38 590	
380	770	88.59	0.0	0.0	0.01	0.9642	−0.3299	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for P40, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	33 568	50.12	−25.11	−9.79	26.95	0.5083	−0.4542	201.3	17 488	38 594	Cm
7 435	33 568	50.37	−27.92	−4.14	28.22	0.455	−0.3411	188.4	18 493	54 674	
10 450	33 569	50.74	−30.4	1.4	30.43	0.4101	−0.2309	177.3	19 499	−1 499c	
12 460	34 570	51.2	−31.78	5.21	32.21	0.3884	−0.1569	170.6	21 507	−1 507c	
13 465	34 571	51.65	−32.25	6.97	33.0	0.3848	−0.1237	167.7	22 512	−1 512c	
14 470	34 572	52.42	−32.54	8.56	33.65	0.3884	−0.0953	165.2	23 519	−1 519c	
14 475	34 574	54.15	−32.7	9.01	33.92	0.4054	−0.0923	164.5	24 522	−1 522c	Gm
15 480	35 578	56.54	−32.56	10.77	34.3	0.4332	−0.0682	161.6	26 531	−1 531c	
17 485	37 585	60.26	−31.09	13.33	33.83	0.4932	−0.0374	156.7	28 543	−1 543c	
17 490	40 600	70.01	−26.08	15.85	30.52	0.6366	−0.0323	148.7	30 554	−1 554c	max
19 495	−1 495c	84.05	−4.59	20.45	20.95	0.9546	−0.0154	102.6	34 571	12 464	
20 500	−1 500c	82.78	−3.32	20.45	20.72	0.9691	−0.0116	99.2	34 571	13 467	
21 510	−1 509c	81.16	−1.71	20.3	20.37	0.9882	−0.0086	94.8	34 572	13 469	
24 520	−1 520c	73.89	5.05	18.85	19.52	1.0777	−0.0035	74.9	35 575	15 476	Ym
26 530	−1 530c	67.28	10.44	17.27	20.19	1.1646	−0.0019	58.8	35 578	16 480	
27 540	−1 539c	63.58	13.15	16.36	20.99	1.2161	−0.0014	51.1	36 580	16 481	
29 545	−1 545c	55.69	18.2	14.36	23.19	1.3362	−0.0008	38.2	36 584	16 484	
29 550	−1 549c	55.69	18.2	14.36	23.19	1.3362	−0.0008	38.2	36 584	16 484	
31 555	−1 555c	47.4	22.3	12.23	25.44	1.4798	−0.0005	28.7	37 588	17 486	
32 560	−1 560c	43.22	23.82	11.16	26.31	1.5605	−0.0005	25.1	38 591	17 487	
33 568	0 405	49.87	25.11	9.8	26.95	1.5129	−0.0622	21.3	38 594	17 488	Rm
33 568	7 435	49.62	27.92	4.14	28.22	1.5719	−0.1751	8.4	54 674	18 493	
33 569	10 450	49.25	30.4	−1.4	30.43	1.6265	−0.2873	357.3	−1 499c	19 499	
34 570	12 460	48.79	31.78	−5.21	32.21	1.6606	−0.3656	350.6	−1 507c	21 507	
34 571	13 465	48.34	32.25	−6.97	33.0	1.6765	−0.403	347.7	−1 512c	22 512	
34 572	14 470	47.57	32.54	−8.56	33.65	1.6934	−0.4388	345.2	−1 519c	23 519	
34 574	14 475	45.84	32.7	−9.01	33.92	1.7225	−0.4553	344.5	−1 522c	24 522	Mm
35 578	15 480	43.45	32.56	−10.77	34.3	1.7587	−0.5066	341.6	−1 531c	26 531	
37 585	17 485	39.73	31.09	−13.33	33.83	1.7918	−0.5943	336.7	−1 543c	28 543	
40 600	17 490	29.98	26.08	−15.85	30.52	1.8794	−0.7875	328.7	−1 554c	30 554	min
−1 495c	19 495	15.94	4.59	−20.44	20.95	1.2972	−1.5411	282.6	12 464	34 571	
−1 500c	20 500	17.21	3.32	−20.45	20.72	1.2023	−1.447	279.2	13 467	34 571	
−1 509c	21 510	18.83	1.71	−20.3	20.37	1.1002	−1.3368	274.8	13 469	34 572	
−1 520c	24 520	26.1	−5.05	−18.85	19.52	0.8155	−0.9812	254.9	15 476	35 575	Bm
−1 530c	26 530	32.71	−10.44	−17.27	20.19	0.6899	−0.7867	238.8	16 480	35 578	
−1 539c	27 540	36.41	−13.15	−16.36	20.99	0.648	−0.7081	231.1	16 481	36 580	
−1 545c	29 545	44.3	−18.2	−14.36	23.19	0.5983	−0.5828	218.2	16 484	36 584	
−1 549c	29 550	44.3	−18.2	−14.36	23.19	0.5983	−0.5828	218.2	16 484	36 584	
−1 555c	31 555	52.59	−22.3	−12.23	25.44	0.5852	−0.4914	208.7	17 486	37 588	
−1 560c	32 560	56.77	−23.82	−11.16	26.31	0.5896	−0.4553	205.1	17 487	38 591	
380	770	88.59	0.0	0.0	0.01	1.0093	−0.2587	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for A00, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	34 574	48.43	−28.75	−5.6	29.29	0.5048	−0.2581	191.0	18 494	39 599	Cm
6 435	34 574	48.59	−29.61	−3.91	29.87	0.4891	−0.2227	187.5	19 496	42 611	
9 450	34 574	48.83	−30.82	−1.31	30.85	0.4673	−0.1692	182.4	20 501	−1 501c	
12 460	35 575	49.01	−31.95	1.74	32.0	0.4465	−0.1066	176.8	21 508	−1 508c	
13 465	35 575	49.25	−32.19	2.74	32.31	0.4448	−0.0866	175.1	22 512	−1 512c	
13 470	35 576	49.84	−32.22	2.82	32.34	0.452	−0.0856	174.9	22 513	−1 513c	
14 475	35 577	50.59	−32.36	3.77	32.58	0.4587	−0.0677	173.3	23 519	−1 519c	Gm
16 480	35 579	51.55	−32.2	5.2	32.62	0.4738	−0.0414	170.8	26 532	−1 532c	
17 485	36 582	53.64	−31.67	5.96	32.23	0.5079	−0.0312	169.3	28 540	−1 540c	
18 490	37 588	57.57	−30.3	6.88	31.08	0.572	−0.0226	167.1	29 548	−1 548c	max
19 495	40 601	65.98	−25.09	8.37	26.46	0.718	−0.0153	161.5	31 559	−1 559c	
20 500	−1 500c	84.75	−0.56	11.29	11.3	1.0918	−0.0091	92.8	35 576	13 469	
21 510	−1 509c	83.55	0.75	11.31	11.34	1.1074	−0.0069	86.2	35 576	14 472	
24 520	−1 520c	77.79	6.62	10.83	12.7	1.1836	−0.003	58.5	35 579	16 480	Ym
26 530	−1 530c	72.2	11.66	10.15	15.46	1.26	−0.0017	41.0	36 582	16 484	
28 540	−1 540c	65.49	16.97	9.25	19.33	1.3576	−0.001	28.6	37 585	17 487	
28 545	−1 544c	65.49	16.97	9.25	19.33	1.3576	−0.001	28.6	37 585	17 487	
29 550	−1 549c	61.79	19.54	8.74	21.41	1.4148	−0.0007	24.1	37 586	17 489	
31 555	−1 555c	53.89	24.15	7.64	25.33	1.5466	−0.0005	17.5	38 590	18 491	
32 560	−1 560c	49.77	26.01	7.05	26.95	1.6212	−0.0004	15.1	38 593	18 492	
34 574	1 405	51.56	28.75	5.6	29.29	1.6561	−0.0335	11.0	39 599	18 494	Rm
34 574	6 435	51.4	29.61	3.91	29.87	1.6745	−0.0662	7.5	42 611	19 496	
34 574	9 450	51.16	30.82	1.31	30.85	1.7009	−0.1166	2.4	−1 501c	20 501	
35 575	12 460	50.98	31.95	−1.74	32.0	1.7252	−0.1766	356.8	−1 508c	21 508	
35 575	13 465	50.74	32.19	−2.74	32.31	1.733	−0.1963	355.1	−1 512c	22 512	
35 576	13 470	50.15	32.22	−2.82	32.34	1.7409	−0.1986	354.9	−1 513c	22 513	
35 577	14 475	49.4	32.36	−3.77	32.58	1.7536	−0.2187	353.3	−1 519c	23 519	Mm
35 579	16 480	48.44	32.2	−5.2	32.62	1.7633	−0.2497	350.8	−1 532c	26 532	
36 582	17 485	46.35	31.67	−5.96	32.23	1.7819	−0.2709	349.3	−1 540c	28 540	
37 588	18 490	42.42	30.3	−6.88	31.08	1.8128	−0.3046	347.1	−1 548c	29 548	min
40 601	19 495	34.01	25.09	−8.37	26.46	1.8363	−0.3886	341.5	−1 559c	31 559	
−1 500c	20 500	15.24	0.56	−11.29	11.3	1.1352	−0.8832	272.8	13 469	35 576	
−1 509c	21 510	16.44	−0.75	−11.31	11.34	1.0528	−0.8302	266.2	14 472	35 576	
−1 520c	24 520	22.2	−6.62	−10.83	12.7	0.8002	−0.6303	238.5	16 480	35 579	Bm
−1 530c	26 530	27.79	−11.66	−10.15	15.46	0.6787	−0.5076	221.0	16 484	36 582	
−1 540c	28 540	34.5	−16.97	−9.25	19.33	0.6065	−0.4105	208.6	17 487	37 585	
−1 544c	28 545	34.5	−16.97	−9.25	19.33	0.6065	−0.4105	208.6	17 487	37 585	
−1 549c	29 550	38.2	−19.54	−8.74	21.41	0.5867	−0.3712	204.1	17 489	37 586	
−1 555c	31 555	46.1	−24.15	−7.64	25.33	0.5745	−0.308	197.5	18 491	38 590	
−1 560c	32 560	50.22	−26.01	−7.05	26.95	0.5804	−0.2828	195.1	18 492	38 593	
380	770	88.58	0.0	0.0	0.01	1.0984	−0.1423	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for E00, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	32 564	50.87	−22.11	−14.47	26.43	0.5653	−0.6846	213.2	16 484	38 592	Cm
6 435	33 565	51.3	−25.82	−7.08	26.77	0.4967	−0.538	195.3	17 488	45 627	
10 450	33 566	51.78	−31.12	4.68	31.48	0.3988	−0.3094	171.4	19 498	−1 498c	
12 460	33 568	52.51	−33.26	10.46	34.86	0.3666	−0.2007	162.5	21 507	−1 507c	
13 465	33 569	53.28	−34.06	13.1	36.49	0.3606	−0.1541	158.9	22 514	−1 514c	
14 470	34 571	54.5	−34.5	15.52	37.83	0.367	−0.1152	155.7	24 522	−1 522c	
14 475	35 575	57.16	−34.67	16.58	38.43	0.3934	−0.1099	154.4	25 525	−1 525c	Gm
16 480	36 581	60.43	−33.93	20.61	39.7	0.4385	−0.0589	148.7	27 538	−1 538c	
17 485	39 595	67.95	−30.26	24.5	38.94	0.5546	−0.0393	140.9	29 549	−1 549c	
18 490	−1 490c	83.75	−9.91	31.5	33.02	0.8815	−0.0238	107.4	33 568	11 459	max
19 495	−1 495c	82.54	−8.75	31.54	32.73	0.8939	−0.0179	105.5	33 568	12 461	
19 500	−1 499c	82.54	−8.75	31.54	32.73	0.8939	−0.0179	105.5	33 568	12 461	
22 510	−1 510c	76.84	−3.16	30.19	30.35	0.9587	−0.0071	95.9	34 571	13 469	
24 520	−1 520c	70.99	2.12	28.12	28.2	1.0299	−0.0038	85.6	34 574	14 473	Ym
26 530	−1 530c	63.88	7.86	25.41	26.6	1.123	−0.0021	72.8	35 577	15 477	
28 540	−1 540c	56.0	13.32	22.33	26.0	1.2379	−0.0011	59.1	36 581	15 479	
29 545	−1 545c	51.9	15.77	20.71	26.03	1.3039	−0.0009	52.7	36 583	16 480	
29 550	−1 549c	51.9	15.77	20.71	26.03	1.3039	−0.0009	52.7	36 583	16 480	
30 555	−1 554c	47.77	17.95	19.07	26.19	1.3757	−0.0007	46.7	37 585	16 482	
32 560	−1 560c	39.54	21.24	15.79	26.47	1.5372	−0.0005	36.6	38 590	16 483	
32 564	1 405	49.12	22.11	14.47	26.42	1.45	−0.1052	33.2	38 592	16 484	Rm
33 565	6 435	48.69	25.82	7.08	26.77	1.5303	−0.2545	15.3	45 627	17 488	
33 566	10 450	48.21	31.12	−4.68	31.48	1.6455	−0.4972	351.4	−1 498c	19 498	
33 568	12 460	47.48	33.26	−10.46	34.86	1.7005	−0.6203	342.5	−1 507c	21 507	
33 569	13 465	46.71	34.06	−13.1	36.49	1.7291	−0.6804	338.9	−1 514c	22 514	
34 571	14 470	45.49	34.5	−15.52	37.83	1.7583	−0.7411	335.7	−1 522c	24 522	
35 575	14 475	42.83	34.67	−16.58	38.43	1.8096	−0.7872	334.4	−1 525c	25 525	Mm
36 581	16 480	39.56	33.93	−20.61	39.7	1.8575	−0.9209	328.7	−1 538c	27 538	
39 595	17 485	32.04	30.26	−24.5	38.94	1.9444	−1.1648	320.9	−1 549c	29 549	
−1 490c	18 490	16.24	9.91	−31.5	33.02	1.6105	−2.3392	287.4	11 459	33 568	min
−1 495c	19 495	17.45	8.75	−31.54	32.73	1.5016	−2.2074	285.5	12 461	33 568	
−1 499c	19 500	17.45	8.75	−31.54	32.73	1.5016	−2.2074	285.5	12 461	33 568	
−1 510c	22 510	23.15	3.16	−30.19	30.35	1.1369	−1.7039	275.9	13 469	34 571	
−1 520c	24 520	29.0	−2.12	−28.12	28.2	0.9266	−1.3696	265.6	14 473	34 574	Bm
−1 530c	26 530	36.11	−7.86	−25.41	26.6	0.7823	−1.1038	252.8	15 477	35 577	
−1 540c	28 540	43.99	−13.32	−22.33	26.0	0.6971	−0.9076	239.1	15 479	36 581	
−1 545c	29 545	48.09	−15.77	−20.71	26.03	0.6719	−0.8307	232.7	16 480	36 583	
−1 549c	29 550	48.09	−15.77	−20.71	26.03	0.6719	−0.8307	232.7	16 480	36 583	
−1 554c	30 555	52.22	−17.95	−19.07	26.19	0.6562	−0.7652	226.7	16 482	37 585	
−1 560c	32 560	60.45	−21.24	−15.79	26.47	0.6485	−0.6613	216.6	16 483	38 590	
380	770	88.59	0.0	0.0	0.01	1.0	−0.4	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for C00, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	32 562	51.1	−19.54	−17.3	26.1	0.5982	−0.8115	221.5	16 482	37 589	Cm
6 435	32 563	51.69	−23.59	−9.26	25.35	0.5242	−0.6521	201.4	17 486	42 612	
10 450	32 564	52.35	−30.25	5.27	30.71	0.4027	−0.3721	170.1	19 496	−1 496c	
11 460	33 566	53.63	−31.86	9.38	33.22	0.3865	−0.2979	163.5	20 501	−1 501c	
13 465	33 568	54.22	−33.89	15.83	37.41	0.3556	−0.1808	154.9	22 513	−1 513c	
14 470	34 570	55.77	−34.55	18.96	39.42	0.3611	−0.1328	151.2	24 522	−1 522c	
15 475	35 575	58.4	−34.72	22.12	41.17	0.3861	−0.0941	147.4	26 530	−1 530c	Gm
16 480	36 582	62.97	−33.68	25.74	42.4	0.4457	−0.064	142.6	28 540	−1 540c	
16 485	40 602	73.14	−28.46	30.55	41.75	0.5915	−0.0552	132.9	30 551	−1 551c	
18 490	−1 490c	82.68	−11.63	36.96	38.75	0.8399	−0.0257	107.4	33 566	11 459	max
19 495	−1 495c	81.3	−10.32	36.91	38.33	0.8536	−0.0188	105.6	33 567	12 462	
19 500	−1 499c	81.3	−10.32	36.91	38.33	0.8536	−0.0188	105.6	33 567	12 462	
21 510	−1 509c	77.66	−6.8	35.96	36.59	0.893	−0.0098	100.7	33 568	13 466	
24 520	−1 520c	69.63	0.45	32.65	32.65	0.9872	−0.0039	89.2	34 572	14 472	Ym
26 530	−1 530c	62.62	5.96	29.47	30.07	1.076	−0.0021	78.5	35 575	15 475	
28 540	−1 540c	54.54	11.4	25.72	28.14	1.1898	−0.0012	66.0	35 579	15 478	
28 545	−1 544c	54.54	11.4	25.72	28.14	1.1898	−0.0012	66.0	35 579	15 478	
29 550	−1 549c	50.25	13.89	23.71	27.48	1.2572	−0.0009	59.6	36 581	15 479	
31 555	−1 555c	41.49	17.97	19.59	26.59	1.4138	−0.0006	47.4	37 586	16 481	
31 560	−1 559c	41.49	17.97	19.59	26.59	1.4138	−0.0006	47.4	37 586	16 481	
32 562	1 405	48.89	19.54	17.3	26.1	1.3804	−0.1189	41.5	37 589	16 482	Rm
32 563	6 435	48.3	23.59	9.26	25.35	1.4692	−0.281	21.4	42 612	17 486	
32 564	10 450	47.64	30.25	−5.27	30.71	1.6157	−0.5836	350.1	−1 496c	19 496	
33 566	11 460	46.36	31.86	−9.38	33.22	1.668	−0.6752	343.5	−1 501c	20 501	
33 568	13 465	45.77	33.89	−15.83	37.41	1.7213	−0.8189	334.9	−1 513c	22 513	
34 570	14 470	44.22	34.55	−18.96	39.42	1.7621	−0.9018	331.2	−1 522c	24 522	
35 575	15 475	41.59	34.72	−22.12	41.17	1.8156	−1.0048	327.4	−1 530c	26 530	Mm
36 582	16 480	37.02	33.68	−25.74	42.4	1.8905	−1.1682	322.6	−1 540c	28 540	
40 602	16 485	26.85	28.46	−30.55	41.75	2.0405	−1.6104	312.9	−1 551c	30 551	
−1 490c	18 490	17.31	11.63	−36.96	38.75	1.6528	−2.6079	287.4	11 459	33 566	min
−1 495c	19 495	18.69	10.32	−36.91	38.33	1.5331	−2.4471	285.6	12 462	33 567	
−1 499c	19 500	18.69	10.32	−36.91	38.33	1.5331	−2.4471	285.6	12 462	33 567	
−1 509c	21 510	22.33	6.8	−35.96	36.59	1.2854	−2.083	280.7	13 466	33 568	
−1 520c	24 520	30.36	−0.45	−32.65	32.65	0.9657	−1.5483	269.2	14 472	34 572	Bm
−1 530c	26 530	37.37	−5.96	−29.47	30.07	0.821	−1.2615	258.5	15 475	35 575	
−1 540c	28 540	45.45	−11.4	−25.72	28.14	0.7297	−1.0389	246.0	15 478	35 579	
−1 544c	28 545	45.45	−11.4	−25.72	28.14	0.7297	−1.0389	246.0	15 478	35 579	
−1 549c	29 550	49.74	−13.89	−23.71	27.48	0.7014	−0.9496	239.6	15 479	36 581	
−1 555c	31 555	58.5	−17.97	−19.59	26.59	0.6734	−0.8079	227.4	16 481	37 586	
−1 559c	31 560	58.5	−17.97	−19.59	26.59	0.6734	−0.8079	227.4	16 481	37 586	
380	770	88.59	0.0	0.0	0.01	0.9807	−0.4729	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for P00, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	33 567	50.33	−24.12	−11.96	26.92	0.5413	−0.5619	206.3	17 486	38 594	Cm
7 435	33 567	50.61	−27.97	−4.18	28.28	0.4679	−0.407	188.5	18 491	−1 491c	
10 450	33 568	51.06	−31.16	2.97	31.31	0.4103	−0.2659	174.5	19 499	−1 499c	
12 460	34 570	51.65	−32.91	7.66	33.79	0.3834	−0.1758	166.8	21 507	−1 507c	
13 465	34 571	52.22	−33.48	9.79	34.88	0.3796	−0.1366	163.6	22 513	−1 513c	
13 470	34 572	53.56	−33.61	10.22	35.13	0.3931	−0.1332	163.0	23 515	−1 515c	
15 475	35 575	54.9	−33.94	13.6	36.57	0.4024	−0.0765	158.1	25 529	−1 529c	Gm
16 480	36 580	57.9	−33.49	15.58	36.94	0.4422	−0.055	155.0	27 537	−1 537c	
17 485	37 589	63.52	−31.34	18.18	36.23	0.5273	−0.0379	149.8	29 547	−1 547c	
18 490	45 625	78.78	−16.44	23.72	28.87	0.8119	−0.023	124.7	32 564	−1 564c	max
18 495	−1 494c	84.48	−7.59	25.57	26.67	0.9308	−0.0215	106.5	34 570	12 460	
20 500	−1 500c	82.05	−5.16	25.6	26.12	0.9577	−0.0121	101.3	34 571	13 465	
22 510	−1 510c	78.23	−1.35	24.85	24.88	1.0033	−0.0066	93.1	34 573	14 470	
24 520	−1 520c	72.8	3.67	23.34	23.62	1.0711	−0.0036	81.0	35 575	14 474	Ym
25 530	−1 529c	69.57	6.43	22.37	23.27	1.1131	−0.0027	73.9	35 577	15 476	
28 540	−1 540c	58.47	14.66	18.89	23.91	1.2713	−0.0011	52.1	36 582	16 481	
28 545	−1 544c	58.47	14.66	18.89	23.91	1.2713	−0.0011	52.1	36 582	16 481	
30 550	−1 550c	50.39	19.36	16.3	25.31	1.4049	−0.0007	40.0	37 586	16 483	
30 555	−1 554c	50.39	19.36	16.3	25.31	1.4049	−0.0007	40.0	37 586	16 483	
32 560	−1 560c	42.17	22.82	13.65	26.59	1.5618	−0.0005	30.8	38 591	17 485	
33 567	1 405	49.66	24.12	11.96	26.92	1.5064	−0.0833	26.3	38 594	17 486	Rm
33 567	7 435	49.38	27.97	4.18	28.28	1.5871	−0.2394	8.5	−1 491c	18 491	
33 568	10 450	48.93	31.16	−2.97	31.31	1.6576	−0.385	354.5	−1 499c	19 499	
34 570	12 460	48.34	32.91	−7.66	33.79	1.7014	−0.4827	346.8	−1 507c	21 507	
34 571	13 465	47.77	33.48	−9.79	34.88	1.7215	−0.5293	343.6	−1 513c	22 513	
34 572	13 470	46.43	33.61	−10.22	35.13	1.7445	−0.5445	343.0	−1 515c	23 515	
35 575	15 475	45.09	33.94	−13.6	36.57	1.7735	−0.6258	338.1	−1 529c	25 529	Mm
36 580	16 480	42.09	33.49	−15.58	36.94	1.8161	−0.6945	335.0	−1 537c	27 537	
37 589	17 485	36.47	31.34	−18.18	36.23	1.8799	−0.8229	329.8	−1 547c	29 547	
45 625	18 490	21.21	16.44	−23.72	28.87	1.796	−1.4429	304.7	−1 564c	32 564	min
−1 494c	18 495	15.51	7.59	−25.57	26.67	1.5099	−1.9729	286.5	12 460	34 570	
−1 500c	20 500	17.94	5.16	−25.6	26.12	1.3082	−1.7514	281.3	13 465	34 571	
−1 510c	22 510	21.76	1.35	−24.85	24.88	1.083	−1.4663	273.1	14 470	34 573	
−1 520c	24 520	27.19	−3.67	−23.34	23.62	0.8855	−1.1826	261.0	14 474	35 575	Bm
−1 529c	25 530	30.42	−6.43	−22.37	23.27	0.8091	−1.0595	253.9	15 476	35 577	
−1 540c	28 540	41.52	−14.66	−18.89	23.91	0.6675	−0.7792	232.1	16 481	36 582	
−1 544c	28 545	41.52	−14.66	−18.89	23.91	0.6675	−0.7792	232.1	16 481	36 582	
−1 550c	30 550	49.6	−19.36	−16.3	25.31	0.6302	−0.6529	220.0	16 483	37 586	
−1 554c	30 555	49.6	−19.36	−16.3	25.31	0.6302	−0.6529	220.0	16 483	37 586	
−1 560c	32 560	57.82	−22.82	−13.65	26.59	0.6259	−0.5603	210.8	17 485	38 591	
380	770	88.59	0.0	0.0	0.01	1.0206	−0.3242	0.0			

Ostwald optimal colours (o) of maximum (m) C_{AB} for Q00, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	32 562	51.28	−19.83	−16.97	26.1	0.5925	−0.8068	220.5	16 482	38 590	Cm
7 435	32 562	51.72	−26.08	−4.41	26.45	0.475	−0.5611	189.5	17 488	−1 488c	
10 450	32 564	52.44	−31.0	6.48	31.67	0.3881	−0.3521	168.1	19 497	−1 497c	
11 460	33 566	53.67	−32.55	10.42	34.18	0.3728	−0.2816	162.2	20 502	−1 502c	
12 465	33 568	54.66	−33.78	14.0	36.57	0.3611	−0.2196	157.4	21 508	−1 508c	
14 470	34 570	55.78	−35.1	19.49	40.15	0.3499	−0.1264	150.9	24 522	−1 522c	
15 475	35 575	58.38	−35.27	22.49	41.83	0.3751	−0.0905	147.4	26 530	−1 530c	Gm
16 480	36 582	62.99	−34.26	26.03	43.02	0.4354	−0.0625	142.7	27 539	−1 539c	
17 485	40 602	72.6	−28.13	31.61	42.31	0.5918	−0.0404	131.6	30 552	−1 552c	
17 490	−1 489c	84.1	−13.23	37.08	39.37	0.8219	−0.0349	109.6	33 565	11 455	max
18 495	−1 494c	83.02	−12.27	37.32	39.29	0.8314	−0.0262	108.2	33 565	11 458	
20 500	−1 500c	80.01	−9.39	36.91	38.09	0.8619	−0.0144	104.2	33 567	12 463	
21 510	−1 509c	77.94	−7.4	36.26	37.01	0.8843	−0.0105	101.5	33 568	13 465	
23 520	−1 519c	72.51	−2.36	34.09	34.17	0.9466	−0.0056	93.9	34 571	14 470	Ym
26 530	−1 530c	61.69	6.39	29.21	29.9	1.0829	−0.0022	77.6	35 576	15 475	
27 540	−1 539c	57.66	9.22	27.34	28.85	1.1393	−0.0016	71.3	35 578	15 477	
28 545	−1 544c	53.52	11.88	25.4	28.04	1.2014	−0.0012	64.9	36 580	15 478	
29 550	−1 549c	49.33	14.3	23.43	27.45	1.2693	−0.0009	58.5	36 582	15 479	
30 555	−1 554c	45.14	16.42	21.44	27.01	1.3431	−0.0007	52.5	36 584	16 480	
31 560	−1 559c	40.99	18.19	19.47	26.65	1.4231	−0.0006	46.9	37 587	16 481	
32 562	1 405	48.71	19.83	16.97	26.1	1.3864	−0.1273	40.5	38 590	16 482	Rm
32 562	7 435	48.27	26.08	4.41	26.45	1.5196	−0.3844	9.5	−1 488c	17 488	
32 564	10 450	47.55	31.0	−6.48	31.67	1.6311	−0.6121	348.1	−1 497c	19 497	
33 566	11 460	46.32	32.55	−10.42	34.18	1.682	−0.7007	342.2	−1 502c	20 502	
33 568	12 465	45.33	33.78	−14.0	36.57	1.7246	−0.7846	337.4	−1 508c	21 508	
34 570	14 470	44.21	35.1	−19.49	40.15	1.7734	−0.9166	330.9	−1 522c	24 522	
35 575	15 475	41.61	35.27	−22.49	41.83	1.827	−1.0163	327.4	−1 530c	26 530	Mm
36 582	16 480	37.0	34.26	−26.03	43.02	1.9052	−1.1793	322.7	−1 539c	27 539	
40 602	17 485	27.39	28.13	−31.61	42.31	2.0061	−1.6296	311.6	−1 552c	30 552	
−1 489c	17 490	15.89	13.23	−37.08	39.37	1.8117	−2.8086	289.6	11 455	33 565	min
−1 494c	18 495	16.97	12.27	−37.32	39.29	1.7025	−2.6742	288.2	11 458	33 565	
−1 500c	20 500	19.98	9.39	−36.91	38.09	1.4493	−2.3227	284.2	12 463	33 567	
−1 509c	21 510	22.05	7.4	−36.26	37.01	1.3149	−2.1206	281.5	13 465	33 568	
−1 519c	23 520	27.48	2.36	−34.09	34.17	1.0654	−1.7161	273.9	14 470	34 571	Bm
−1 530c	26 530	38.3	−6.39	−29.21	29.9	0.8124	−1.2384	257.6	15 475	35 576	
−1 539c	27 540	42.33	−9.22	−27.34	28.85	0.7613	−1.1216	251.3	15 477	35 578	
−1 544c	28 545	46.47	−11.88	−25.4	28.04	0.7235	−1.0224	244.9	15 478	36 580	
−1 549c	29 550	50.66	−14.3	−23.43	27.45	0.6969	−0.9383	238.5	15 479	36 582	
−1 554c	30 555	54.85	−16.42	−21.44	27.01	0.6798	−0.8668	232.5	16 480	36 584	
−1 559c	31 560	59.0	−18.19	−19.47	26.65	0.671	−0.8059	226.9	16 481	37 587	
380	770	88.59	0.0	0.0	0.01	0.9793	−0.4758	0.0			