

Ostwald optimal colours (o) of maximum (m) C _{AB,10} for D65, Y _{w,10} =100, Y _m =520_770															
id	λ ₁	id	λ ₂	Y ₁₀	A ₁₀	B ₁₀	C _{10AB,10}	a ₁₀	b ₁₀	h _{10ab,10}	i _d	λ _d	i _c	λ _c	Code
0	405	31	556	56.57	-21.89	-18.32	28.54	0.5611	-0.7532	219.9	15	476	37	585	Cm
6	435	31	557	57.42	-26.44	-8.79	27.86	0.4876	-0.5825	198.4	16	480	44	621	
10	450	31	559	57.53	-32.48	6.09	33.05	0.3834	-0.3234	169.3	18	491	-1	491c	
11	460	32	562	59.27	-33.9	10.52	35.5	0.3761	-0.2517	162.7	19	498	-1	498c	
12	465	33	565	60.92	-34.93	14.56	37.84	0.3747	-0.1903	157.3	21	506	-1	506c	
14	470	34	570	63.07	-35.18	20.67	40.8	0.3903	-0.1016	149.5	24	522	-1	522c	
15	475	35	579	68.64	-33.55	24.85	41.75	0.4593	-0.0672	143.4	26	533	-1	533c	Gm
16	480	41	606	81.94	-23.65	31.88	39.7	0.6594	-0.0401	126.5	30	550	-1	550c	
16	485	-1	484c	92.3	-10.45	36.33	37.8	0.8348	-0.0356	106.0	32	560	10	454	
18	490	-1	490c	89.06	-7.57	36.55	37.33	0.863	-0.0188	101.7	32	562	11	459	max
19	495	-1	495c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32	563	12	461	
19	500	-1	499c	87.05	-5.68	36.18	36.62	0.8828	-0.0136	98.9	32	563	12	461	
22	510	-1	510c	79.1	1.43	33.55	33.58	0.9662	-0.0051	87.5	33	566	13	466	
23	520	-1	519c	75.81	4.11	32.27	32.53	1.0024	-0.0036	82.7	33	568	13	468	Ym
26	530	-1	530c	64.17	12.31	27.48	30.11	1.14	-0.001	65.8	34	573	14	472	
27	540	-1	539c	59.9	14.81	25.68	29.65	1.1955	-0.0005	60.0	35	576	14	473	
28	545	-1	544c	55.54	17.09	23.83	29.32	1.2559	-0.0002	54.3	35	578	14	474	
29	550	-1	549c	51.12	19.09	21.94	29.08	1.3215	-0.0001	48.9	36	580	15	475	
31	555	-1	555c	42.37	21.98	18.19	28.53	1.4668	0.0	39.6	37	586	15	476	
32	560	10	451	40.04	32.52	-6.18	33.11	1.7605	-0.5839	349.2	-1	492c	18	492	
31	556	0	405	43.42	21.89	18.32	28.54	1.4522	-0.0074	39.9	37	585	15	476	Rm
31	557	6	435	42.57	26.44	8.79	27.86	1.5691	-0.2226	18.4	44	621	16	480	
31	559	10	450	42.46	32.48	-6.09	33.05	1.713	-0.5727	349.3	-1	491c	18	491	
32	562	11	460	40.72	33.9	-10.52	35.5	1.7806	-0.6878	342.7	-1	498c	19	498	
33	565	12	465	39.07	34.93	-14.56	37.84	1.8419	-0.8019	337.3	-1	506c	21	506	
34	570	14	470	36.92	35.18	-20.67	40.8	1.901	-0.9892	329.5	-1	522c	24	522	
35	579	15	475	31.35	33.55	-24.85	41.75	2.0184	-1.2221	323.4	-1	533c	26	533	Mm
41	606	16	480	18.05	23.65	-31.88	39.7	2.2587	-2.1959	306.5	-1	550c	30	550	
-1	484c	16	485	7.69	10.45	-36.33	37.8	2.306	-5.1484	286.0	10	454	32	560	
-1	490c	18	490	10.93	7.57	-36.55	37.33	1.6407	-3.7725	281.7	11	459	32	562	min
-1	495c	19	495	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12	461	32	563	
-1	499c	19	500	12.94	5.68	-36.18	36.62	1.3873	-3.2239	278.9	12	461	32	563	
-1	510c	22	510	20.89	-1.43	-33.55	33.58	0.8795	-2.035	267.5	13	466	33	566	
-1	519c	23	520	24.18	-4.12	-32.27	32.53	0.7777	-1.7639	262.7	13	468	33	568	Bm
-1	530c	26	530	35.82	-12.31	-27.48	30.11	0.6044	-1.1965	245.8	14	472	34	573	
-1	539c	27	540	40.09	-14.81	-25.68	29.65	0.5785	-1.0699	240.0	14	473	35	576	
-1	544c	28	545	44.45	-17.09	-23.83	29.32	0.5635	-0.9653	234.3	14	474	35	578	
-1	549c	29	550	48.87	-19.09	-21.94	29.08	0.5575	-0.8782	228.9	15	475	36	580	
-1	555c	31	555	57.62	-21.98	-18.19	28.53	0.5667	-0.745	219.6	15	476	37	586	
10	451	32	560	59.95	-32.52	6.18	33.11	0.4056	-0.3261	169.2	18	492	-1	492c	
380	770	100.0	0.0	0.0	0.0	0.01	0.9481	-0.4293	0.0						