

6

-6

TUB registration: 20201101-BEE0/BEE0L0NP.PDF/.PS
application for evaluation and measurement of display or print output

TUB material: code=rha4ta

6

-6



http://farbe.li.tu-berlin.de/BEE0/BEE0L0NP.PDF/.PS; only vector graphic VG; start output

N:

T

Y

M

C

O

V

L

C

M

see similar files: http://farbe.li.tu-berlin.de/BEE0/BEE0L0NP.PDF/.PS

technical information: http://farbe.li.tu-berlin.de or http://color.li.tu-berlin.de

V

-8

TUB-test chart BEE0; Additive colour mixture; spectral mixture to
optimal colour of Ostwald, ideal projector colours, colour mixture in colour television for D65

input: $rgb/cmy0/000k/n$

$R(\lambda)$ reflection factor; optimal colour:
device yellow Y_d $\lambda_d=570nm$

$R(\lambda)$ reflection factor; optimal colour:
device green G_d $\lambda_d=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device cyan-blue C_d $\lambda_d=489nm$

$R(\lambda)$ reflection factor; optimal colour:
device red R_d $\lambda_d=596nm$

$R(\lambda)$ reflection factor; optimal colour:
device white W_d

$R(\lambda)$ reflection factor; optimal colour:
device blue B_d $\lambda_d=463nm$

$R(\lambda)$ reflection factor; optimal colour:
device white W_d

$R(\lambda)$ reflection factor; optimal colour:
device green G_{wd} $\lambda_d=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device magenta-red M_d $\lambda_c=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device cyan-blue C_{nd} $\lambda_d=489nm$

$R(\lambda)$ reflection factor; optimal colour:
device blue B_{nd} $\lambda_d=463nm$

Wavelength ranges for
CIE standard illuminant D65
 $R_{max}(\lambda)=1,00, R_{min}(\lambda)=0,00$

$R(\lambda)$ reflection factor; optimal colour:
device yellow Y_{wd} $\lambda_d=570nm$

$R(\lambda)$ reflection factor; optimal colour:
device green G_{wd} $\lambda_d=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device cyan-blue C_{nd} $\lambda_d=489nm$

$R(\lambda)$ reflection factor; optimal colour:
device red R_{wd} $\lambda_d=596nm$

$R(\lambda)$ reflection factor; optimal colour:
device white W_{wd}

$R(\lambda)$ reflection factor; optimal colour:
device blue B_{wd} $\lambda_d=463nm$

Wavelength ranges for
CIE standard illuminant D65
 $R_{max}(\lambda)=1,00, R_{min}(\lambda)=0,00$

$R(\lambda)$ reflection factor; optimal colour:
device yellow Y_d $\lambda_d=570nm$

$R(\lambda)$ reflection factor; optimal colour:
device red R_d $\lambda_d=596nm$

$R(\lambda)$ reflection factor; optimal colour:
device green G_d $\lambda_d=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device magenta-red M_d $\lambda_c=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device cyan-blue C_{ad} $\lambda_d=489nm$

$R(\lambda)$ reflection factor; optimal colour:
device blue B_{ad} $\lambda_d=463nm$

Wavelength ranges for
CIE standard illuminant D65
 $R_{max}(\lambda)=1,00, R_{min}(\lambda)=0,00$

$R(\lambda)$ reflection factor; optimal colour:
device red R_{ad} $\lambda_d=596nm$

$R(\lambda)$ reflection factor; optimal colour:
device green G_{ad} $\lambda_d=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device magenta-red M_{ad} $\lambda_c=535nm$

$R(\lambda)$ reflection factor; optimal colour:
device cyan-blue C_{nd} $\lambda_d=489nm$

$R(\lambda)$ reflection factor; optimal colour:
device blue B_{nd} $\lambda_d=463nm$

$R(\lambda)$ reflection factor; optimal colour:
device red R_{nd} $\lambda_d=596nm$

Wavelength ranges for
CIE standard illuminant D65
 $R_{max}(\lambda)=1,00, R_{min}(\lambda)=0,00$

C

M

Y

O

L

V

-8

-6