



$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device green G_d $\lambda_d=535\text{nm}$




$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device cyan-blue C_d $\lambda_d=489\text{nm}$




BEE-70-7C

$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device yellow Y_d $\lambda_d=570\text{nm}$




BEE-70-7Y

$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device white W_d




BEE-70-7W

$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device blue B_d $\lambda_d=463\text{nm}$




BEE-70-7B

$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device red R_d $\lambda_d=596\text{nm}$



BEE-70-7R

$R_0(\lambda)=R(\lambda)/0,5$ reflection factor
device magenta-red M_d $\lambda_c=535\text{nm}$



BEE-70-7M

Contrast $C=2:1=R_{\text{max}}:R_{\text{min}}$

Wavelength ranges for

CIE standard illuminant D65

$R_{\text{max}}(\lambda)=0,667$, $R_{\text{min}}(\lambda)=0,333$

$R_0(\lambda)=R(\lambda)/0,500$