

Ostwald-Optimalfarben (o) von maximalem (m) $C_{AB,10}$ für P60, $Y_{w,10}=100$, $Y_m=520_770$

i_1, λ_1	i_2, λ_2	Y_{10}	A_{10}	B_{10}	$C_{AB,10}$	a_{10}	b_{10}	$h_{AB,10}$	i_d, λ_d	i_c, λ_c	Code
1 405	31 557	56.06	-22.77	-17.39	28.65	0.5647	-0.7263	217.3	15 477	37 587	Cm
7 435	31 559	56.56	-28.95	-4.15	29.25	0.459	-0.4895	188.1	16 483	-1 483c	
9 450	32 561	57.37	-32.01	3.34	32.18	0.4129	-0.3577	174.0	17 489	-1 489c	
12 460	32 563	58.05	-35.14	13.39	37.61	0.3655	-0.1852	159.1	21 505	-1 505c	
13 465	33 566	59.57	-35.64	16.63	39.33	0.3725	-0.1368	154.9	22 514	-1 514c	
14 470	34 571	62.58	-35.56	20.01	40.8	0.4027	-0.0962	150.6	24 524	-1 524c	
14 475	36 580	69.18	-34.58	22.75	41.4	0.4709	-0.0871	146.6	26 531	-1 531c	Gm
15 480	41 605	82.76	-25.44	30.04	39.37	0.6635	-0.053	130.2	30 550	-1 550c	
16 485	-1 484c	92.83	-10.41	35.45	36.95	0.8587	-0.0341	106.3	32 561	10 453	
18 490	-1 490c	89.72	-7.57	35.7	36.49	0.8865	-0.0181	101.9	32 563	11 458	max
19 495	-1 495c	87.78	-5.71	35.36	35.82	0.9058	-0.0131	99.1	32 564	12 461	
20 500	-1 500c	85.54	-3.58	34.77	34.96	0.9291	-0.0095	95.8	33 565	12 463	
21 510	-1 509c	82.98	-1.2	33.95	33.97	0.9563	-0.0068	92.0	33 566	12 464	
24 520	-1 520c	73.29	6.88	30.31	31.09	1.0648	-0.0023	77.2	34 571	13 469	Ym
26 530	-1 530c	65.52	12.31	27.19	29.85	1.1589	-0.0009	65.6	34 574	14 472	
28 540	-1 540c	57.09	17.17	23.73	29.3	1.2718	-0.0002	54.1	35 578	14 474	
29 545	-1 545c	52.78	19.22	21.95	29.18	1.3351	-0.0001	48.7	36 581	15 475	
30 550	-1 550c	48.45	20.93	20.16	29.06	1.4029	0.0	43.9	36 583	15 476	
31 555	-1 555c	44.14	22.26	18.36	28.86	1.4754	0.0	39.5	37 586	15 476	
31 560	8 442	45.29	29.83	1.68	29.88	1.6295	-0.3787	3.2	-1 485c	17 485	
31 557	1 405	43.93	22.77	17.39	28.65	1.4893	-0.02	37.3	37 587	15 477	Rm
31 559	7 435	43.43	28.95	4.15	29.25	1.6375	-0.3204	8.1	-1 483c	16 483	
32 561	9 450	42.62	32.01	-3.34	32.18	1.7219	-0.4945	354.0	-1 489c	17 489	
32 563	12 460	41.94	35.14	-13.39	37.61	1.8087	-0.7354	339.1	-1 505c	21 505	
33 566	13 465	40.42	35.64	-16.63	39.33	1.8527	-0.8274	334.9	-1 514c	22 514	
34 571	14 470	37.41	35.56	-20.01	40.8	1.9215	-0.951	330.6	-1 524c	24 524	
36 580	14 475	30.81	34.58	-22.75	41.4	2.0932	-1.1545	326.6	-1 531c	26 531	Mm
41 605	15 480	17.23	25.44	-30.04	39.37	2.4477	-2.1598	310.2	-1 550c	30 550	
-1 484c	16 485	7.16	10.41	-35.45	36.95	2.4246	-5.3649	286.3	10 453	32 561	
-1 490c	18 490	10.27	7.57	-35.7	36.49	1.7082	-3.8917	281.9	11 458	32 563	min
-1 495c	19 495	12.21	5.71	-35.36	35.82	1.4388	-3.3127	279.1	12 461	32 564	
-1 500c	20 500	14.45	3.57	-34.77	34.96	1.2186	-2.8226	275.8	12 463	33 565	
-1 509c	21 510	17.01	1.2	-33.95	33.97	1.0419	-2.4114	272.0	12 464	33 566	
-1 520c	24 520	26.7	-6.88	-30.31	31.09	0.7132	-1.5512	257.2	13 469	34 571	Bm
-1 530c	26 530	34.47	-12.31	-27.19	29.85	0.6137	-1.2049	245.6	14 472	34 574	
-1 540c	28 540	42.9	-17.18	-23.73	29.3	0.5705	-0.9693	234.1	14 474	35 578	
-1 545c	29 545	47.21	-19.22	-21.95	29.18	0.5638	-0.881	228.7	15 475	36 581	
-1 550c	30 550	51.54	-20.93	-20.16	29.06	0.5647	-0.8071	223.9	15 476	36 583	
-1 555c	31 555	55.85	-22.26	-18.36	28.86	0.5722	-0.7448	219.5	15 476	37 586	
8 442	31 560	54.7	-29.83	-1.68	29.88	0.4255	-0.4469	183.2	17 485	-1 485c	
380	770	99.99	0.0	0.0	0.01	0.9709	-0.416	0.0			