

Ostwald-Optimalfarben (o) von maximalem (m) $C_{AB,10}$ für D65, $Y_{w,10}=88,6$, $Y_m=520_770$

id	λ_1	id	λ_2	Y_{10}	A_{10}	B_{10}	$C_{10AB,10}$	θ_{10}	b_{10}	$h_{10ab,10}$	i_d	λ_c	i_c	λ_c	Code
0	405	31	556	50.11	-19.39	-16.23	25.29	0.5611	-0.7532	219.9	15	476	37	585	Cm
6	435	31	557	50.86	-23.42	-7.79	24.68	0.4876	-0.5825	198.4	16	480	44	621	
10	450	31	559	50.96	-28.77	5.39	29.28	0.3834	-0.3234	169.3	18	491	-1	491c	
11	460	32	562	52.51	-30.03	9.32	31.45	0.3761	-0.2517	162.7	19	498	-1	498c	
12	465	33	565	53.96	-30.94	12.89	33.52	0.3747	-0.1903	157.3	21	506	-1	506c	
14	470	34	570	55.87	-31.17	18.31	36.15	0.3903	-0.1016	149.5	24	522	-1	522c	
15	475	35	579	60.81	-29.72	22.02	36.99	0.4593	-0.0672	143.4	26	533	-1	533c	Gm
16	480	41	606	72.59	-20.95	28.25	35.17	0.6594	-0.0401	126.5	30	550	-1	550c	
16	485	-1	484c	81.76	-9.26	32.18	33.49	0.8348	-0.0356	106.0	32	560	10	454	
18	490	-1	490c	78.9	-6.71	32.38	33.07	0.863	-0.0188	101.7	32	562	11	459	max
19	495	-1	495c	77.11	-5.03	32.05	32.44	0.8828	-0.0136	98.9	32	563	12	461	
19	500	-1	499c	77.11	-5.03	32.05	32.44	0.8828	-0.0136	98.9	32	563	12	461	
22	510	-1	510c	70.07	1.26	29.72	29.75	0.9662	-0.0051	87.5	33	566	13	466	
23	520	-1	519c	67.16	3.64	28.59	28.82	1.0024	-0.0036	82.7	33	568	13	468	Ym
26	530	-1	530c	56.85	10.9	24.34	26.68	1.14	-0.001	65.8	34	573	14	472	
27	540	-1	539c	53.07	13.12	22.75	26.26	1.1955	-0.0005	60.0	35	576	14	473	
28	545	-1	544c	49.2	15.14	21.11	25.98	1.2559	-0.0002	54.3	35	578	14	474	
29	550	-1	549c	45.28	16.91	19.43	25.76	1.3215	-0.0001	48.9	36	580	15	475	
31	555	-1	555c	37.53	19.47	16.11	25.27	1.4668	0.0	39.6	37	586	15	476	
32	560	10	451	35.47	28.81	-5.48	29.33	1.7605	-0.5839	349.2	-1	492c	18	492	
31	556	0	405	49.88	19.39	16.23	25.29	1.3369	-0.1039	39.9	37	585	15	476	Rm
31	557	6	435	49.13	23.42	7.79	24.68	1.4249	-0.2706	18.4	44	621	16	480	
31	559	10	450	49.03	28.77	-5.39	29.28	1.535	-0.5393	349.3	-1	491c	18	491	
32	562	11	460	47.48	30.03	-9.32	31.45	1.5806	-0.6257	342.7	-1	498c	19	498	
33	565	12	465	46.03	30.94	-12.89	33.52	1.6203	-0.7095	337.3	-1	506c	21	506	
34	570	14	470	44.12	31.16	-18.31	36.15	1.6546	-0.8444	329.5	-1	522c	24	522	
35	579	15	475	39.18	29.72	-22.02	36.99	1.7067	-0.9913	323.4	-1	533c	26	533	Mm
41	606	16	480	27.4	20.95	-28.25	35.17	1.713	-1.4603	306.5	-1	550c	30	550	
-1	484c	16	485	18.23	9.26	-32.18	33.49	1.4561	-2.1949	286.0	10	454	32	560	
-1	490c	18	490	21.09	6.7	-32.38	33.07	1.2661	-1.9644	281.7	11	459	32	562	min
-1	495c	19	495	22.88	5.03	-32.05	32.44	1.1683	-1.8303	278.9	12	461	32	563	
-1	499c	19	500	22.88	5.03	-32.05	32.44	1.1683	-1.8303	278.9	12	461	32	563	
-1	510c	22	510	29.92	-1.26	-29.72	29.75	0.9057	-1.4227	267.5	13	466	33	566	
-1	519c	23	520	32.83	-3.64	-28.59	28.82	0.8369	-1.3001	262.7	13	468	33	568	Bm
-1	530c	26	530	43.14	-10.9	-24.34	26.68	0.6953	-0.9936	245.8	14	472	34	573	
-1	539c	27	540	46.92	-13.12	-22.75	26.26	0.6683	-0.9141	240.0	14	473	35	576	
-1	544c	28	545	50.79	-15.14	-21.11	25.98	0.6499	-0.8449	234.3	14	474	35	578	
-1	549c	29	550	54.71	-16.91	-19.43	25.76	0.639	-0.7846	228.9	15	475	36	580	
-1	555c	31	555	62.46	-19.47	-16.11	25.27	0.6363	-0.6873	219.6	15	476	37	586	
10	451	32	560	64.52	-28.81	5.48	29.33	0.5015	-0.3443	169.2	18	492	-1	492c	
	380		770	88.59	0.0	0.0	0.01	0.9481	-0.4293	0.0					