

$\log [(\Delta Y/Y) / (\Delta Y/Y)_u]$

IECsRGBu6 relative

Normfarbwertempfindlichkeit

$Y_{nc} = L^*_{wRGBnc} = 100, 52, 87, 31$

$S_r/S_{ru} = (\Delta Y/Y) / (\Delta Y/Y)_u$

2 100

$T^*_{IECsRGBu6} = 50 (Y/Y_u)^{1/2,4} \quad (Y_u = 18, Y_{nc}/100 < Y \leq Y_{nc})$

$\log[(dY/Y)/(dY/Y)_u] = - (1/2,4) \log(Y/Y_u)$

1 10

$(dY/Y)_{90}/(dY/Y)_u = 0,51, \gamma = 2,4, 1/\gamma = 1/2,4 = 0,41$

$(dY/Y)_{18}/(dY/Y)_u = 1,00, S_n = 50,00, D_n = -0,00$

$(dY/Y)_{3,6}/(dY/Y)_u = 1,95, Y_u = 18, dY_u = 4,80$

Anwendungsbereich

0 1

$\log[(dY/Y)/(dY/Y)_u] = 0, m_u = -0,41$

$T^*_u = 50, dY_u = 4,80, dY_u/Y_u = 0,2666$

0,1

1

10

100

$Y_u = 18$

Y

-1

-1

0

1

2

log(Y)

$Y_N = 3,6$

$Y_W = 90$