

Ostwald optimal colours (o) of maximum (m) $C_{AB,10}$ for D65, $Y_{w,10}=100$, $Y_m=520_770$															
i_1, λ_1	i_2, λ_2	X_{10}	Y_{10}	Z_{10}	x_{10}	y_{10}	z_{10}	$h_{xy,10}$	i_d, λ_d	i_c, λ_c	Code				
0	405	31	556	31.74	56.57	106.53	0.1629	0.2903	0.5467	195.0	15	476	37	585	Cm
6	435	31	557	28.0	57.42	83.63	0.1656	0.3396	0.4947	176.6	16	480	44	621	
10	450	31	559	22.06	57.53	46.52	0.1749	0.4561	0.3689	137.9	18	491	-1	491c	
11	460	32	562	22.29	59.27	37.3	0.1875	0.4986	0.3137	126.9	19	498	-1	498c	
12	465	33	565	22.82	60.92	28.98	0.2025	0.5403	0.2571	117.9	21	506	-1	506c	
14	470	34	570	24.62	63.07	16.02	0.2373	0.6081	0.1544	105.3	24	522	-1	522c	
15	475	35	579	31.53	68.64	11.53	0.2822	0.6144	0.1032	96.3	26	533	-1	533c	Gm
16	480	41	606	54.03	81.94	8.23	0.3746	0.5682	0.0571	75.5	30	550	-1	550c	
16	485	-1	484c	77.05	92.3	8.23	0.4339	0.5197	0.0463	57.5	32	560	10	454	
18	490	-1	490c	76.87	89.06	4.2	0.4518	0.5234	0.0247	54.3	32	562	11	459	max
19	495	-1	495c	76.85	87.05	2.97	0.4605	0.5216	0.0178	52.4	32	563	12	461	
19	500	-1	499c	76.85	87.05	2.97	0.4605	0.5216	0.0178	52.4	32	563	12	461	
22	510	-1	510c	76.43	79.1	1.01	0.4882	0.5052	0.0064	44.9	33	566	13	466	
23	520	-1	519c	76.0	75.81	0.68	0.4983	0.4971	0.0045	41.9	33	568	13	468	Ym
26	530	-1	530c	73.15	64.17	0.16	0.532	0.4667	0.0012	31.8	34	573	14	472	
27	540	-1	539c	71.61	59.9	0.08	0.5441	0.4551	0.0006	28.3	35	576	14	473	
28	545	-1	544c	69.75	55.54	0.04	0.5565	0.4431	0.0003	24.7	35	578	14	474	
29	550	-1	549c	67.56	51.12	0.01	0.5691	0.4306	0.0001	21.3	36	580	15	475	
31	555	-1	555c	62.15	42.37	0.0	0.5946	0.4053	0.0	14.8	37	586	15	476	
32	560	10	451	70.49	40.04	58.45	0.4171	0.2369	0.3458	317.7	-1	492c	18	492	
31	556	0	405	63.06	43.42	0.8	0.5877	0.4047	0.0074	15.0	37	585	15	476	Rm
31	557	6	435	66.81	42.57	23.7	0.5019	0.3199	0.178	356.6	44	621	16	480	
31	559	10	450	72.75	42.46	60.8	0.4132	0.2412	0.3454	317.9	-1	491c	18	491	
32	562	11	460	72.51	40.72	70.03	0.3956	0.2222	0.3821	307.0	-1	498c	19	498	
33	565	12	465	71.98	39.07	78.34	0.38	0.2063	0.4136	298.0	-1	506c	21	506	
34	570	14	470	70.19	36.92	91.31	0.3537	0.186	0.4601	285.4	-1	522c	24	522	
35	579	15	475	63.28	31.35	95.79	0.3323	0.1646	0.503	276.3	-1	533c	26	533	Mm
41	606	16	480	40.77	18.05	99.09	0.2581	0.1143	0.6275	255.6	-1	550c	30	550	
-1	484c	16	485	17.75	7.69	99.09	0.1425	0.0618	0.7956	237.5	10	454	32	560	
-1	490c	18	490	17.94	10.93	103.13	0.1359	0.0828	0.7812	234.3	11	459	32	562	min
-1	495c	19	495	17.96	12.94	104.35	0.1327	0.0957	0.7714	232.4	12	461	32	563	
-1	499c	19	500	17.96	12.94	104.35	0.1327	0.0957	0.7714	232.4	12	461	32	563	
-1	510c	22	510	18.38	20.89	106.32	0.1262	0.1435	0.7302	224.9	13	466	33	566	
-1	519c	23	520	18.8	24.18	106.64	0.1256	0.1616	0.7126	222.0	13	468	33	568	Bm
-1	530c	26	530	21.65	35.82	107.16	0.1315	0.2175	0.6508	211.8	14	472	34	573	
-1	539c	27	540	23.19	40.09	107.24	0.136	0.2351	0.6288	208.3	14	473	35	576	
-1	544c	28	545	25.05	44.45	107.29	0.1417	0.2514	0.6068	204.8	14	474	35	578	
-1	549c	29	550	27.25	48.87	107.32	0.1485	0.2664	0.585	201.3	15	475	36	580	
-1	555c	31	555	32.65	57.62	107.33	0.1652	0.2916	0.5431	194.8	15	476	37	586	
10	451	32	560	24.31	59.95	48.88	0.1826	0.4502	0.367	137.6	18	492	-1	492c	
380	770	94.81	100.0	107.33	0.3137	0.3309	0.3552	0.0							