

Ostwald optimal colours (o) of maximum (m) C_{AB} for D65, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	Y	A	B	C _{AB}	a	b	h _{AB}	i _d , λ _d	i _c , λ _c	Code
0 405	32 561	57.55	−22.49	−17.69	28.62	0.5596	−0.743	218.1	16 483	37 589	Cm
7 435	32 562	58.04	−27.99	−6.64	28.77	0.4682	−0.55	193.3	17 488	−1 488c	
9 450	32 563	58.99	−31.59	1.12	31.61	0.4148	−0.4165	177.9	18 493	−1 493c	
11 460	33 565	60.01	−34.9	9.17	36.09	0.3687	−0.2826	165.2	20 501	−1 501c	
13 465	33 567	60.53	−37.02	15.95	40.31	0.3387	−0.172	156.6	22 512	−1 512c	
14 470	33 569	62.02	−37.72	19.11	42.28	0.3422	−0.1274	153.1	24 520	−1 520c	
15 475	34 573	64.56	−37.86	22.22	43.9	0.364	−0.0913	149.5	25 528	−1 528c	Gm
16 480	36 580	69.17	−37.06	25.75	45.13	0.4146	−0.0632	145.2	27 537	−1 537c	
17 485	39 595	77.87	−32.37	30.66	44.58	0.5347	−0.0418	136.5	29 548	−1 548c	
18 490	−1 490c	92.76	−11.93	37.97	39.8	0.8218	−0.0261	107.4	33 565	11 459	max
18 495	−1 494c	92.76	−11.93	37.97	39.8	0.8218	−0.0261	107.4	33 565	11 459	
20 500	−1 500c	89.41	−8.81	37.65	38.66	0.8518	−0.0144	103.1	33 567	12 464	
21 510	−1 509c	87.1	−6.65	37.02	37.61	0.874	−0.0105	100.1	33 568	13 467	
23 520	−1 519c	81.07	−1.24	34.85	34.87	0.935	−0.0056	92.0	34 570	14 471	Ym
25 530	−1 529c	73.22	5.1	31.66	32.07	1.0201	−0.0031	80.8	34 573	15 475	
28 540	−1 540c	59.46	14.34	25.82	29.54	1.1917	−0.0012	60.9	35 579	15 479	
29 545	−1 545c	54.65	16.98	23.75	29.2	1.2613	−0.0009	54.4	36 582	16 480	
30 550	−1 550c	49.84	19.28	21.67	29.0	1.3372	−0.0007	48.3	36 584	16 481	
31 555	−1 555c	45.12	21.14	19.62	28.85	1.419	−0.0006	42.8	37 586	16 482	
31 560	−1 559c	45.12	21.14	19.62	28.85	1.419	−0.0006	42.8	37 586	16 482	
32 561	0 405	41.32	22.49	17.69	28.62	1.4947	−0.0072	38.1	37 589	16 483	Rm
32 562	7 435	40.83	27.99	6.64	28.77	1.6359	−0.2728	13.3	−1 488c	17 488	
32 563	9 450	39.89	31.59	−1.12	31.61	1.7425	−0.4636	357.9	−1 493c	18 493	
33 565	11 460	38.86	34.9	−9.17	36.09	1.8485	−0.6716	345.2	−1 501c	20 501	
33 567	13 465	38.35	37.02	−15.95	40.31	1.9158	−0.8515	336.6	−1 512c	22 512	
33 569	14 470	36.85	37.72	−19.11	42.28	1.9738	−0.9541	333.1	−1 520c	24 520	
34 573	15 475	34.31	37.86	−22.22	43.9	2.0536	−1.083	329.5	−1 528c	25 528	Mm
36 580	16 480	29.7	37.06	−25.75	45.13	2.1981	−1.3025	325.2	−1 537c	27 537	
39 595	17 485	21.0	32.37	−30.66	44.58	2.4913	−1.895	316.5	−1 548c	29 548	
−1 490c	18 490	6.12	11.93	−37.97	39.8	2.899	−6.6372	287.4	11 459	33 565	min
−1 494c	18 495	6.12	11.93	−37.97	39.8	2.899	−6.6372	287.4	11 459	33 565	
−1 500c	20 500	9.47	8.81	−37.65	38.66	1.8814	−4.4106	283.1	12 464	33 567	
−1 509c	21 510	11.77	6.65	−37.02	37.61	1.5159	−3.5796	280.1	13 467	33 568	
−1 519c	23 520	17.8	1.24	−34.85	34.87	1.0204	−2.3925	272.0	14 471	34 570	Bm
−1 529c	25 530	25.66	−5.1	−31.66	32.07	0.7516	−1.6693	260.8	15 475	34 573	
−1 540c	28 540	39.42	−14.34	−25.82	29.54	0.5865	−1.0906	240.9	15 479	35 579	
−1 545c	29 545	44.23	−16.98	−23.75	29.2	0.5663	−0.9725	234.4	16 480	36 582	
−1 550c	30 550	49.04	−19.28	−21.67	29.0	0.5572	−0.8774	228.3	16 481	36 584	
−1 555c	31 555	53.75	−21.14	−19.62	28.85	0.557	−0.8006	222.8	16 482	37 586	
−1 559c	31 560	53.75	−21.14	−19.62	28.85	0.557	−0.8006	222.8	16 482	37 586	
380	770	98.88	0.0	0.0	0.01	0.9504	−0.4355	0.0			