

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P60, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	32 563	80.6	−69.04	−32.83	76.45	0.1809	−0.1017	205.4	16 483	38 590	Cm
6 435	32 563	80.9	−85.01	−17.38	86.77	0.1727	−0.0938	191.5	17 487	44 621	
10 450	33 565	81.24	−110.59	13.51	111.41	0.1596	−0.0781	173.0	19 497	−1 497c	
11 460	33 566	81.91	−114.9	24.29	117.44	0.1578	−0.0727	168.0	20 502	−1 502c	
13 465	33 568	82.21	−122.74	45.93	131.05	0.154	−0.0619	159.4	22 513	−1 513c	
14 470	34 570	83.01	−122.36	57.87	135.35	0.1547	−0.0561	154.6	24 521	−1 521c	
15 475	34 574	84.33	−117.73	70.24	137.09	0.1578	−0.0504	149.1	25 529	−1 529c	Gm
15 480	36 580	86.98	−106.76	74.78	130.35	0.1647	−0.0492	144.9	27 535	−1 535c	
17 485	39 595	90.78	−80.88	99.33	128.1	0.1788	−0.0391	129.1	29 549	−1 549c	
18 490	−1 490c	97.72	−21.98	119.18	121.19	0.2072	−0.0333	100.4	33 566	11 459	max
19 495	−1 495c	97.14	−19.56	125.55	127.06	0.2082	−0.0302	98.8	33 567	12 461	
20 500	−1 500c	96.4	−16.41	131.28	132.3	0.2095	−0.0273	97.1	33 568	12 464	
22 510	−1 510c	94.31	−7.64	140.4	140.61	0.2134	−0.0222	93.1	34 570	13 469	
24 520	−1 520c	91.27	4.18	144.83	144.89	0.2189	−0.0181	88.3	34 572	14 473	Ym
25 530	−1 529c	89.41	10.85	145.41	145.81	0.2221	−0.0163	85.7	34 574	15 475	
27 540	−1 539c	85.1	25.03	142.59	144.77	0.2294	−0.0133	80.0	35 578	15 478	
29 545	−1 545c	80.08	39.56	136.03	141.66	0.2376	−0.011	73.7	36 582	16 480	
29 550	−1 549c	80.08	39.56	136.03	141.66	0.2376	−0.011	73.7	36 582	16 480	
30 555	−1 554c	77.33	46.69	131.81	139.84	0.2421	−0.0103	70.4	36 584	16 481	
32 560	−1 560c	71.36	60.13	122.12	136.13	0.2515	−0.0093	63.7	37 589	16 483	
32 563	0 405	71.04	61.19	108.28	124.37	0.2523	−0.0235	60.5	38 590	16 483	Rm
32 563	6 435	70.67	71.54	29.52	77.39	0.2584	−0.0682	22.4	44 621	17 487	
33 565	10 450	70.24	85.56	−14.39	86.76	0.2668	−0.0932	350.4	−1 497c	19 497	
33 566	11 460	69.38	89.91	−23.58	92.95	0.2699	−0.0986	345.3	−1 502c	20 502	
33 568	13 465	68.98	94.51	−36.41	101.28	0.2729	−0.1061	338.9	−1 513c	22 513	
34 570	14 470	67.89	97.55	−42.59	106.45	0.2754	−0.11	336.4	−1 521c	24 521	
34 574	15 475	65.98	101.03	−49.17	112.36	0.2789	−0.1145	334.0	−1 529c	25 529	Mm
36 580	15 480	61.69	107.7	−56.56	121.65	0.2867	−0.1209	332.2	−1 535c	27 535	
39 595	17 485	54.03	111.06	−74.04	133.48	0.2967	−0.1371	326.3	−1 549c	29 549	
−1 490c	18 490	28.86	88.41	−118.79	148.08	0.3162	−0.2156	306.6	11 459	33 566	min
−1 495c	19 495	32.32	73.79	−113.85	135.67	0.2938	−0.2012	302.9	12 461	33 567	
−1 500c	20 500	36.05	57.8	−108.2	122.68	0.2728	−0.1875	298.1	12 464	33 568	
−1 510c	22 510	44.26	23.08	−95.07	97.84	0.2362	−0.1628	283.6	13 469	34 570	
−1 520c	24 520	52.87	−10.61	−80.73	81.42	0.2091	−0.1428	262.5	14 473	34 572	Bm
−1 529c	25 530	57.04	−25.1	−73.7	77.86	0.1996	−0.1347	251.1	15 475	34 574	
−1 539c	27 540	64.8	−47.72	−60.51	77.07	0.1872	−0.1219	231.7	15 478	35 578	
−1 545c	29 545	71.68	−61.73	−48.74	78.66	0.1814	−0.1124	218.2	16 480	36 582	
−1 549c	29 550	71.68	−61.73	−48.74	78.66	0.1814	−0.1124	218.2	16 480	36 582	
−1 554c	30 555	74.78	−65.73	−43.42	78.78	0.1804	−0.1086	213.4	16 481	36 584	
−1 560c	32 560	80.34	−68.41	−33.85	76.33	0.1811	−0.1023	206.3	16 483	37 589	
380	770	100.0	0.0	0.0	0.0	0.2169	−0.085	0.0			

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für P55, Y _w =100, Y _m =520_770													
i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code		
1 405	32 564	80.5	-72.98	-32.59	79.93	0.1791	-0.0988	204.0	16 484	38 591	Cm		
6 435	32 564	80.78	-86.91	-18.11	88.78	0.1719	-0.0915	191.7	17 488	43 619			
9 450	33 565	81.19	-103.91	3.69	103.98	0.1633	-0.0808	177.9	18 494	-1 494c			
11 460	33 567	81.69	-113.93	22.75	116.18	0.1584	-0.0714	168.7	20 502	-1 502c			
13 465	33 568	81.97	-121.2	44.2	129.01	0.1548	-0.0609	159.9	22 513	-1 513c			
14 470	34 570	82.7	-120.79	55.97	133.13	0.1555	-0.0554	155.1	24 521	-1 521c			
15 475	34 574	83.91	-116.62	68.14	135.07	0.1583	-0.0499	149.7	25 529	-1 529c	Gm		
16 480	36 580	86.0	-106.74	81.13	134.08	0.1644	-0.0444	142.7	27 537	-1 537c			
17 485	38 592	89.73	-84.48	96.17	128.01	0.1769	-0.039	131.2	29 547	-1 547c			
17 490	-1 489c	98.31	-21.18	110.91	112.91	0.2078	-0.0361	100.8	33 566	11 456	max		
19 495	-1 495c	97.31	-17.18	124.55	125.73	0.2095	-0.0299	97.8	33 567	12 462			
19 500	-1 499c	97.31	-17.18	124.55	125.73	0.2095	-0.0299	97.8	33 567	12 462			
21 510	-1 509c	95.7	-10.35	135.56	135.96	0.2125	-0.0244	94.3	33 569	13 467			
24 520	-1 520c	91.64	5.75	145.62	145.74	0.2199	-0.018	87.7	34 573	14 474	Ym		
26 530	-1 530c	87.83	19.09	145.42	146.67	0.2264	-0.0146	82.5	35 576	15 477			
27 540	-1 539c	85.63	26.14	143.5	145.86	0.2301	-0.0132	79.6	35 578	15 479			
28 545	-1 544c	83.25	33.29	140.65	144.54	0.2341	-0.012	76.6	36 580	16 480			
30 550	-1 550c	77.99	47.5	132.94	141.17	0.2427	-0.0102	70.3	37 585	16 482			
30 555	-1 554c	77.99	47.5	132.94	141.17	0.2427	-0.0102	70.3	37 585	16 482			
32 560	-1 560c	72.09	60.84	123.37	137.56	0.252	-0.0092	63.7	38 590	16 484			
32 564	1 405	71.16	63.39	100.63	118.93	0.2538	-0.0272	57.7	38 591	16 484	Rm		
32 564	6 435	70.82	72.23	31.03	78.62	0.2591	-0.0654	23.2	43 619	17 488			
33 565	9 450	70.31	82.25	-4.44	82.37	0.2652	-0.085	356.9	-1 494c	18 494			
33 567	11 460	69.66	88.69	-22.25	91.44	0.2694	-0.095	345.9	-1 502c	20 502			
33 568	13 465	69.3	92.92	-35.25	99.39	0.2721	-0.1024	339.2	-1 513c	22 513			
34 570	14 470	68.32	95.59	-41.34	104.15	0.2743	-0.1061	336.6	-1 521c	24 521			
34 574	15 475	66.61	98.69	-47.69	109.61	0.2774	-0.1102	334.2	-1 529c	25 529	Mm		
36 580	16 480	63.36	102.9	-55.81	117.06	0.2825	-0.1163	331.5	-1 537c	27 537			
38 592	17 485	56.37	107.59	-69.76	128.23	0.2921	-0.1288	327.0	-1 547c	29 547			
-1 489c	17 490	24.71	96.78	-124.34	157.56	0.3372	-0.2291	307.8	11 456	33 566		min	
-1 495c	19 495	31.36	69.01	-115.35	134.41	0.2907	-0.1994	300.8	12 462	33 567			
-1 499c	19 500	31.36	69.01	-115.35	134.41	0.2907	-0.1994	300.8	12 462	33 567			
-1 509c	21 510	39.09	35.95	-103.46	109.53	0.2501	-0.1726	289.1	13 467	33 569			
-1 520c	24 520	51.95	-15.41	-82.28	83.71	0.2057	-0.1406	259.3	14 474	34 573	Bm		
-1 530c	26 530	60.16	-42.21	-68.42	80.39	0.1892	-0.1256	238.3	15 477	35 576			
-1 539c	27 540	63.97	-52.33	-61.93	81.08	0.1842	-0.1197	229.8	15 479	35 578			
-1 544c	28 545	67.55	-60.24	-55.8	82.12	0.1808	-0.1146	222.8	16 480	36 580			
-1 550c	30 550	74.07	-69.84	-44.63	82.88	0.1781	-0.1063	212.5	16 482	37 585			
-1 554c	30 555	74.07	-69.84	-44.63	82.88	0.1781	-0.1063	212.5	16 482	37 585			
-1 560c	32 560	79.73	-72.07	-34.9	80.08	0.1792	-0.1	205.8	16 484	38 590			
380	770	100.0	0.0	0.0	0.0	0.2172	-0.0826	0.0					

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P50, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	33 565	80.38	−76.36	−33.29	83.3	0.1776	−0.0958	203.5	17 485	38 592	Cm
7 435	33 565	80.58	−93.88	−13.06	94.78	0.1686	−0.086	187.9	18 490	−1 490c	
9 450	33 566	80.98	−103.84	2.21	103.87	0.1636	−0.0787	178.7	19 495	−1 495c	
11 460	33 568	81.44	−112.86	20.91	114.78	0.1592	−0.0698	169.5	20 502	−1 502c	
12 465	33 569	81.88	−115.94	31.86	120.24	0.1578	−0.0647	164.6	21 507	−1 507c	
14 470	34 571	82.33	−118.97	53.7	130.53	0.1565	−0.0545	155.7	24 520	−1 520c	
15 475	34 574	83.42	−115.33	65.64	132.7	0.1591	−0.0492	150.3	25 528	−1 528c	Gm
16 480	35 579	85.29	−106.57	78.25	132.22	0.1645	−0.044	143.7	27 536	−1 536c	
16 485	37 589	89.01	−88.97	84.61	122.78	0.1749	−0.0424	136.4	28 544	−1 544c	
17 490	47 636	97.22	−28.87	107.37	111.19	0.2048	−0.0358	105.0	33 565	−1 565c	max
19 495	−1 495c	97.5	−14.61	123.31	124.17	0.2112	−0.0295	96.7	33 568	12 462	
20 500	−1 500c	96.83	−11.75	129.27	129.81	0.2124	−0.0267	95.1	33 569	13 465	
21 510	−1 509c	95.98	−8.12	134.59	134.83	0.214	−0.0241	93.4	34 570	13 468	
24 520	−1 520c	92.08	7.36	144.51	144.7	0.2211	−0.0178	87.0	34 574	14 474	Ym
26 530	−1 530c	88.38	20.31	146.42	147.82	0.2275	−0.0145	82.1	35 577	15 478	
28 540	−1 540c	83.93	34.2	141.8	145.87	0.235	−0.0119	76.4	36 581	16 481	
28 545	−1 544c	83.93	34.2	141.8	145.87	0.235	−0.0119	76.4	36 581	16 481	
30 550	−1 550c	78.77	48.19	134.27	142.66	0.2434	−0.0102	70.2	37 585	16 483	
30 555	−1 554c	78.77	48.19	134.27	142.66	0.2434	−0.0102	70.2	37 585	16 483	
32 560	−1 560c	72.97	61.4	124.87	139.15	0.2525	−0.0092	63.8	38 590	17 485	
33 565	0 405	71.32	65.08	112.25	129.75	0.2553	−0.0211	59.8	38 592	17 485	Rm
33 565	7 435	71.07	75.29	19.88	77.87	0.2614	−0.0692	14.7	−1 490c	18 490	
33 566	9 450	70.57	81.53	−2.69	81.57	0.2653	−0.0812	358.1	−1 495c	19 495	
33 568	11 460	69.99	87.29	−20.64	89.7	0.269	−0.0909	346.6	−1 502c	20 502	
33 569	12 465	69.42	90.28	−28.54	94.68	0.2711	−0.0952	342.4	−1 507c	21 507	
34 571	14 470	68.82	93.35	−39.87	101.51	0.2733	−0.1015	336.8	−1 520c	24 520	
34 574	15 475	67.31	96.05	−45.97	106.49	0.2759	−0.1053	334.4	−1 528c	25 528	Mm
35 579	16 480	64.5	99.59	−53.45	113.03	0.2802	−0.1105	331.7	−1 536c	27 536	
37 589	16 485	57.87	106.87	−64.87	125.01	0.2908	−0.1204	328.7	−1 544c	28 544	
47 636	17 490	31.87	98.12	−111.66	148.65	0.3213	−0.1878	311.3	−1 565c	33 565	min
−1 495c	19 495	30.21	63.32	−117.12	133.14	0.287	−0.1972	298.3	12 462	33 568	
−1 500c	20 500	33.93	47.38	−111.57	121.22	0.2657	−0.1833	293.0	13 465	33 569	
−1 509c	21 510	37.93	30.3	−105.34	109.61	0.2461	−0.1702	286.0	13 468	34 570	
−1 520c	24 520	50.83	−21.06	−84.16	86.75	0.2017	−0.1381	255.9	14 474	34 574	Bm
−1 530c	26 530	59.1	−47.73	−70.21	84.9	0.1856	−0.123	235.7	15 478	35 577	
−1 540c	28 540	66.58	−65.46	−57.47	87.11	0.1776	−0.112	221.2	16 481	36 581	
−1 544c	28 545	66.58	−65.46	−57.47	87.11	0.1776	−0.112	221.2	16 481	36 581	
−1 550c	30 550	73.2	−74.61	−46.12	87.72	0.1754	−0.1037	211.7	16 483	37 585	
−1 554c	30 555	73.2	−74.61	−46.12	87.72	0.1754	−0.1037	211.7	16 483	37 585	
−1 560c	32 560	78.98	−76.31	−36.2	84.46	0.1771	−0.0974	205.3	17 485	38 590	
380	770	100.0	0.0	0.0	0.0	0.2177	−0.0798	0.0			

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P45, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	33 566	80.19	−80.6	−33.27	87.2	0.176	−0.0918	202.4	17 487	38 593	Cm
7 435	33 567	80.37	−95.16	−14.37	96.24	0.1684	−0.083	188.5	18 491	−1 491c	
10 450	33 568	80.65	−108.48	8.6	108.82	0.1615	−0.0725	175.4	19 498	−1 498c	
12 460	33 569	80.99	−115.64	28.5	119.1	0.158	−0.0634	166.1	21 507	−1 507c	
13 465	34 570	81.34	−117.42	39.59	123.92	0.1573	−0.0584	161.3	22 512	−1 512c	
13 470	34 571	82.12	−114.86	40.91	121.93	0.1591	−0.0579	160.3	22 514	−1 514c	
15 475	34 574	82.87	−113.79	62.62	129.88	0.1601	−0.0483	151.1	25 528	−1 528c	Gm
15 480	35 578	84.81	−106.37	65.96	125.16	0.165	−0.0474	148.1	26 532	−1 532c	
17 485	37 587	87.37	−90.72	88.42	126.68	0.174	−0.0385	135.7	28 544	−1 544c	
17 490	42 611	94.08	−50.55	99.92	111.98	0.1952	−0.0361	116.8	31 559	−1 559c	max
19 495	−1 495c	97.73	−11.88	121.73	122.3	0.2132	−0.0289	95.5	33 569	12 463	
20 500	−1 500c	97.1	−9.19	127.84	128.17	0.2143	−0.0263	94.1	34 570	13 466	
22 510	−1 510c	95.29	−1.58	137.89	137.9	0.2177	−0.0214	90.6	34 572	14 471	
24 520	−1 520c	92.59	8.95	143.87	144.15	0.2226	−0.0176	86.4	34 574	15 475	Ym
26 530	−1 530c	89.04	21.42	147.61	149.16	0.2288	−0.0144	81.7	35 578	15 479	
27 540	−1 539c	86.98	28.1	145.84	148.53	0.2323	−0.013	79.0	35 579	16 480	
29 545	−1 545c	82.31	41.81	139.81	145.93	0.24	−0.0109	73.3	36 583	16 483	
29 550	−1 549c	82.31	41.81	139.81	145.93	0.24	−0.0109	73.3	36 583	16 483	
30 555	−1 554c	79.71	48.64	135.87	144.31	0.2442	−0.0101	70.3	37 585	16 484	
31 560	−1 559c	76.95	55.31	131.46	142.62	0.2486	−0.0096	67.1	37 588	17 485	
33 566	1 405	71.54	67.01	103.65	123.43	0.2573	−0.0238	57.1	38 593	17 487	Rm
33 567	7 435	71.33	75.3	22.16	78.49	0.2622	−0.0652	16.3	−1 491c	18 491	
33 568	10 450	70.99	82.55	−9.46	83.09	0.2666	−0.0812	353.4	−1 498c	19 498	
33 569	12 460	70.55	86.92	−25.45	90.57	0.2694	−0.0895	343.6	−1 507c	21 507	
34 570	13 465	70.11	88.96	−32.14	94.58	0.2709	−0.093	340.1	−1 512c	22 512	
34 571	13 470	69.1	90.69	−33.87	96.81	0.2725	−0.0941	339.5	−1 514c	22 514	
34 574	15 475	68.09	93.08	−43.97	102.95	0.2746	−0.0996	334.7	−1 528c	25 528	Mm
35 578	15 480	65.25	97.37	−48.86	108.94	0.2792	−0.1031	333.3	−1 532c	26 532	
37 587	17 485	60.99	99.61	−61.03	116.83	0.2841	−0.1116	328.5	−1 544c	28 544	
42 611	17 490	44.99	102.55	−88.6	135.52	0.3037	−0.1409	319.1	−1 559c	31 559	min
−1 495c	19 495	28.81	56.51	−119.25	131.96	0.2825	−0.1945	295.3	12 463	33 569	
−1 500c	20 500	32.52	40.63	−113.78	120.82	0.261	−0.1805	289.6	13 466	34 570	
−1 510c	22 510	40.74	5.93	−100.84	101.02	0.2238	−0.1553	273.3	14 471	34 572	
−1 520c	24 520	49.46	−27.74	−86.46	90.8	0.197	−0.135	252.2	15 475	34 574	Bm
−1 530c	26 530	57.8	−54.21	−72.43	90.47	0.1812	−0.1199	233.1	15 479	35 578	
−1 539c	27 540	61.69	−64.02	−65.82	91.82	0.1767	−0.114	225.7	16 480	35 579	
−1 545c	29 545	68.85	−76.87	−53.59	93.71	0.1725	−0.1044	214.8	16 483	36 583	
−1 549c	29 550	68.85	−76.87	−53.59	93.71	0.1725	−0.1044	214.8	16 483	36 583	
−1 554c	30 555	72.11	−80.15	−47.99	93.42	0.1723	−0.1006	210.9	16 484	37 585	
−1 559c	31 560	75.17	−81.55	−42.73	92.07	0.1731	−0.0972	207.6	17 485	37 588	
380	770	100.0	0.0	0.0	0.0	0.2185	−0.0764	0.0			

Ostwald-Optimalfarben (o) von maximalem (m) C _{AB} für P40, Y _w =100, Y _m =520_770																			
i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code								
0 405	33 568	79.95	−84.51	−34.12	91.14	0.1748	−0.0873	201.9	17 488	38 594	54 674	Cm							
7 435	33 568	80.1	−96.58	−15.98	97.9	0.1685	−0.0794	189.3	18 493	54 674									
10 450	33 569	80.34	−107.65	6.16	107.83	0.1627	−0.0697	176.7	19 499	−1 499c									
12 460	34 570	80.63	−113.5	25.58	116.35	0.1598	−0.0613	167.2	21 507	−1 507c									
13 465	34 571	80.91	−114.78	36.41	120.41	0.1593	−0.0566	162.3	22 512	−1 512c									
14 470	34 572	81.39	−114.41	47.53	123.89	0.1598	−0.0519	157.4	23 519	−1 519c									
14 475	34 574	82.45	−111.22	49.34	121.68	0.1621	−0.0513	156.0	24 522	−1 522c	Gm								
15 480	35 578	83.87	−105.72	61.75	122.43	0.1657	−0.0464	149.7	26 531	−1 531c									
17 485	37 585	86.02	−93.35	83.49	125.24	0.1731	−0.038	138.1	28 543	−1 543c									
17 490	40 600	91.25	−65.8	92.44	113.47	0.1884	−0.0362	125.4	30 554	−1 554c	max								
19 495	−1 495c	97.98	−9.02	119.65	119.99	0.2157	−0.0283	94.3	34 571	12 464									
20 500	−1 500c	97.41	−6.56	125.94	126.11	0.2168	−0.0257	92.9	34 571	13 467									
21 510	−1 509c	96.66	−3.4	131.64	131.68	0.2182	−0.0233	91.4	34 572	13 469									
24 520	−1 520c	93.2	10.4	142.94	143.32	0.2246	−0.0173	85.8	35 575	15 476	Ym								
26 530	−1 530c	89.83	22.28	149.05	150.71	0.2305	−0.0142	81.4	35 578	16 480									
27 540	−1 539c	87.86	28.7	147.39	150.16	0.2338	−0.0129	78.9	36 580	16 481									
29 545	−1 545c	83.37	41.99	141.62	147.72	0.2413	−0.0108	73.4	36 584	16 484									
29 550	−1 549c	83.37	41.99	141.62	147.72	0.2413	−0.0108	73.4	36 584	16 484									
31 555	−1 555c	78.17	55.22	133.54	144.51	0.2496	−0.0095	67.5	37 588	17 486									
32 560	−1 560c	75.32	61.53	128.87	142.81	0.2541	−0.0091	64.4	38 591	17 487									
33 568	0 405	71.84	68.49	117.18	135.73	0.2595	−0.0179	59.6	38 594	17 488	Rm								
33 568	7 435	71.65	75.18	25.05	79.24	0.2635	−0.0604	18.4	54 674	18 493									
33 569	10 450	71.37	81.14	−6.9	81.43	0.2671	−0.0757	355.1	−1 499c	19 499									
34 570	12 460	71.01	84.71	−23.18	87.82	0.2694	−0.0836	344.6	−1 507c	21 507									
34 571	13 465	70.66	86.26	−29.94	91.31	0.2705	−0.0869	340.8	−1 512c	22 512									
34 572	14 470	70.05	87.8	−35.89	94.85	0.2718	−0.0899	337.7	−1 519c	23 519									
34 574	14 475	68.66	90.25	−38.28	98.03	0.2741	−0.0914	337.0	−1 522c	24 522	Mm								
35 578	15 480	66.66	93.09	−45.56	103.65	0.2772	−0.0956	333.9	−1 531c	26 531									
37 585	17 485	63.33	95.05	−56.43	110.54	0.2808	−0.1023	329.3	−1 543c	28 543									
40 600	17 490	52.92	100.17	−74.36	124.76	0.2939	−0.1177	323.4	−1 554c	30 554	min								
−1 495c	19 495	27.1	48.32	−121.83	131.07	0.277	−0.1913	291.6	12 464	34 571									
−1 500c	20 500	30.79	32.53	−116.48	120.94	0.2552	−0.1771	285.6	13 467	34 571									
−1 509c	21 510	34.77	15.53	−110.39	111.48	0.2353	−0.1638	278.0	13 469	34 572									
−1 520c	24 520	47.74	−35.63	−89.33	96.18	0.1912	−0.1313	248.2	15 476	35 575	Bm								
−1 530c	26 530	56.15	−61.81	−75.22	97.36	0.176	−0.1162	230.5	16 480	35 578									
−1 539c	27 540	60.09	−71.38	−68.53	98.96	0.1719	−0.1102	223.8	16 481	36 580									
−1 545c	29 545	67.38	−83.62	−56.09	100.69	0.1686	−0.1007	213.8	16 484	36 584									
−1 549c	29 550	67.38	−83.62	−56.09	100.69	0.1686	−0.1007	213.8	16 484	36 584									
−1 555c	31 555	73.87	−87.57	−44.97	98.45	0.17	−0.0934	207.1	17 486	37 588									
−1 560c	32 560	76.81	−86.88	−39.92	95.61	0.172	−0.0905	204.6	17 487	38 591									
380	770	100.0	0.0	0.0	0.0	0.2197	−0.0724	0.0											

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P35, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	34 570	79.6	−89.05	−34.47	95.49	0.1738	−0.0816	201.1	18 490	39 596	Cm
7 435	34 570	79.72	−97.82	−18.06	99.47	0.1691	−0.0749	190.4	18 494	48 640	
9 450	34 571	79.96	−103.1	−4.65	103.2	0.1664	−0.0694	182.5	19 498	−1 498c	
12 460	34 572	80.13	−110.67	21.82	112.8	0.1625	−0.0586	168.8	21 507	−1 507c	
12 465	34 572	80.5	−109.66	22.44	111.94	0.1632	−0.0584	168.4	21 508	−1 508c	
14 470	34 573	80.76	−111.57	43.19	119.64	0.1624	−0.05	158.8	23 519	−1 519c	
14 475	35 575	81.62	−108.9	44.67	117.7	0.1643	−0.0496	157.6	24 520	−1 520c	Gm
15 480	35 578	82.78	−104.64	56.53	118.93	0.1672	−0.0451	151.6	25 529	−1 529c	
17 485	36 583	84.47	−95.01	77.44	122.57	0.173	−0.0373	140.8	28 542	−1 542c	
18 490	38 593	88.15	−75.14	91.83	118.66	0.1846	−0.0329	129.2	30 552	−1 552c	max
19 495	52 661	97.9	−8.98	116.21	116.55	0.2176	−0.0275	94.4	34 572	12 460	
20 500	−1 500c	97.76	−3.97	123.35	123.41	0.2199	−0.025	91.8	34 573	13 468	
22 510	−1 510c	96.24	2.41	134.39	134.41	0.2228	−0.0206	88.9	34 574	14 473	
23 520	−1 519c	95.18	6.67	138.42	138.58	0.2248	−0.0187	87.2	35 576	15 475	Ym
26 530	−1 530c	90.79	22.67	150.81	152.51	0.2326	−0.014	81.4	35 579	16 481	
27 540	−1 539c	88.93	28.75	149.28	152.02	0.2358	−0.0127	79.0	36 581	16 483	
29 545	−1 545c	84.67	41.49	143.85	149.71	0.2429	−0.0107	73.9	37 585	17 486	
29 550	−1 549c	84.67	41.49	143.85	149.71	0.2429	−0.0107	73.9	37 585	17 486	
31 555	−1 555c	79.69	54.35	136.13	146.58	0.2509	−0.0095	68.2	37 589	17 488	
32 560	−1 560c	76.94	60.55	131.62	144.88	0.2552	−0.0091	65.2	38 591	17 489	
34 570	1 405	72.25	69.9	108.28	128.89	0.2625	−0.0194	57.1	39 596	18 490	Rm
34 570	7 435	72.11	74.62	28.87	80.01	0.2653	−0.0547	21.1	48 640	18 494	
34 571	9 450	71.82	77.87	5.94	78.09	0.2673	−0.0648	4.3	−1 498c	19 498	
34 572	12 460	71.61	81.82	−20.16	84.27	0.2698	−0.0765	346.1	−1 507c	21 507	
34 572	12 465	71.17	82.58	−20.91	85.19	0.2704	−0.0769	345.7	−1 508c	21 508	
34 573	14 470	70.85	84.32	−33.08	90.58	0.2717	−0.0824	338.5	−1 519c	23 519	
35 575	14 475	69.76	86.12	−34.96	92.94	0.2734	−0.0835	337.9	−1 520c	24 520	Mm
35 578	15 480	68.21	88.29	−41.7	97.64	0.2756	−0.0869	334.7	−1 529c	25 529	
36 583	17 485	65.78	89.55	−51.39	103.25	0.278	−0.0921	330.1	−1 542c	28 542	
38 593	18 490	59.56	91.85	−63.93	111.91	0.2842	−0.1006	325.1	−1 552c	30 552	min
52 661	19 495	27.69	47.15	−120.29	129.2	0.2773	−0.1754	291.4	12 460	34 572	
−1 500c	20 500	28.6	22.83	−119.84	121.99	0.2481	−0.1728	280.7	13 468	34 573	
−1 510c	22 510	36.77	−11.57	−107.28	107.9	0.2104	−0.1472	263.8	14 473	34 574	
−1 519c	23 520	41.14	−28.86	−100.22	104.3	0.1957	−0.1362	253.9	15 475	35 576	Bm
−1 530c	26 530	54.01	−70.63	−78.81	105.83	0.1698	−0.1116	228.1	16 481	35 579	
−1 539c	27 540	58.02	−79.87	−72.05	107.56	0.1662	−0.1056	222.0	16 483	36 581	
−1 545c	29 545	65.46	−91.3	−59.37	108.91	0.164	−0.096	213.0	17 486	37 585	
−1 549c	29 550	65.46	−91.3	−59.37	108.91	0.164	−0.096	213.0	17 486	37 585	
−1 555c	31 555	72.14	−94.39	−47.93	105.86	0.1666	−0.0888	206.9	17 488	37 589	
−1 560c	32 560	75.19	−93.26	−42.69	102.57	0.1691	−0.0858	204.5	17 489	38 591	
380	770	100.0	0.0	0.0	0.0	0.2217	−0.0675	0.0			

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P30, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	34 573	79.06	−92.29	−35.75	98.97	0.1741	−0.0748	201.1	18 493	39 598	Cm
6 435	34 573	79.18	−96.4	−25.52	99.72	0.1719	−0.071	194.8	19 495	42 612	
10 450	34 573	79.31	−104.18	−1.07	104.19	0.1677	−0.0618	180.5	20 502	−1 502c	
12 460	34 574	79.48	−107.49	16.89	108.81	0.166	−0.0551	171.0	21 508	−1 508c	
13 465	34 574	79.66	−108.35	27.05	111.68	0.1657	−0.0513	165.9	22 512	−1 512c	
14 470	35 575	79.95	−108.0	37.47	114.32	0.166	−0.0475	160.8	23 518	−1 518c	
15 475	35 576	80.43	−106.24	48.04	116.6	0.1673	−0.0437	155.6	25 525	−1 525c	Gm
16 480	35 579	81.28	−102.72	58.74	118.33	0.1697	−0.0399	150.2	26 533	−1 533c	
17 485	36 582	82.72	−95.86	69.87	118.63	0.1741	−0.0362	143.9	28 540	−1 540c	
18 490	37 589	85.35	−82.99	82.5	117.02	0.1821	−0.0324	135.1	29 549	−1 549c	max
19 495	41 606	90.85	−52.17	99.6	112.43	0.1993	−0.0282	117.6	32 561	−1 561c	
20 500	−1 500c	98.17	−1.61	119.65	119.66	0.224	−0.024	90.7	35 575	13 469	
21 510	−1 509c	97.59	0.84	125.91	125.91	0.2252	−0.0219	89.6	35 576	14 472	
24 520	−1 520c	94.78	12.07	139.33	139.85	0.2305	−0.0166	85.0	35 578	15 479	Ym
25 530	−1 529c	93.46	16.94	142.19	143.2	0.2328	−0.0151	83.2	36 580	16 481	
28 540	−1 540c	88.37	33.76	149.47	153.23	0.2416	−0.0114	77.2	36 584	17 486	
29 545	−1 545c	86.3	39.85	146.64	151.96	0.2451	−0.0105	74.7	37 586	17 488	
30 550	−1 550c	84.05	46.02	143.26	150.47	0.2488	−0.0099	72.1	37 588	17 489	
31 555	−1 555c	81.61	52.19	139.39	148.85	0.2527	−0.0094	69.4	38 590	18 490	
32 560	−1 560c	78.99	58.24	135.11	147.13	0.2568	−0.009	66.6	38 592	18 491	
34 573	0 405	72.87	70.02	122.48	141.09	0.2659	−0.0138	60.2	39 598	18 493	Rm
34 573	6 435	72.74	72.34	47.26	86.42	0.2673	−0.0424	33.1	42 612	19 495	
34 573	10 450	72.59	76.31	1.25	76.32	0.2697	−0.0609	0.9	−1 502c	20 502	
34 574	12 460	72.39	78.32	−16.01	79.94	0.271	−0.0679	348.4	−1 508c	21 508	
34 574	13 465	72.18	79.27	−23.18	82.59	0.2717	−0.0708	343.6	−1 512c	22 512	
35 575	14 470	71.84	80.03	−29.31	85.23	0.2723	−0.0733	339.8	−1 518c	23 518	
35 576	15 475	71.25	80.82	−34.73	87.97	0.2731	−0.0756	336.7	−1 525c	25 525	Mm
35 579	16 480	70.2	81.98	−39.96	91.2	0.2744	−0.078	334.0	−1 533c	26 533	
36 582	17 485	68.29	83.46	−45.88	95.24	0.2764	−0.0808	331.2	−1 540c	28 540	
37 589	18 490	64.41	85.54	−54.6	101.49	0.2803	−0.0857	327.4	−1 549c	29 549	min
41 606	19 495	53.86	83.47	−74.37	111.79	0.2871	−0.0994	318.2	−1 561c	32 561	
−1 500c	20 500	25.77	11.31	−124.08	124.59	0.2389	−0.1675	275.2	13 469	35 575	
−1 509c	21 510	29.68	−5.34	−118.35	118.47	0.2187	−0.1539	267.4	14 472	35 576	
−1 520c	24 520	42.61	−55.59	−97.8	112.5	0.1752	−0.121	240.3	15 479	35 578	Bm
−1 529c	25 530	46.94	−69.3	−90.64	114.1	0.1673	−0.1128	232.5	16 481	36 580	
−1 540c	28 540	59.13	−95.65	−70.15	118.62	0.1583	−0.0947	216.2	17 486	36 584	
−1 545c	29 545	62.85	−99.71	−63.81	118.38	0.1588	−0.0903	212.6	17 488	37 586	
−1 550c	30 550	66.4	−101.68	−57.74	116.94	0.1604	−0.0864	209.5	17 489	37 588	
−1 555c	31 555	69.77	−101.78	−51.97	114.28	0.1629	−0.083	207.0	18 490	38 590	
−1 560c	32 560	72.96	−100.19	−46.5	110.46	0.166	−0.0801	204.8	18 491	38 592	
380	770	100.0	0.0	0.0	0.0	0.2248	−0.0614	0.0			

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für P25, Y_w=100, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
1 405	35 576	78.24	−94.34	−37.02	101.35	0.1763	−0.0661	201.4	19 497	40 601	Cm
6 435	35 576	78.32	−96.46	−28.68	100.63	0.1751	−0.0633	196.5	19 499	42 611	
10 450	35 577	78.4	−100.94	−6.7	101.17	0.1726	−0.056	183.8	20 504	−1 504c	
11 460	35 577	78.58	−101.68	1.38	101.69	0.1723	−0.0534	179.2	21 506	−1 506c	
13 465	35 577	78.64	−103.32	19.67	105.18	0.1714	−0.0473	169.2	22 513	−1 513c	
14 470	35 578	78.84	−103.15	29.58	107.31	0.1717	−0.0441	163.9	23 518	−1 518c	
15 475	35 579	79.17	−102.15	39.61	109.56	0.1724	−0.0408	158.8	24 524	−1 524c	Gm
16 480	36 580	79.74	−99.8	49.68	111.48	0.1741	−0.0376	153.5	26 531	−1 531c	
17 485	36 582	80.7	−95.27	59.92	112.54	0.1771	−0.0345	147.8	27 539	−1 539c	
18 490	37 586	82.42	−87.46	70.97	112.63	0.1823	−0.0313	140.9	29 546	−1 546c	max
18 495	38 594	85.95	−73.66	76.97	106.54	0.1911	−0.0302	133.7	30 553	−1 553c	
20 500	44 620	93.35	−30.34	104.98	109.28	0.2148	−0.0238	106.1	34 570	−1 570c	
21 510	−1 509c	98.16	2.19	120.67	120.69	0.2306	−0.0208	88.9	35 578	14 474	
24 520	−1 520c	95.82	11.59	135.58	136.08	0.2351	−0.0159	85.1	36 581	16 481	Ym
25 530	−1 529c	94.69	15.79	139.05	139.94	0.2372	−0.0145	83.5	36 582	16 484	
28 540	−1 540c	90.22	30.79	152.71	155.79	0.2451	−0.0111	78.6	37 586	17 489	
28 545	−1 544c	90.22	30.79	152.71	155.79	0.2451	−0.0111	78.6	37 586	17 489	
29 550	−1 549c	88.37	36.37	150.2	154.54	0.2482	−0.0103	76.3	37 588	18 491	
30 555	−1 554c	86.32	42.11	147.15	153.05	0.2516	−0.0097	74.0	37 589	18 492	
32 560	−1 560c	81.65	53.73	139.66	149.64	0.2589	−0.0089	68.9	38 594	18 494	
35 576	1 405	73.8	68.72	124.19	141.93	0.2704	−0.0135	61.0	40 601	19 497	Rm
35 576	6 435	73.71	69.92	54.67	88.76	0.2712	−0.0348	38.0	42 611	19 499	
35 577	10 450	73.61	72.2	8.18	72.66	0.2726	−0.051	6.4	−1 504c	20 504	
35 577	11 460	73.42	73.02	−1.52	73.04	0.2731	−0.0543	358.8	−1 506c	21 506	
35 577	13 465	73.35	73.94	−17.46	75.97	0.2737	−0.0599	346.7	−1 513c	22 513	
35 578	14 470	73.13	74.44	−23.89	78.19	0.2741	−0.0622	342.2	−1 518c	23 518	
35 579	15 475	72.74	74.99	−29.42	80.56	0.2747	−0.0642	338.5	−1 524c	24 524	Mm
36 580	16 480	72.08	75.62	−34.41	83.08	0.2754	−0.066	335.5	−1 531c	26 531	
36 582	17 485	70.92	76.39	−39.42	85.97	0.2765	−0.068	332.7	−1 539c	27 539	
37 586	18 490	68.7	77.69	−45.6	90.08	0.2785	−0.0706	329.5	−1 546c	29 546	min
38 594	18 495	63.43	81.3	−54.66	97.97	0.2842	−0.0753	326.0	−1 553c	30 553	
44 620	20 500	47.27	67.08	−85.93	109.01	0.2861	−0.0963	307.9	−1 570c	34 570	
−1 509c	21 510	25.81	−18.19	−124.15	125.48	0.2064	−0.1467	261.6	14 474	35 578	
−1 520c	24 520	38.59	−67.19	−104.31	124.08	0.1639	−0.1135	237.2	16 481	36 581	Bm
−1 529c	25 530	42.92	−80.33	−97.24	126.13	0.1569	−0.1054	230.4	16 484	36 582	
−1 540c	28 540	55.3	−104.6	−76.61	129.66	0.1514	−0.0874	216.2	17 489	37 586	
−1 544c	28 545	55.3	−104.6	−76.61	129.66	0.1514	−0.0874	216.2	17 489	37 586	
−1 549c	29 550	59.14	−108.01	−70.1	128.77	0.153	−0.083	212.9	18 491	37 588	
−1 554c	30 555	62.82	−109.41	−63.82	126.67	0.1556	−0.0791	210.2	18 492	37 589	
−1 560c	32 560	69.72	−107.0	−52.03	118.98	0.1631	−0.0728	205.9	18 494	38 594	
380	770	100.0	0.0	0.0	0.0	0.2296	−0.0538	0.0			