

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB,10} für D65, Y_{w,10}=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	X ₁₀	Y ₁₀	Z ₁₀	x ₁₀	y ₁₀	z ₁₀	h _{xy,10}	i _d , λ _d	i _c , λ _c	Code
0 405	31 556	28.12	50.11	94.37	0.1629	0.2903	0.5467	195.0	15 476	37 585	Cm
6 435	31 557	24.8	50.86	74.08	0.1656	0.3396	0.4947	176.6	16 480	44 621	
10 450	31 559	19.54	50.96	41.21	0.1749	0.4561	0.3689	137.9	18 491	-1 491c	
11 460	32 562	19.75	52.51	33.04	0.1875	0.4986	0.3137	126.9	19 498	-1 498c	
12 465	33 565	20.22	53.96	25.67	0.2025	0.5403	0.2571	117.9	21 506	-1 506c	
14 470	34 570	21.81	55.87	14.19	0.2373	0.6081	0.1544	105.3	24 522	-1 522c	
15 475	35 579	27.93	60.81	10.22	0.2822	0.6144	0.1032	96.3	26 533	-1 533c	Gm
16 480	41 606	47.87	72.59	7.29	0.3746	0.5682	0.0571	75.5	30 550	-1 550c	
16 485	-1 484c	68.26	81.76	7.29	0.4339	0.5197	0.0463	57.5	32 560	10 454	
18 490	-1 490c	68.1	78.9	3.72	0.4518	0.5234	0.0247	54.3	32 562	11 459	max
19 495	-1 495c	68.08	77.11	2.63	0.4605	0.5216	0.0178	52.4	32 563	12 461	
19 500	-1 499c	68.08	77.11	2.63	0.4605	0.5216	0.0178	52.4	32 563	12 461	
22 510	-1 510c	67.71	70.07	0.89	0.4882	0.5052	0.0064	44.9	33 566	13 466	
23 520	-1 519c	67.33	67.16	0.6	0.4983	0.4971	0.0045	41.9	33 568	13 468	Ym
26 530	-1 530c	64.81	56.85	0.14	0.532	0.4667	0.0012	31.8	34 573	14 472	
27 540	-1 539c	63.44	53.07	0.07	0.5441	0.4551	0.0006	28.3	35 576	14 473	
28 545	-1 544c	61.79	49.2	0.03	0.5565	0.4431	0.0003	24.7	35 578	14 474	
29 550	-1 549c	59.85	45.28	0.01	0.5691	0.4306	0.0001	21.3	36 580	15 475	
31 555	-1 555c	55.06	37.53	0.0	0.5946	0.4053	0.0	14.8	37 586	15 476	
32 560	10 451	62.45	35.47	51.78	0.4171	0.2369	0.3458	317.7	-1 492c	18 492	
31 556	0 405	66.68	49.88	12.95	0.5148	0.3851	0.1	15.0	37 585	15 476	Rm
31 557	6 435	70.0	49.13	33.24	0.4594	0.3224	0.2181	356.6	44 621	16 480	
31 559	10 450	75.26	49.03	66.11	0.3952	0.2575	0.3472	317.9	-1 491c	18 491	
32 562	11 460	75.06	47.48	74.29	0.3813	0.2412	0.3774	307.0	-1 498c	19 498	
33 565	12 465	74.58	46.03	81.65	0.3687	0.2275	0.4036	298.0	-1 506c	21 506	
34 570	14 470	73.0	44.12	93.14	0.3471	0.2098	0.4429	285.4	-1 522c	24 522	
35 579	15 475	66.88	39.18	97.11	0.3291	0.1928	0.4779	276.3	-1 533c	26 533	Mm
41 606	16 480	46.93	27.4	100.03	0.2691	0.1571	0.5736	255.6	-1 550c	30 550	
-1 484c	16 485	26.54	18.23	100.03	0.1833	0.1258	0.6907	237.5	10 454	32 560	
-1 490c	18 490	26.71	21.09	103.61	0.1764	0.1393	0.6842	234.3	11 459	32 562	min
-1 495c	19 495	26.73	22.88	104.69	0.1732	0.1482	0.6784	232.4	12 461	32 563	
-1 499c	19 500	26.73	22.88	104.69	0.1732	0.1482	0.6784	232.4	12 461	32 563	
-1 510c	22 510	27.1	29.92	106.43	0.1657	0.183	0.6511	225.0	13 466	33 566	
-1 519c	23 520	27.48	32.83	106.72	0.1645	0.1965	0.6389	222.0	13 468	33 568	Bm
-1 530c	26 530	30.0	43.14	107.18	0.1663	0.2392	0.5943	211.8	14 472	34 573	
-1 539c	27 540	31.36	46.92	107.25	0.169	0.2529	0.578	208.3	14 473	35 576	
-1 544c	28 545	33.01	50.79	107.29	0.1727	0.2657	0.5614	204.8	14 474	35 578	
-1 549c	29 550	34.96	54.71	107.32	0.1774	0.2777	0.5447	201.3	15 475	36 580	
-1 555c	31 555	39.75	62.46	107.33	0.1896	0.298	0.5122	194.8	15 476	37 586	
10 451	32 560	32.36	64.52	55.55	0.2122	0.4232	0.3644	137.6	18 492	-1 492c	
380	770	83.99	88.59	95.08	0.3137	0.3309	0.3552	0.0			