

Ostwald-Optimalfarben (o) von maximalem (m) C_{AB} für D65, Y_w=88,6, Y_m=520_770

i ₁ , λ ₁	i ₂ , λ ₂	L*	a*	b*	C* _{ab}	a'	b'	h _{ab}	i _d , λ _d	i _c , λ _c	Code
0 405	32 561	77.02	−64.87	−31.25	72.01	0.1805	−0.1029	205.7	16 483	37 589	Cm
6 435	32 562	77.34	−78.65	−18.49	80.79	0.1732	−0.096	193.2	17 486	42 610	
10 450	32 563	77.66	−104.74	10.98	105.32	0.1595	−0.0803	174.0	19 496	−1 496c	
12 460	33 565	78.13	−115.96	31.94	120.28	0.1538	−0.0692	164.5	21 505	−1 505c	
12 465	33 567	78.83	−114.06	33.13	118.77	0.1552	−0.0687	163.8	21 506	−1 506c	
14 470	33 569	79.37	−118.58	55.25	130.82	0.1532	−0.0572	155.0	24 520	−1 520c	
15 475	34 573	80.65	−114.03	67.6	132.56	0.1564	−0.0512	149.3	25 528	−1 528c	Gm
16 480	36 580	82.9	−102.97	80.87	130.93	0.1633	−0.0452	141.8	27 537	−1 537c	
17 485	39 595	86.88	−77.35	96.11	123.37	0.1778	−0.0394	128.8	29 548	−1 548c	
18 490	−1 490c	93.06	−22.24	114.34	116.48	0.2052	−0.0337	101.0	33 565	11 459	max
19 495	−1 495c	92.47	−19.81	120.45	122.06	0.2062	−0.0306	99.3	33 566	12 462	
20 500	−1 500c	91.73	−16.65	125.95	127.04	0.2076	−0.0277	97.5	33 567	12 464	
22 510	−1 510c	89.65	−7.92	134.61	134.84	0.2116	−0.0224	93.3	33 569	13 469	
23 520	−1 519c	88.27	−2.43	137.31	137.33	0.2142	−0.0202	91.0	34 570	14 471	Ym
25 530	−1 529c	84.79	10.36	138.25	138.64	0.2205	−0.0165	85.7	34 573	15 475	
27 540	−1 539c	80.46	24.53	135.02	137.23	0.2281	−0.0134	79.7	35 577	15 478	
28 545	−1 544c	78.04	31.74	131.99	135.75	0.2322	−0.0121	76.4	35 579	15 479	
29 550	−1 549c	75.43	38.97	128.25	134.04	0.2367	−0.0111	73.0	36 582	16 480	
30 555	−1 554c	72.66	46.06	123.97	132.25	0.2413	−0.0103	69.6	36 584	16 481	
32 560	−1 560c	66.77	59.19	114.35	128.76	0.2511	−0.0093	62.6	37 589	16 483	
32 561	0 405	75.1	50.51	58.31	77.15	0.2431	−0.0541	49.1	37 589	16 483	Rm
32 562	6 435	74.77	58.71	25.94	64.18	0.2477	−0.0718	23.8	42 610	17 486	
32 563	10 450	74.42	71.74	−10.3	72.47	0.255	−0.0918	351.8	−1 496c	19 496	
33 565	12 460	73.91	77.65	−24.5	81.42	0.2585	−0.0997	342.4	−1 505c	21 505	
33 567	12 465	73.14	79.04	−25.83	83.15	0.2597	−0.1006	341.9	−1 506c	21 506	
33 569	14 470	72.52	82.59	−35.89	90.05	0.262	−0.1064	336.5	−1 520c	24 520	
34 573	15 475	70.98	85.03	−41.59	94.66	0.2642	−0.11	333.9	−1 528c	25 528	Mm
36 580	16 480	68.04	87.88	−48.91	100.57	0.2676	−0.1152	330.9	−1 537c	27 537	
39 595	17 485	61.86	87.86	−61.19	107.07	0.2718	−0.1254	325.1	−1 548c	29 548	
−1 490c	18 490	48.14	51.23	−86.03	100.13	0.2553	−0.1532	300.7	11 459	33 565	min
−1 495c	19 495	49.78	44.33	−84.1	95.07	0.2491	−0.15	297.7	12 462	33 566	
−1 500c	20 500	51.73	36.01	−81.43	89.04	0.242	−0.1462	293.8	12 464	33 567	
−1 510c	22 510	56.54	15.71	−74.03	75.68	0.2262	−0.1371	281.9	13 469	33 569	
−1 519c	23 520	59.32	4.57	−69.51	69.66	0.2184	−0.1323	273.7	14 471	34 570	Bm
−1 529c	25 530	65.28	−17.14	−59.54	61.96	0.2048	−0.1227	253.9	15 475	34 573	
−1 539c	27 540	71.22	−34.96	−49.47	60.58	0.1953	−0.1145	234.7	15 478	35 577	
−1 544c	28 545	74.02	−41.75	−44.69	61.16	0.1922	−0.1109	226.9	15 479	35 579	
−1 549c	29 550	76.7	−47.12	−40.09	61.87	0.19	−0.1077	220.3	16 480	36 582	
−1 554c	30 555	79.24	−51.0	−35.73	62.27	0.1886	−0.1049	215.0	16 481	36 584	
−1 560c	32 560	83.79	−54.46	−27.9	61.19	0.1881	−0.1001	207.1	16 483	37 589	
380	770	95.41	0.0	0.0	0.0	0.2154	−0.0861	0.0			